

# Ammunitions with Inert Projectile (Cartridges for Small Arms)

## TSA OUTDOORS

Chemwatch Hazard Alert Code: 3

Chemwatch: 5534-26

Version No: 2.1

Safety Data Sheet according to WHS Regulations (Hazardous Chemicals) Amendment 2020 and ADG requirements

Issue Date: 14/03/2022

Print Date: 15/03/2022

S.GHS.AUS.EN

### SECTION 1 Identification of the substance / mixture and of the company / undertaking

#### Product Identifier

<b>Product name</b>	Ammunitions with Inert Projectile (Cartridges for Small Arms)
<b>Chemical Name</b>	Not Applicable
<b>Synonyms</b>	Not Available
<b>Proper shipping name</b>	CARTRIDGES FOR WEAPONS, INERT PROJECTILE or CARTRIDGES, SMALL ARMS
<b>Chemical formula</b>	Not Applicable
<b>Other means of identification</b>	Not Available

#### Relevant identified uses of the substance or mixture and uses advised against

<b>Relevant identified uses</b>	Cal.22 cartridges.
---------------------------------	--------------------

#### Details of the supplier of the safety data sheet

<b>Registered company name</b>	<b>TSA OUTDOORS</b>
<b>Address</b>	Unit 6/ 9 - 13 Winbourne Road Brookvale NSW 2100 Australia
<b>Telephone</b>	+61 2 9938 3244
<b>Fax</b>	+61 2 9939 2972
<b>Website</b>	<a href="http://Tsaoutdoors.com.au">Tsaoutdoors.com.au</a>
<b>Email</b>	sales@tasco.com.au

#### Emergency telephone number

<b>Association / Organisation</b>	<b>Aaron Millard</b>	<b>CHEMWATCH EMERGENCY RESPONSE</b>
<b>Emergency telephone numbers</b>	+61 450 086 593 (Mon-Fri, 9 am-6pm)	+61 1800 951 288
<b>Other emergency telephone numbers</b>	Not Available	+61 2 9186 1132

Once connected and if the message is not in your preferred language then please dial 01

### SECTION 2 Hazards identification

#### Classification of the substance or mixture

<b>Poisons Schedule</b>	Not Applicable
<b>Classification [1]</b>	Explosives Division 1.4, Acute Toxicity (Oral) Category 4, Acute Toxicity (Dermal) Category 3, Sensitisation (Skin) Category 1, Serious Eye Damage/Eye Irritation Category 2A, Acute Toxicity (Inhalation) Category 2, Reproductive Toxicity Category 1A, Reproductive Toxicity Effects on or via Lactation, Hazardous to the Aquatic Environment Acute Hazard Category 3, Hazardous to the Aquatic Environment Long-Term Hazard Category 2
<b>Legend:</b>	1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI

#### Label elements

<b>Hazard pictogram(s)</b>	
<b>Signal word</b>	<b>Danger</b>

#### Hazard statement(s)

<b>H204</b>	Fire or projection hazard.
<b>H302</b>	Harmful if swallowed.
<b>H311</b>	Toxic in contact with skin.
<b>H317</b>	May cause an allergic skin reaction.

## Ammunitions with Inert Projectile (Cartridges for Small Arms)

<b>H319</b>	Causes serious eye irritation.
<b>H330</b>	Fatal if inhaled.
<b>H360Df</b>	May damage the unborn child. Suspected of damaging fertility.
<b>H362</b>	May cause harm to breast-fed children.
<b>H402</b>	Harmful to aquatic life.
<b>H411</b>	Toxic to aquatic life with long lasting effects.

### Precautionary statement(s) Prevention

<b>P201</b>	Obtain special instructions before use.
<b>P210</b>	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
<b>P234</b>	Keep only in original packaging.
<b>P250</b>	Do not subject to grinding/shock/sources of friction.
<b>P260</b>	Do not breathe dust/fume.
<b>P263</b>	Avoid contact during pregnancy and while nursing.
<b>P271</b>	Use only outdoors or in a well-ventilated area.
<b>P280</b>	Wear protective gloves, protective clothing, eye protection, face protection and hearing protection.
<b>P240</b>	Ground and bond container and receiving equipment.
<b>P270</b>	Do not eat, drink or smoke when using this product.
<b>P264</b>	Wash all exposed external body areas thoroughly after handling.
<b>P273</b>	Avoid release to the environment.
<b>P284</b>	[In case of inadequate ventilation] wear respiratory protection.
<b>P272</b>	Contaminated work clothing should not be allowed out of the workplace.

### Precautionary statement(s) Response

<b>P304+P340</b>	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
<b>P308+P313</b>	IF exposed or concerned: Get medical advice/ attention.
<b>P310</b>	Immediately call a POISON CENTER/doctor/physician/first aider.
<b>P370+P372+P380+P373</b>	In case of fire: Explosion risk. Evacuate area. DO NOT fight fire when fire reaches explosives.
<b>P370+P380+P375</b>	In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion.
<b>P302+P352</b>	IF ON SKIN: Wash with plenty of water and soap.
<b>P305+P351+P338</b>	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
<b>P333+P313</b>	If skin irritation or rash occurs: Get medical advice/attention.
<b>P337+P313</b>	If eye irritation persists: Get medical advice/attention.
<b>P361+P364</b>	Take off immediately all contaminated clothing and wash it before reuse.
<b>P391</b>	Collect spillage.
<b>P301+P312</b>	IF SWALLOWED: Call a POISON CENTER/doctor/physician/first aider if you feel unwell.
<b>P330</b>	Rinse mouth.

### Precautionary statement(s) Storage

<b>P403+P233</b>	Store in a well-ventilated place. Keep container tightly closed.
<b>P405</b>	Store locked up.
<b>P401</b>	Store in accordance with local/regional/national/international regulations.

### Precautionary statement(s) Disposal

<b>P501</b>	Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.
<b>P503</b>	Refer to manufacturer or supplier for information on disposal/recovery/recycling.

## SECTION 3 Composition / information on ingredients

### Substances

See section below for composition of Mixtures

### Mixtures

CAS No	%[weight]	Name
7439-92-1	50-75	lead
7440-50-8	10-20	copper
7440-66-6	5-10	zinc
9004-70-0	0-5	nitrocellulose
63918-97-8	0-1	lead styphnate
109-27-3	0-1	tetrazene
78-11-5	0-1	pentaerythritol tetranitrate

## Ammunitions with Inert Projectile (Cartridges for Small Arms)

CAS No	%[weight]	Name
55-63-0	0-1	<u>nitroglycerin</u>
1309-60-0	0-1	<u>lead dioxide</u>
10022-31-8	0-1	<u>barium nitrate</u>
1345-04-6	0-1	<u>antimony trisulfide</u>
7727-43-7	0-1	<u>barium sulfate</u>
7429-90-5	0-1	<u>aluminium</u>

**Legend:** 1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. Classification drawn from C&L; \* EU IOELVs available

## SECTION 4 First aid measures

## Description of first aid measures

<b>Eye Contact</b>	<p>If this product comes in contact with the eyes:</p> <ul style="list-style-type: none"> <li>▶ Immediately hold eyelids apart and flush the eye continuously with running water.</li> <li>▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.</li> <li>▶ Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.</li> <li>▶ Transport to hospital or doctor without delay.</li> <li>▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.</li> <li>▶ <b>DO NOT attempt to remove particles attached to or embedded in eye .</b></li> <li>▶ Lay victim down, on stretcher if available and pad <b>BOTH</b> eyes, make sure dressing does not press on the injured eye by placing thick pads under dressing, above and below the eye.</li> <li>▶ Seek urgent medical assistance, or transport to hospital.</li> </ul>
<b>Skin Contact</b>	<p>If skin or hair contact occurs:</p> <ul style="list-style-type: none"> <li>▶ Immediately flush body and clothes with large amounts of water, using safety shower if available.</li> <li>▶ Quickly remove all contaminated clothing, including footwear.</li> <li>▶ Wash skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre.</li> <li>▶ Transport to hospital, or doctor.</li> <li>▶ Immediately wash contaminated skin with plenty of soap and water.</li> <li>▶ Immediately seek medical advice.</li> <li>▶ Wearing gloves, remove all contaminated clothing and loosen remaining clothing.</li> <li>▶ Allow patient to assume comfortable position, keep warm.</li> <li>▶ Keep at rest until fully recovered.</li> <li>▶ If breathing has stopped or is shallow apply artificial respiration at once.</li> <li>▶ In the event of cardiac arrest apply external cardiac massage.</li> <li>▶ If breathing is laboured and patient cyanotic (blue), ensure airways are clear and have qualified person give oxygen through a face mask.</li> </ul> <p>For thermal burns:</p> <ul style="list-style-type: none"> <li>▶ Decontaminate area around burn.</li> <li>▶ Consider the use of cold packs and topical antibiotics.</li> </ul> <p>For first-degree burns (affecting top layer of skin)</p> <ul style="list-style-type: none"> <li>▶ Hold burned skin under cool (not cold) running water or immerse in cool water until pain subsides.</li> <li>▶ Use compresses if running water is not available.</li> <li>▶ Cover with sterile non-adhesive bandage or clean cloth.</li> <li>▶ Do NOT apply butter or ointments; this may cause infection.</li> <li>▶ Give over-the counter pain relievers if pain increases or swelling, redness, fever occur.</li> </ul> <p>For second-degree burns (affecting top two layers of skin)</p> <ul style="list-style-type: none"> <li>▶ Cool the burn by immerse in cold running water for 10-15 minutes.</li> <li>▶ Use compresses if running water is not available.</li> <li>▶ Do NOT apply ice as this may lower body temperature and cause further damage.</li> <li>▶ Do NOT break blisters or apply butter or ointments; this may cause infection.</li> <li>▶ Protect burn by cover loosely with sterile, nonstick bandage and secure in place with gauze or tape.</li> </ul> <p>To prevent shock: (unless the person has a head, neck, or leg injury, or it would cause discomfort):</p> <ul style="list-style-type: none"> <li>▶ Lay the person flat.</li> <li>▶ Elevate feet about 12 inches.</li> <li>▶ Elevate burn area above heart level, if possible.</li> <li>▶ Cover the person with coat or blanket.</li> <li>▶ Seek medical assistance.</li> </ul> <p>For third-degree burns Seek immediate medical or emergency assistance.</p> <p>In the mean time:</p> <ul style="list-style-type: none"> <li>▶ Protect burn area cover loosely with sterile, nonstick bandage or, for large areas, a sheet or other material that will not leave lint in wound.</li> <li>▶ Separate burned toes and fingers with dry, sterile dressings.</li> <li>▶ Do not soak burn in water or apply ointments or butter; this may cause infection.</li> <li>▶ To prevent shock see above.</li> <li>▶ For an airway burn, do not place pillow under the person's head when the person is lying down. This can close the airway.</li> <li>▶ Have a person with a facial burn sit up.</li> <li>▶ Check pulse and breathing to monitor for shock until emergency help arrives.</li> </ul>
<b>Inhalation</b>	<ul style="list-style-type: none"> <li>▶ If fumes or combustion products are inhaled remove from contaminated area.</li> <li>▶ Lay patient down. Keep warm and rested.</li> <li>▶ Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.</li> <li>▶ Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.</li> <li>▶ Transport to hospital, or doctor, without delay.</li> <li>▶ Remove victim from exposure - avoid becoming a casualty.</li> <li>▶ Seek immediate medical advice and treat as for skin absorption.</li> </ul>
<b>Ingestion</b>	<ul style="list-style-type: none"> <li>▶ Give a slurry of activated charcoal in water to drink. <b>NEVER GIVE AN UNCONSCIOUS PATIENT WATER TO DRINK.</b></li> <li>▶ At least 3 tablespoons in a glass of water should be given.</li> <li>▶ Although induction of vomiting may be recommended (<b>IN CONSCIOUS PERSONS ONLY</b>), such a first aid measure is dissuaded due to the risk of aspiration of stomach contents. (i) It is better to take the patient to a doctor who can decide on the necessity and method of emptying the stomach. (ii) Special circumstances may however exist; these include non-availability of charcoal and the ready availability of the doctor.</li> </ul>

## Ammunitions with Inert Projectile (Cartridges for Small Arms)

**NOTE:** If vomiting is induced, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.

**NOTE:** Wear protective gloves when inducing vomiting.

- ▶ REFER FOR MEDICAL ATTENTION WITHOUT DELAY.
- ▶ In the mean time, qualified first-aid personnel should treat the patient following observation and employing supportive measures as indicated by the patient's condition.
- ▶ If the services of a medical officer or medical doctor are readily available, the patient should be placed in his/her care and a copy of the SDS should be provided. Further action will be the responsibility of the medical specialist.
- ▶ If medical attention is not available on the worksite or surroundings send the patient to a hospital together with a copy of the SDS. (ICSC20305/20307)

### Indication of any immediate medical attention and special treatment needed

Nitroglycerin is a sensitive explosive. If free Nitroglycerin or its analogues, are present, great care must be taken in carrying out first-aid procedures to ensure that it is not initiated through impact.

Treat symptomatically.

for copper intoxication:

- ▶ Unless extensive vomiting has occurred empty the stomach by lavage with water, milk, sodium bicarbonate solution or a 0.1% solution of potassium ferrocyanide (the resulting copper ferrocyanide is insoluble).
- ▶ Administer egg white and other demulcents.
- ▶ Maintain electrolyte and fluid balances.
- ▶ Morphine or meperidine (Demerol) may be necessary for control of pain.
- ▶ If symptoms persist or intensify (especially circulatory collapse or cerebral disturbances, try BAL intramuscularly or penicillamine in accordance with the supplier's recommendations.
- ▶ Treat shock vigorously with blood transfusions and perhaps vasopressor amines.
- ▶ If intravascular haemolysis becomes evident protect the kidneys by maintaining a diuresis with mannitol and perhaps by alkalising the urine with sodium bicarbonate.
- ▶ It is unlikely that methylene blue would be effective against the occasional methaemoglobinemia and it might exacerbate the subsequent haemolytic episode.
- ▶ Institute measures for impending renal and hepatic failure.

[GOSSELIN, SMITH & HODGE: Commercial Toxicology of Commercial Products]

- ▶ A role for activated charcoals for emesis is, as yet, unproven.
- ▶ In severe poisoning CaNa<sub>2</sub>EDTA has been proposed.

[ELLENHORN & BARCELOUX: Medical Toxicology]

for dinitrophenols:

Marked fatigue, tremendous thirst, profuse sweating, flushing of the face are all characteristics of intoxication by dinitrophenol derivatives. These may be followed by restlessness, anxiety, excitement which may occasionally lead to convulsions. Rises in body temperature (proportional to dose) may result in severe hyperpyrexia. tachycardia, hyperpnoea, dyspnoea, cyanosis and muscle cramps characterise later symptomatology. Late complications include decreased urine output with albuminuria, casts, pigment, and sometimes blood cells due to toxic nephritis. Jaundice and liver tenderness also develop as a result of toxic hepatitis.

**TREATMENT** for dinitrophenol intoxications:

- ▶ Gastric lavage with large quantities of 5% sodium bicarbonate solution leaving 1-2 pints in the stomach.
- ▶ Saline cathartics e.g. 15-30 gm sodium or magnesium sulfate in water.
- ▶ Cold packs and alcohol sponges to reduce body temperature. Antipyretic drugs are ineffective here. Cold water enemas have been used. Intensive efforts to correct a dinitrophenol fever are justified. If it can be accomplished, mild hypothermia (rectal temperature between 33.5 and 36 deg. C) is desirable because dinitrophenol appears to lose its metabolic activity at reduced temperature. **[DO NOT give atropine, aspirin, and other salicylates to control hyperthermia, as these agents appear likely to enhance the toxicity of phenolic substances. Aspirin also enhances the uncoupling of oxidative phosphorylation.]**
- ▶ Fluids, orally or intravenously (e.g. glucose in saline, 1000 ml) to correct dehydration and acidosis.
- ▶ Because dinitrophenol is actively transported by the renal organic acid transport processes in some species, a trial of forced diuresis with alkalinisation of the urine is warranted.
- ▶ Oxygen therapy. Artificial ventilation is needed. [Administer oxygen by mask to minimise anoxia].
- ▶ Prophylactic measures in anticipation of kidney and liver insufficiency.

GOSSELIN, SMITH HODGE; Clinical Toxicology of Commercial Products 5th Ed.

Diazepam may be used, if necessary, for the treatment of convulsions, to reduce body heat and control agitation. Be prepared to counter respirator depression and hypotension which may occur following administration of anticonvulsants.

Copper, magnesium, aluminium, antimony, iron, manganese, nickel, zinc (and their compounds) in welding, brazing, galvanising or smelting operations all give rise to thermally produced particulates of smaller dimension than may be produced if the metals are divided mechanically. Where insufficient ventilation or respiratory protection is available these particulates may produce "metal fume fever" in workers from an acute or long term exposure.

- ▶ Onset occurs in 4-6 hours generally on the evening following exposure. Tolerance develops in workers but may be lost over the weekend. (Monday Morning Fever)
- ▶ Pulmonary function tests may indicate reduced lung volumes, small airway obstruction and decreased carbon monoxide diffusing capacity but these abnormalities resolve after several months.
- ▶ Although mildly elevated urinary levels of heavy metal may occur they do not correlate with clinical effects.
- ▶ The general approach to treatment is recognition of the disease, supportive care and prevention of exposure.
- ▶ Seriously symptomatic patients should receive chest x-rays, have arterial blood gases determined and be observed for the development of tracheobronchitis and pulmonary edema.

[Ellenhorn and Barceloux: Medical Toxicology]

- ▶ Gastric acids solubilise lead and its salts and lead absorption occurs in the small bowel.
- ▶ Particles of less than 1 µm diameter are substantially absorbed by the alveoli following inhalation.
- ▶ Lead is distributed to the red blood cells and has a half-life of 35 days. It is subsequently redistributed to soft tissue & bone-stores or eliminated. The kidney accounts for 75% of daily lead loss; integumentary and alimentary losses account for the remainder.
- ▶ Neurasthenic symptoms are the most common symptoms of intoxication. Lead toxicity produces a classic motor neuropathy. Acute encephalopathy appears infrequently in adults. Diazepam is the best drug for seizures.
- ▶ Whole-blood lead is the best measure of recent exposure; free erythrocyte protoporphyrin (FEP) provides the best screening for chronic exposure. Obvious clinical symptoms occur in adults when whole-blood lead exceeds 80 µg/dL.
- ▶ British Anti-Lewisite is an effective antidote and enhances faecal and urinary excretion of lead. The onset of action of BAL is about 30 minutes and most of the chelated metal complex is excreted in 4-6 hours, primarily in the bile. Adverse reaction appears in up to 50% of patients given BAL in doses exceeding 5 mg/kg. CaNa<sub>2</sub>EDTA has also been used alone or in concert with BAL as an antidote. D-penicillamine is the usual oral agent for mobilisation of bone lead; its use in the treatment of lead poisoning remains investigational. 2,3-dimercapto-1-propanesulfonic acid (DMPS) and dimercaptosuccinic acid (DMSA) are water soluble analogues of BAL and their effectiveness is undergoing review. As a rule, stop BAL if lead decreases below 50 µg/dL; stop CaNa<sub>2</sub>EDTA if blood lead decreases below 40 µg/dL or urinary lead drops below 2 mg/24hrs.

[Ellenhorn & Barceloux: Medical Toxicology]

### BIOLOGICAL EXPOSURE INDEX - BEI

These represent the determinants observed in specimens collected from a healthy worker who has been exposed at the Exposure Standard (ES or TLV):

Determinant	Index	Sampling Time	Comments
1. Lead in blood	30 µg/100 ml	Not Critical	
2. Lead in urine	150 µg/gm creatinine	Not Critical	B

Continued...

## Ammunitions with Inert Projectile (Cartridges for Small Arms)

3. Zinc protoporphyrin in blood                      250 ug/100 ml erythrocytes OR 100 ug/100 ml blood                      After 1 month exposure                      B

B: Background levels occur in specimens collected from subjects **NOT** exposed.

Symptoms of vasodilation and reflex tachycardia may present following organic nitrate overdose; most organic nitrates are extensively metabolised by hydrolysis to inorganic nitrites. Organic nitrates and nitrites are readily absorbed through the skin, lungs, mucosa and gastro-intestinal tract.

### SECTION 5 Firefighting measures

#### Extinguishing media

Metal dust fires need to be smothered with sand, inert dry powders.

**DO NOT USE WATER, CO<sub>2</sub> or FOAM.**

- ▶ Use DRY sand, graphite powder, dry sodium chloride based extinguishers, G-1 or Met L-X to smother fire.
- ▶ Confining or smothering material is preferable to applying water as chemical reaction may produce flammable and explosive hydrogen gas.
- ▶ Chemical reaction with CO<sub>2</sub> may produce flammable and explosive methane.
- ▶ If impossible to extinguish, withdraw, protect surroundings and allow fire to burn itself out.
- ▶ **DO NOT** use halogenated fire extinguishing agents.

#### Special hazards arising from the substrate or mixture

<b>Fire Incompatibility</b>	<ul style="list-style-type: none"> <li>▶ Reacts with acids producing flammable / explosive hydrogen (H<sub>2</sub>) gas</li> <li>▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result</li> </ul>
-----------------------------	--

#### Advice for firefighters

<b>Fire Fighting</b>	<p><b>WARNING: EXPLOSIVE MATERIALS / ARTICLES PRESENT!</b></p> <ul style="list-style-type: none"> <li>▶ Evacuate all personnel and move upwind.</li> <li>▶ Prevent re-entry.</li> <li>▶ Alert Fire Brigade and tell them location and nature of hazard.</li> <li>▶ May detonate and burning material may be propelled from fire.</li> <li>▶ Wear full-body protective clothing with breathing apparatus.</li> <li>▶ Prevent, by any means available, spillage and fire effluent from entering drains and water courses.</li> <li>▶ Fight fire from safe distances and from protected locations.</li> <li>▶ Use flooding quantities of water.</li> <li>▶ <b>DO NOT</b> approach containers or packages suspected to be hot.</li> <li>▶ Cool any exposed containers not involved in fire from a protected location.</li> <li>▶ Equipment should be thoroughly decontaminated after use.</li> </ul>
<b>Fire/Explosion Hazard</b>	<ul style="list-style-type: none"> <li>▶ Zinc dust clouds are potentially explosive.</li> <li>▶ Electric sparks may ignite the dust cloud even in atmospheres containing low oxygen (10%).</li> <li>▶ In air the dust may be ignited in contact with hot surfaces or flame where temperatures exceed 600 deg C.</li> <li>▶ <b>DO NOT disturb burning dust. Explosion may result if dust is stirred into a cloud, by providing oxygen to a large surface of hot metal.</b></li> <li>▶ <b>DO NOT use water or foam as generation of explosive hydrogen may result.</b></li> </ul> <p>With the exception of the metals that burn in contact with air or water (for example, sodium), masses of combustible metals do not represent unusual fire risks because they have the ability to conduct heat away from hot spots so efficiently that the heat of combustion cannot be maintained - this means that it will require a lot of heat to ignite a mass of combustible metal. Generally, metal fire risks exist when sawdust, machine shavings and other metal 'fines' are present.</p> <p>Metal powders, while generally regarded as non-combustible:</p> <ul style="list-style-type: none"> <li>▶ May burn when metal is finely divided and energy input is high.</li> <li>▶ May react explosively with water.</li> <li>▶ May be ignited by friction, heat, sparks or flame.</li> <li>▶ May <b>REIGNITE</b> after fire is extinguished.</li> <li>▶ Will burn with intense heat.</li> </ul> <p>Note:</p> <ul style="list-style-type: none"> <li>▶ Metal dust fires are slow moving but intense and difficult to extinguish.</li> <li>▶ Containers may explode on heating.</li> <li>▶ Dusts or fumes may form explosive mixtures with air.</li> <li>▶ Gases generated in fire may be poisonous, corrosive or irritating.</li> <li>▶ Hot or burning metals may react violently upon contact with other materials, such as oxidising agents and extinguishing agents used on fires involving ordinary combustibles or flammable liquids.</li> <li>▶ Temperatures produced by burning metals can be higher than temperatures generated by burning flammable liquids</li> <li>▶ Some metals can continue to burn in carbon dioxide, nitrogen, water, or steam atmospheres in which ordinary combustibles or flammable liquids would be incapable of burning.</li> </ul> <p>Ignites spontaneously in air (pyrophoric) and burns with intense heat.</p> <p>Division 1.4 Substances, mixtures and articles which present no significant hazard: substances, mixtures and articles which present only a small hazard in the event of ignition or initiation. The effects are largely confined to the package and no projection of fragments of appreciable size or range is to be expected. An external fire shall not cause virtually instantaneous explosion of almost the entire contents of the package.</p> <p>Combustion products include:</p> <p>carbon monoxide (CO) carbon dioxide (CO<sub>2</sub>) nitrogen oxides (NO<sub>x</sub>) metal oxides other pyrolysis products typical of burning organic material.</p>
<b>HAZCHEM</b>	1YE

### SECTION 6 Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

See section 8

#### Environmental precautions

See section 12

#### Methods and material for containment and cleaning up

## Ammunitions with Inert Projectile (Cartridges for Small Arms)

<b>Minor Spills</b>	<p>For nitroglycerine and similar products:</p> <ul style="list-style-type: none"> <li>▶ Clean up spills immediately. Avoid all personal contact.</li> <li>▶ Wear protective clothing, impervious gloves and safety glasses.</li> <li>▶ Minor splashes should be wiped clean with an alcohol soaked cloth.</li> <li>▶ The spill area is decontaminated using NG Decontamination Solution<sup>1</sup>.</li> <li>▶ Do not use metal or spark producing implements during clean up.</li> </ul> <p><b>WARNING! EXPLOSIVE.</b> BLAST and/or PROJECTION and/or FIRE HAZARD</p> <ul style="list-style-type: none"> <li>▶ Clean up all spills immediately.</li> <li>▶ Avoid inhalation of the material and avoid contact with eyes and skin.</li> <li>▶ Wear impervious gloves and safety glasses.</li> <li>▶ Remove all ignition sources.</li> <li>▶ Use spark-free tools when handling.</li> <li>▶ Sweep into non-sparking containers or barrels and moisten with water.</li> <li>▶ Place spilled material in clean, sealable, labelled container for disposal.</li> <li>▶ Flush area with large amounts of water.</li> </ul>
<b>Major Spills</b>	<ul style="list-style-type: none"> <li>· Do not use compressed air to remove metal dusts from floors, beams or equipment</li> <li>· Vacuum cleaners, of flame-proof design, should be used to minimise dust accumulation.</li> <li>· Use non-sparking handling equipment, tools and natural bristle brushes.</li> <li>· Provide grounding and bonding where necessary to prevent accumulation of static charges during metal dust handling and transfer operations</li> <li>· Cover and reseal partially empty containers.</li> <li>· Do not allow chips, fines or dusts to contact water, particularly in enclosed areas.</li> </ul> <p>If molten:</p> <ul style="list-style-type: none"> <li>▶ Contain the flow using dry sand or salt flux as a dam.</li> <li>▶ All tooling (e.g., shovels or hand tools) and containers which come in contact with molten metal must be preheated or specially coated, rust free and approved for such use.</li> <li>▶ Allow the spill to cool before remelting scrap.</li> </ul> <p><b>WARNING! EXPLOSIVE.</b></p> <ul style="list-style-type: none"> <li>▶ Clear area of personnel and move upwind.</li> <li>▶ Alert Fire Brigade and tell them location and nature of hazard.</li> <li>▶ May be violently or explosively reactive.</li> <li>▶ Wear full body protective clothing with breathing apparatus.</li> <li>▶ Consider evacuation (or protect in place).</li> <li>▶ In case of transport accident notify Police, Emergency Authority, Competent Explosives Authority or Manufacturer.</li> <li>▶ No smoking, naked lights, heat or ignition sources.</li> <li>▶ Increase ventilation.</li> <li>▶ Use extreme caution to prevent physical shock.</li> <li>▶ Use only spark-free shovels and explosion-proof equipment.</li> <li>▶ Collect recoverable material and segregate from spilled material.</li> <li>▶ Wash spill area with large quantities of water.</li> </ul>

Personal Protective Equipment advice is contained in Section 8 of the SDS.

## SECTION 7 Handling and storage

### Precautions for safe handling

<b>Safe handling</b>	<p>For molten metals:</p> <ul style="list-style-type: none"> <li>· Molten metal and water can be an explosive combination. The risk is greatest when there is sufficient molten metal to entrap or seal off water. Water and other forms of contamination on or contained in scrap or remelt ingot are known to have caused explosions in melting operations. While the products may have minimal surface roughness and internal voids, there remains the possibility of moisture contamination or entrapment. If confined, even a few drops can lead to violent explosions.</li> <li>· All tooling, containers, molds and ladles, which come in contact with molten metal must be preheated or specially coated, rust free and approved for such use.</li> <li>· Any surfaces that may contact molten metal (e.g. concrete) should be specially coated</li> <li>· Drops of molten metal in water (e.g. from plasma arc cutting), while not normally an explosion hazard, can generate enough flammable hydrogen gas to present an explosion hazard. Vigorous circulation of the water and removal of the particles minimise the hazard.</li> </ul> <p>During melting operations, the following minimum guidelines should be observed:</p> <ul style="list-style-type: none"> <li>· Inspect all materials prior to furnace charging and completely remove surface contamination such as water, ice, snow, deposits of grease and oil or other surface contamination resulting from weather exposure, shipment, or storage.</li> <li>· Store materials in dry, heated areas with any cracks or cavities pointed downwards.</li> <li>· Preheat and dry large objects adequately before charging in to a furnace containing molten metal. This is typically done by the use of a drying oven or homogenising furnace. The dry cycle should bring the metal temperature of the coldest item of the batch to 200 degree C (400 deg F) and then hold at that temperature for 6 hours. <ul style="list-style-type: none"> <li>▶ Handle gently. Use good occupational work practice.</li> <li>▶ Observe manufacturer's storage and handling recommendations contained within this SDS.</li> <li>▶ Avoid all personal contact, including inhalation.</li> <li>▶ Avoid smoking, naked lights, heat or ignition sources.</li> <li>▶ Explosives must not be struck with metal implements.</li> <li>▶ Avoid mechanical and thermal shock and friction.</li> <li>▶ Use in a well ventilated area.</li> <li>▶ Avoid contact with incompatible materials.</li> <li>▶ <b>When handling DO NOT eat, drink or smoke.</b></li> <li>▶ Avoid physical damage to containers.</li> <li>▶ Always wash hands with soap and water after handling.</li> <li>▶ Work clothes should be laundered separately.</li> </ul> </li> <li>· Organic powders when finely divided over a range of concentrations regardless of particulate size or shape and suspended in air or some other oxidizing medium may form explosive dust-air mixtures and result in a fire or dust explosion (including secondary explosions)</li> <li>· Minimise airborne dust and eliminate all ignition sources. Keep away from heat, hot surfaces, sparks, and flame.</li> <li>· Establish good housekeeping practices.</li> <li>· Remove dust accumulations on a regular basis by vacuuming or gentle sweeping to avoid creating dust clouds.</li> <li>· Use continuous suction at points of dust generation to capture and minimise the accumulation of dusts. Particular attention should be given to overhead and hidden horizontal surfaces to minimise the probability of a "secondary" explosion. According to NFPA Standard 654, dust layers 1/32 in.(0.8 mm) thick can be sufficient to warrant immediate cleaning of the area.</li> <li>· Do not use air hoses for cleaning.</li> <li>· Minimise dry sweeping to avoid generation of dust clouds. Vacuum dust-accumulating surfaces and remove to a chemical disposal area.</li> </ul>
----------------------	--



## Ammunitions with Inert Projectile (Cartridges for Small Arms)

	<p>Vacuums with explosion-proof motors should be used.</p> <ul style="list-style-type: none"> <li>▶ Control sources of static electricity. Dusts or their packages may accumulate static charges, and static discharge can be a source of ignition.</li> <li>▶ Solids handling systems must be designed in accordance with applicable standards (e.g. NFPA including 654 and 77) and other national guidance.</li> <li>▶ Do not empty directly into flammable solvents or in the presence of flammable vapors.</li> <li>▶ The operator, the packaging container and all equipment must be grounded with electrical bonding and grounding systems. Plastic bags and plastics cannot be grounded, and antistatic bags do not completely protect against development of static charges.</li> </ul> <p>Empty containers may contain residual dust which has the potential to accumulate following settling. Such dusts may explode in the presence of an appropriate ignition source.</p> <ul style="list-style-type: none"> <li>▶ <b>Do NOT cut, drill, grind or weld such containers.</b></li> <li>▶ In addition ensure such activity is not performed near full, partially empty or empty containers without appropriate workplace safety authorisation or permit.</li> </ul>
<p style="text-align: center;"><b>Other information</b></p>	<ul style="list-style-type: none"> <li>▶ <b>DO NOT store near acids, or oxidising agents</b></li> <li>▶ Store cases in a well ventilated magazine licensed for the appropriate Class, Division and Compatibility Group.</li> <li>▶ Rotate stock to prevent ageing. Use on FIFO (first in-first out) basis.</li> <li>▶ Observe manufacturer's storage and handling recommendations contained within this SDS.</li> <li>▶ Store in a cool place in original containers.</li> <li>▶ Keep containers securely sealed.</li> <li>▶ No smoking, naked lights, heat or ignition sources.</li> <li>▶ Store in an isolated area away from other materials.</li> <li>▶ Keep storage area free of debris, waste and combustibles.</li> <li>▶ Protect containers against physical damage.</li> <li>▶ Check regularly for spills and leaks</li> </ul> <p><b>NOTE:</b> If explosives need to be destroyed contact the Competent Authority.</p>

### Conditions for safe storage, including any incompatibilities

<p style="text-align: center;"><b>Suitable container</b></p>	<ul style="list-style-type: none"> <li>▶ Bulk bags: Reinforced bags required for dense materials.</li> <li>▶ <b>CARE:</b> Packing of high density product in light weight metal or plastic packages may result in container collapse with product release</li> <li>▶ All packaging for Class 1 Goods shall be in accordance with the requirements of the relevant Code for the transport of Dangerous Goods.</li> <li>▶ Class 1 is unique in that the type of packaging used frequently has a very decisive effect on the hazard and therefore on the assignment to a particular division</li> <li>▶ Heavy gauge metal packages / Heavy gauge metal drums</li> </ul>
<p style="text-align: center;"><b>Storage incompatibility</b></p>	<p>Inorganic derivative of Group 11 metal. For aluminas (aluminium oxide): Incompatible with hot chlorinated rubber. In the presence of chlorine trifluoride may react violently and ignite. -May initiate explosive polymerisation of olefin oxides including ethylene oxide. -Produces exothermic reaction above 200°C with halocarbons and an exothermic reaction at ambient temperatures with halocarbons in the presence of other metals. -Produces exothermic reaction with oxygen difluoride. -May form explosive mixture with oxygen difluoride. -Forms explosive mixtures with sodium nitrate. -Reacts vigorously with vinyl acetate.</p> <p>Aluminium oxide is an amphoteric substance, meaning it can react with both acids and bases, such as hydrofluoric acid and sodium hydroxide, acting as an acid with a base and a base with an acid, neutralising the other and producing a salt.</p> <p>Nitroglycerin:</p> <ul style="list-style-type: none"> <li>▶ is heat-, UV-, acid-, friction-, mechanical-shock-high explosive</li> <li>▶ is hydrolysed in water forming an explosive solution of nitric acid and glycerol</li> <li>▶ is a strong oxidiser - reacts vigorously, with possible detonation, on contact with strong reducing agents</li> <li>▶ explodes on contact with ozone or at temperatures above approximately 177 deg C</li> <li>▶ thermal sensitivity may be increased in the presence of metal oxides</li> <li>▶ may form explosive salts on reaction with organic bases</li> <li>▶ <b>WARNING:</b> Avoid or control reaction with peroxides. All <i>transition metal</i> peroxides should be considered as potentially explosive. For example transition metal complexes of alkyl hydroperoxides may decompose explosively.</li> <li>▶ The pi-complexes formed between chromium(0), vanadium(0) and other transition metals (haloarene-metal complexes) and mono- or poly-fluorobenzene show extreme sensitivity to heat and are explosive.</li> <li>▶ Avoid reaction with borohydrides or cyanoborohydrides</li> <li>▶ Many metals may incandesce, react violently, ignite or react explosively upon addition of concentrated nitric acid.</li> </ul> <p>Nitrophenols are:</p> <ul style="list-style-type: none"> <li>▶ combustible solids which may form explosive mixtures with air when finely divided</li> <li>▶ strong oxidisers which react violently with reducing agents</li> <li>▶ reactive with combustible, organic and other easily oxidisable materials</li> <li>▶ thermally unstable burning in the absence of air causing fast pressure rises; closed containers may explode</li> <li>▶ able to form shock-sensitive explosive mixtures with chlorine trifluoride</li> <li>▶ incompatible with strong acids, caustics, aliphatic amines, amides, diethylamine, potassium hydride, potassium hydroxide</li> </ul> <p>▶ Sulfides are incompatible with acids, diazo and azo compounds, halocarbons, isocyanates, aldehydes, alkali metals, nitrides, hydrides, and other strong reducing agents.</p> <ul style="list-style-type: none"> <li>▶ Many reactions of sulfides with these materials generate heat and in many cases hydrogen gas.</li> <li>▶ Many sulfide compounds may liberate hydrogen sulfide upon reaction with an acid.</li> </ul> <p>Metals exhibit varying degrees of activity. Reaction is reduced in the massive form (sheet, rod, or drop), compared with finely divided forms. The less active metals will not burn in air but:</p> <ul style="list-style-type: none"> <li>▶ can react exothermically with oxidising acids to form noxious gases.</li> <li>▶ catalyse polymerisation and other reactions, particularly when finely divided</li> <li>▶ react with halogenated hydrocarbons (for example, copper dissolves when heated in carbon tetrachloride), sometimes forming explosive compounds.</li> </ul> <ul style="list-style-type: none"> <li>▶ Many metals in elemental form react exothermically with compounds having active hydrogen atoms (such as acids and water) to form flammable hydrogen gas and caustic products.</li> <li>▶ Elemental metals may react with azo/diazo compounds to form explosive products.</li> <li>▶ Some elemental metals form explosive products with halogenated hydrocarbons.</li> <li>▶ Explosion hazard may follow contact with incompatible materials</li> <li>▶ Finely divided metal powders develop pyrophoricity when a critical specific surface area is exceeded; this is ascribed to high heat of oxide formation on exposure to air.</li> </ul>

## Ammunitions with Inert Projectile (Cartridges for Small Arms)

- ▶ Safe handling is possible in relatively low concentrations of oxygen in an inert gas.
- ▶ Several pyrophoric metals, stored in glass bottles have ignited when the container is broken on impact. Storage of these materials moist and in metal containers is recommended.
- ▶ The reaction residues from various metal syntheses (involving vacuum evaporation and co-deposition with a ligand) are often pyrophoric. Factors influencing the pyrophoricity of metals are particle size, presence of moisture, nature of the surface of the particle, heat of formation of the oxide, or nitride, mass, hydrogen content, stress, purity and presence of oxide, among others.
- ▶ Phenols are incompatible with strong reducing substances such as hydrides, nitrides, alkali metals, and sulfides.
- ▶ Avoid use of aluminium, copper and brass alloys in storage and process equipment.
- ▶ Heat is generated by the acid-base reaction between phenols and bases.
- ▶ Phenols are sulfonated very readily (for example, by concentrated sulfuric acid at room temperature), these reactions generate heat.
- ▶ Phenols are nitrated very rapidly, even by dilute nitric acid.
- ▶ Nitrated phenols often explode when heated. Many of them form metal salts that tend toward detonation by rather mild shock.

### SECTION 8 Exposure controls / personal protection

#### Control parameters

##### Occupational Exposure Limits (OEL)

##### INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Australia Exposure Standards	lead	Lead, inorganic dusts & fumes (as Pb)	0.05 mg/m <sup>3</sup>	Not Available	Not Available	Not Available
Australia Exposure Standards	copper	Copper, dusts & mists (as Cu)	1 mg/m <sup>3</sup>	Not Available	Not Available	Not Available
Australia Exposure Standards	copper	Copper (fume)	0.2 mg/m <sup>3</sup>	Not Available	Not Available	Not Available
Australia Exposure Standards	nitroglycerin	Nitroglycerine (NG)	0.05 ppm / 0.46 mg/m <sup>3</sup>	Not Available	Not Available	Not Available
Australia Exposure Standards	lead dioxide	Lead, inorganic dusts & fumes (as Pb)	0.05 mg/m <sup>3</sup>	Not Available	Not Available	Not Available
Australia Exposure Standards	barium nitrate	Barium, soluble compounds (as Ba)	0.5 mg/m <sup>3</sup>	Not Available	Not Available	Not Available
Australia Exposure Standards	antimony trisulfide	Antimony & compounds (as Sb)	0.5 mg/m <sup>3</sup>	Not Available	Not Available	Not Available
Australia Exposure Standards	barium sulfate	Barium sulphate	10 mg/m <sup>3</sup>	Not Available	Not Available	(a) This value is for inhalable dust containing no asbestos and < 1% crystalline silica.
Australia Exposure Standards	aluminium	Aluminium (welding fumes) (as Al)	5 mg/m <sup>3</sup>	Not Available	Not Available	Not Available
Australia Exposure Standards	aluminium	Aluminium (metal dust)	10 mg/m <sup>3</sup>	Not Available	Not Available	Not Available
Australia Exposure Standards	aluminium	Aluminium, pyro powders (as Al)	5 mg/m <sup>3</sup>	Not Available	Not Available	Not Available

##### Emergency Limits

Ingredient	TEEL-1	TEEL-2	TEEL-3
lead	0.15 mg/m <sup>3</sup>	120 mg/m <sup>3</sup>	700 mg/m <sup>3</sup>
copper	3 mg/m <sup>3</sup>	33 mg/m <sup>3</sup>	200 mg/m <sup>3</sup>
zinc	6 mg/m <sup>3</sup>	21 mg/m <sup>3</sup>	120 mg/m <sup>3</sup>
pentaerythritol tetranitrate	5 mg/m <sup>3</sup>	55 mg/m <sup>3</sup>	330 mg/m <sup>3</sup>
nitroglycerin	0.1 mg/m <sup>3</sup>	2 mg/m <sup>3</sup>	75 mg/m <sup>3</sup>
lead dioxide	0.17 mg/m <sup>3</sup>	140 mg/m <sup>3</sup>	810 mg/m <sup>3</sup>
barium nitrate	2.9 mg/m <sup>3</sup>	350 mg/m <sup>3</sup>	2,100 mg/m <sup>3</sup>
barium sulfate	15 mg/m <sup>3</sup>	170 mg/m <sup>3</sup>	990 mg/m <sup>3</sup>

Ingredient	Original IDLH	Revised IDLH
lead	Not Available	Not Available
copper	100 mg/m <sup>3</sup>	Not Available
zinc	Not Available	Not Available
nitrocellulose	Not Available	Not Available
lead styphnate	100 mg/m <sup>3</sup>	Not Available
tetrazene	Not Available	Not Available
pentaerythritol tetranitrate	Not Available	Not Available
nitroglycerin	75 mg/m <sup>3</sup>	Not Available
lead dioxide	100 mg/m <sup>3</sup>	Not Available
barium nitrate	50 mg/m <sup>3</sup>	Not Available
antimony trisulfide	50 mg/m <sup>3</sup>	Not Available
barium sulfate	Not Available	Not Available
aluminium	Not Available	Not Available

##### Occupational Exposure Banding

Continued...



## Ammunitions with Inert Projectile (Cartridges for Small Arms)

Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit
lead styphnate	E	≤ 0.01 mg/m <sup>3</sup>
tetrazene	E	≤ 0.01 mg/m <sup>3</sup>
pentaerythritol tetranitrate	E	≤ 0.01 mg/m <sup>3</sup>
<b>Notes:</b>	Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.	

## Exposure controls

<b>Appropriate engineering controls</b>	<p>Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are:</p> <p>Process controls which involve changing the way a job activity or process is done to reduce the risk.</p> <p>Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.</p> <p>Employers may need to use multiple types of controls to prevent employee overexposure.</p> <ul style="list-style-type: none"> <li>▶ Employees exposed to confirmed human carcinogens should be authorized to do so by the employer, and work in a regulated area.</li> <li>▶ Work should be undertaken in an isolated system such as a "glove-box" . Employees should wash their hands and arms upon completion of the assigned task and before engaging in other activities not associated with the isolated system.</li> <li>▶ Within regulated areas, the carcinogen should be stored in sealed containers, or enclosed in a closed system, including piping systems, with any sample ports or openings closed while the carcinogens are contained within.</li> <li>▶ Open-vessel systems are prohibited.</li> <li>▶ Each operation should be provided with continuous local exhaust ventilation so that air movement is always from ordinary work areas to the operation.</li> <li>▶ Exhaust air should not be discharged to regulated areas, non-regulated areas or the external environment unless decontaminated. Clean make-up air should be introduced in sufficient volume to maintain correct operation of the local exhaust system.</li> <li>▶ For maintenance and decontamination activities, authorized employees entering the area should be provided with and required to wear clean, impervious garments, including gloves, boots and continuous-air supplied hood. Prior to removing protective garments the employee should undergo decontamination and be required to shower upon removal of the garments and hood.</li> <li>▶ Except for outdoor systems, regulated areas should be maintained under negative pressure (with respect to non-regulated areas).</li> <li>▶ Local exhaust ventilation requires make-up air be supplied in equal volumes to replaced air.</li> <li>▶ Laboratory hoods must be designed and maintained so as to draw air inward at an average linear face velocity of 0.76 m/sec with a minimum of 0.64 m/sec. Design and construction of the fume hood requires that insertion of any portion of the employees body, other than hands and arms, be disallowed.</li> </ul>
<b>Personal protection</b>	
<b>Eye and face protection</b>	<ul style="list-style-type: none"> <li>▶ Safety glasses with side shields.</li> <li>▶ Chemical goggles.</li> <li>▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent]</li> </ul>
<b>Skin protection</b>	See Hand protection below
<b>Hands/feet protection</b>	<ul style="list-style-type: none"> <li>▶ Wear chemical protective gloves, e.g. PVC.</li> <li>▶ Wear safety footwear or safety gumboots, e.g. Rubber</li> </ul> <p><b>NOTE:</b></p> <ul style="list-style-type: none"> <li>▶ The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.</li> <li>▶ Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed.</li> </ul> <p>The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.</p> <p>The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.</p> <p>Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.</p> <p>Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include:</p> <ul style="list-style-type: none"> <li>· frequency and duration of contact,</li> <li>· chemical resistance of glove material,</li> <li>· glove thickness and</li> <li>· dexterity</li> </ul> <p>Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent).</p> <ul style="list-style-type: none"> <li>· When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.</li> <li>· When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.</li> <li>· Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for long-term use.</li> <li>· Contaminated gloves should be replaced.</li> </ul> <p>As defined in ASTM F-739-96 in any application, gloves are rated as:</p> <ul style="list-style-type: none"> <li>· Excellent when breakthrough time &gt; 480 min</li> <li>· Good when breakthrough time &gt; 20 min</li> <li>· Fair when breakthrough time &lt; 20 min</li> <li>· Poor when glove material degrades</li> </ul> <p>For general applications, gloves with a thickness typically greater than 0.35 mm, are recommended.</p>

## Ammunitions with Inert Projectile (Cartridges for Small Arms)

	<p>It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times.</p> <p>Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers technical data should always be taken into account to ensure selection of the most appropriate glove for the task.</p> <p>Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example:</p> <ul style="list-style-type: none"> <li>· Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of.</li> <li>· Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential</li> </ul> <p>Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.</p> <ul style="list-style-type: none"> <li>▸ Protective gloves eg. Leather gloves or gloves with Leather facing             <ul style="list-style-type: none"> <li>· Non-sparking or conductive footwear essential. Conductive footwear describes a boot or shoe with a sole made from a conductive compound chemically bound to the bottom components, for permanent control to electrically ground the foot an shall dissipate static electricity from the body to reduce the possibility of ignition of volatile compounds. Electrical resistance must range between 0 to 500,000 ohms. Conductive shoes should be stored in lockers close to the room in which they are worn. Personnel who have been issued conductive footwear should not wear them from their place of work to their homes and return.</li> </ul> </li> </ul>
<b>Body protection</b>	See Other protection below
<b>Other protection</b>	<ul style="list-style-type: none"> <li>▸ Employees working with confirmed human carcinogens should be provided with, and be required to wear, clean, full body protective clothing (smocks, coveralls, or long-sleeved shirt and pants), shoe covers and gloves prior to entering the regulated area. [AS/NZS ISO 6529:2006 or national equivalent]</li> <li>▸ Employees engaged in handling operations involving carcinogens should be provided with, and required to wear and use half-face filter-type respirators with filters for dusts, mists and fumes, or air purifying canisters or cartridges. A respirator affording higher levels of protection may be substituted. [AS/NZS 1715 or national equivalent]</li> <li>▸ Emergency deluge showers and eyewash fountains, supplied with potable water, should be located near, within sight of, and on the same level with locations where direct exposure is likely.</li> <li>▸ Prior to each exit from an area containing confirmed human carcinogens, employees should be required to remove and leave protective clothing and equipment at the point of exit and at the last exit of the day, to place used clothing and equipment in impervious containers at the point of exit for purposes of decontamination or disposal. The contents of such impervious containers must be identified with suitable labels. For maintenance and decontamination activities, authorized employees entering the area should be provided with and required to wear clean, impervious garments, including gloves, boots and continuous-air supplied hood.</li> <li>▸ Prior to removing protective garments the employee should undergo decontamination and be required to shower upon removal of the garments and hood.</li> </ul> <p>For handling explosives or explosive compositions:</p> <ul style="list-style-type: none"> <li>▸ Wear close-fitting flame-protection treated clothing closed at the neck and sleeves.</li> <li>▸ Cotton underwear, socks and conductive shoes are recommended to avoid human static discharge.</li> </ul> <p>· During repair or maintenance activities the potential exists for exposures to toxic metal particulate in excess of the occupational standards. Under these circumstances, protecting workers can require the use of specific work practices or procedures involving the combined use of ventilation, wet and vacuum cleaning methods, respiratory protection, decontamination, special protective clothing, and when necessary, restricted work zones.</p> <ul style="list-style-type: none"> <li>· Protective over-garments or work clothing must be worn by persons who may become contaminated with particulate during activities such as machining, furnace rebuilding, air cleaning equipment filter changes, maintenance, furnace tending, etc. Contaminated work clothing and over-garments must be managed in a controlled manner to prevent secondary exposure to workers of third parties, to prevent the spread of particulate to other areas, and to prevent particulate from being taken home by workers.</li> <li>· Personnel who handle and work with <u>molten metal</u> should utilise primary protective clothing like polycarbonate face shields, fire resistant tapper's jackets, neck shades (snoods), leggings, spats and similar equipment to prevent burn injuries. In addition to primary protection, secondary or day-to-day work clothing that is fire resistant and sheds metal splash is recommended for use with molten metal. Synthetic materials should never be worn even as secondary clothing (undergarments).</li> </ul> <p>Manufacture may require:</p> <ul style="list-style-type: none"> <li>▸ Non-static flame retardant treated clothing</li> <li>▸ Access to deluge Safety shower</li> <li>▸ Barrier cream.</li> </ul>

### Respiratory protection

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required. Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	A-AUS P2	-	A-PAPR-AUS / Class 1 P2
up to 50 x ES	-	A-AUS / Class 1 P2	-
up to 100 x ES	-	A-2 P2	A-PAPR-2 P2 ^

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO<sub>2</sub>), G = Agricultural chemicals, K = Ammonia(NH<sub>3</sub>), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

- Respirators may be necessary when engineering and administrative controls do not adequately prevent exposures.
- The decision to use respiratory protection should be based on professional judgment that takes into account toxicity information, exposure measurement data, and frequency and likelihood of the worker's exposure - ensure users are not subject to high thermal loads which may result in heat stress or distress due to personal protective equipment (powered, positive flow, full face apparatus may be an option).
- Published occupational exposure limits, where they exist, will assist in determining the adequacy of the selected respiratory protection. These may be government mandated or vendor recommended.
- Certified respirators will be useful for protecting workers from inhalation of particulates when properly selected and fit tested as part of a complete respiratory protection program.
- Where protection from nuisance levels of dusts are desired, use type N95 (US) or type P1 (EN143) dust masks. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU)
- Use approved positive flow mask if significant quantities of dust becomes airborne.
- Try to avoid creating dust conditions.

Where significant concentrations of the material are likely to enter the breathing zone, a Class P3 respirator may be required.

Class P3 particulate filters are used for protection against highly toxic or highly irritant particulates.

Filtration rate: Filters at least 99.95% of airborne particles

Suitable for:

- Relatively small particles generated by mechanical processes eg. grinding, cutting, sanding, drilling, sawing.
- Sub-micron thermally generated particles e.g. welding fumes, fertilizer and bushfire smoke.

Continued...

## Ammunitions with Inert Projectile (Cartridges for Small Arms)

- Biologically active airborne particles under specified infection control applications e.g. viruses, bacteria, COVID-19, SARS
  - Highly toxic particles e.g. Organophosphate Insecticides, Radionuclides, Asbestos
- Note: P3 Rating can only be achieved when used with a Full Face Respirator or Powered Air-Purifying Respirator (PAPR). If used with any other respirator, it will only provide filtration protection up to a P2 rating.

### SECTION 9 Physical and chemical properties

#### Information on basic physical and chemical properties

<b>Appearance</b>	Metallic cylinder; insoluble in water.		
<b>Physical state</b>	Manufactured	<b>Relative density (Water = 1)</b>	Not Available
<b>Odour</b>	Not Available	<b>Partition coefficient n-octanol / water</b>	Not Available
<b>Odour threshold</b>	Not Available	<b>Auto-ignition temperature (°C)</b>	Not Applicable
<b>pH (as supplied)</b>	Not Applicable	<b>Decomposition temperature</b>	Not Available
<b>Melting point / freezing point (°C)</b>	Not Available	<b>Viscosity (cSt)</b>	Not Applicable
<b>Initial boiling point and boiling range (°C)</b>	Not Applicable	<b>Molecular weight (g/mol)</b>	Not Applicable
<b>Flash point (°C)</b>	Not Applicable	<b>Taste</b>	Not Available
<b>Evaporation rate</b>	Not Available	<b>Explosive properties</b>	Not Available
<b>Flammability</b>	Not Applicable	<b>Oxidising properties</b>	Not Available
<b>Upper Explosive Limit (%)</b>	Not Applicable	<b>Surface Tension (dyn/cm or mN/m)</b>	Not Applicable
<b>Lower Explosive Limit (%)</b>	Not Applicable	<b>Volatile Component (%vol)</b>	Not Available
<b>Vapour pressure (kPa)</b>	Not Applicable	<b>Gas group</b>	Not Available
<b>Solubility in water</b>	Immiscible	<b>pH as a solution (Not Available%)</b>	Not Applicable
<b>Vapour density (Air = 1)</b>	Not Available	<b>VOC g/L</b>	Not Available

### SECTION 10 Stability and reactivity

<b>Reactivity</b>	See section 7
<b>Chemical stability</b>	<ul style="list-style-type: none"> <li>▶ Presence of shock and friction</li> <li>▶ Presence of heat source and ignition source</li> <li>▶ Product is considered stable under normal handling conditions.</li> <li>▶ Stable under normal storage conditions.</li> <li>▶ Hazardous polymerization will not occur.</li> </ul> Avoid contact with other chemicals.
<b>Possibility of hazardous reactions</b>	See section 7
<b>Conditions to avoid</b>	See section 7
<b>Incompatible materials</b>	See section 7
<b>Hazardous decomposition products</b>	See section 5

### SECTION 11 Toxicological information

#### Information on toxicological effects

<b>Inhaled</b>	<p>The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage. Inhalation of dusts, generated by the material during the course of normal handling, may produce severe damage to the health of the individual. Relatively small amounts absorbed from the lungs may prove fatal.</p> <p>Inhaling 0.04-0.5 parts per million nitroglycerin may result in headache, with overexposure causing temporary loss of vision in some people. It causes dilation of the blood vessels and low blood pressure. Exposure to small amounts can result in headache, dizziness, weakness and nausea. Large exposures can result in vomiting, bluing of the extremities, convulsions, coma and possible circulatory collapse and paralysis of breathing. Prior ingestion of alcohol can worsen these effects. Repeated exposure can cause temporary tolerance to headache, which disappears rapidly; a short absence from exposure may lead to severe poisoning from amounts that were previously safe. Operators are required to obtain Occupational Health Centre "classification" prior to working in areas with nitroglycerin. Animal testing shows it can cause methaemoglobin in the blood.</p> <p>The inhalation of small particles of metal oxide results in sudden thirst, a sweet, metallic foul taste, throat irritation, cough, dry mucous membranes, tiredness and general unwellness. Headache, nausea and vomiting, fever or chills, restlessness, sweating, diarrhoea, excessive urination and prostration may also occur.</p> <p>Copper poisoning following exposure to copper dusts and fume may result in headache, cold sweat and weak pulse. Capillary, kidney, liver and brain damage are the longer term manifestations of such poisoning. Inhalation of freshly formed metal oxide particles sized below 1.5 microns and generally between 0.02 to 0.05 microns may result in "metal fume fever". Symptoms may be delayed for up to 12 hours and begin with the sudden onset of thirst, and a sweet, metallic or foul taste in the mouth. Other symptoms include upper respiratory tract irritation accompanied by coughing and a dryness of the mucous membranes, lassitude and a generalised feeling of malaise. Mild to severe headache, nausea, occasional vomiting, fever or chills, exaggerated mental activity, profuse sweating, diarrhoea, excessive urination and prostration may also occur. Tolerance to the fumes develops rapidly, but is quickly lost. All symptoms usually subside within 24-36 hours following removal from exposure. Not normally a hazard due to physical form of product.</p>
<b>Ingestion</b>	Not normally a hazard due to physical form of product.

## Ammunitions with Inert Projectile (Cartridges for Small Arms)

<b>Skin Contact</b>	<p>Skin contact with the material may produce toxic effects; systemic effects may result following absorption. There is some evidence to suggest that this material can cause inflammation of the skin on contact in some persons. The material may accentuate any pre-existing dermatitis condition</p> <p>Open cuts, abraded or irritated skin should not be exposed to this material</p> <p>Exposure to copper, by skin, has come from its use in pigments, ointments, ornaments, jewellery, dental amalgams and IUDs (intra-uterine devices), and in killing fungi and algae. Although copper is used in the treatment of water in swimming pools and reservoirs, there are no reports of toxicity from these applications.</p> <p>Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.</p> <p>Not normally a hazard due to physical form of product.</p>
<b>Eye</b>	This material can cause eye irritation and damage in some persons.
<b>Chronic</b>	<p>Long-term exposure to respiratory irritants may result in airways disease, involving difficulty breathing and related whole-body problems. Skin contact with the material is more likely to cause a sensitisation reaction in some persons compared to the general population.</p> <p>Ample evidence exists that this material directly causes reduced fertility</p> <p>Ample evidence exists that developmental disorders are directly caused by human exposure to the material.</p> <p>Ample evidence exists from experimentation that reduced human fertility is directly caused by exposure to the material.</p> <p>Ample evidence exists, from results in experimentation, that developmental disorders are directly caused by human exposure to the material.</p> <p>Based on experience with animal studies, exposure to the material may result in toxic effects to the development of the foetus, at levels which do not cause significant toxic effects to the mother.</p> <p>Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.</p> <p>Animal testing shows long term exposure to aluminium oxides may cause lung disease and cancer, depending on the size of the particle. The smaller the size, the greater the tendencies of causing harm.</p> <p>Lead, in large amounts, can affect the blood, nervous system, heart, glands, immune system and digestive system. Anaemia may occur.</p> <p>Lead can cross the placenta, and cause miscarriage, stillbirths and birth defects. Exposure before birth can cause mental retardation, behavioural disorders and infant death.</p> <p>For copper and its compounds (typically copper chloride):</p> <p>Acute toxicity: There are no reliable acute oral toxicity results available. Animal testing shows that skin in exposure to copper may lead to hardness of the skin, scar formation, exudation and reddish changes. Inflammation, irritation and injury of the skin were noted.</p> <p>Repeat dose toxicity: Animal testing shows that very high levels of copper monochloride may cause anaemia.</p> <p>Genetic toxicity: Copper monochloride does not appear to cause mutations in vivo, although chromosomal aberrations were seen at very high concentrations in vitro.</p> <p>Cancer-causing potential: There was insufficient information to evaluate the cancer-causing activity of copper monochloride.</p> <p>2,4-dinitrophenol can cause skin eruption, peripheral nerve damage, liver and kidney damage, and rarely cataracts. Repeated or prolonged contact may produce an allergic or irritant inflammation of the skin.</p> <p>Exposure over a long period of time to nitrophenols may produce kidney and liver damage. Inflammation of the colon, intestine, liver, stomach, and enlargement of the spleen may occur.</p>

Ammunitions with Inert Projectile (Cartridges for Small Arms)	TOXICITY	IRRITATION
	Not Available	Not Available
lead	TOXICITY	IRRITATION
	dermal (rat) LD50: >2000 mg/kg <sup>[1]</sup>	Not Available
	Inhalation(Rat) LC50; >5.05 mg/14h <sup>[1]</sup>	
Oral (Rat) LD50; >2000 mg/kg <sup>[1]</sup>		
copper	TOXICITY	IRRITATION
	dermal (rat) LD50: >2000 mg/kg <sup>[1]</sup>	Eye: no adverse effect observed (not irritating) <sup>[1]</sup>
	Inhalation(Rat) LC50; 0.733 mg/14h <sup>[1]</sup>	Skin: no adverse effect observed (not irritating) <sup>[1]</sup>
Oral (Mouse) LD50; 0.7 mg/kg <sup>[2]</sup>		
zinc	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: 1130 mg/kg <sup>[2]</sup>	Eye: no adverse effect observed (not irritating) <sup>[1]</sup>
Oral (Rat) LD50; >2000 mg/kg <sup>[1]</sup>	Skin: no adverse effect observed (not irritating) <sup>[1]</sup>	
nitrocellulose	TOXICITY	IRRITATION
	Oral (Rat) LD50; >5000 mg/kg <sup>[2]</sup>	Not Available
lead styphnate	TOXICITY	IRRITATION
	dermal (rat) LD50: >2000 mg/kg <sup>[1]</sup>	Not Available
	Inhalation(Rat) LC50; >5.05 mg/14h <sup>[1]</sup>	
Oral (Rat) LD50; >2000 mg/kg <sup>[1]</sup>		
tetrazene	TOXICITY	IRRITATION
	Not Available	Not Available
pentaerythritol tetranitrate	TOXICITY	IRRITATION
	Oral (Rat) LD50; 1660 mg/kg <sup>[2]</sup>	Not Available
nitroglycerin	TOXICITY	IRRITATION
	dermal (rat) LD50: >9560 mg/kg <sup>[1]</sup>	Eye: no adverse effect observed (not irritating) <sup>[1]</sup>
Oral (Rat) LD50; 105 mg/kg <sup>[2]</sup>	Skin: adverse effect observed (irritating) <sup>[1]</sup>	

## Ammunitions with Inert Projectile (Cartridges for Small Arms)

lead dioxide	<b>TOXICITY</b>	<b>IRRITATION</b>
	Oral (Rat) LD50; >2000 mg/kg <sup>[1]</sup>	Not Available
barium nitrate	<b>TOXICITY</b>	<b>IRRITATION</b>
	dermal (rat) LD50: >2000 mg/kg <sup>[1]</sup> Oral (Rat) LD50; >50<300 mg/kg <sup>[1]</sup>	Eye (rabbit):100 mg/24h - moderate Skin (rabbit): 500 mg/24h - mild
antimony trisulfide	<b>TOXICITY</b>	<b>IRRITATION</b>
	dermal (rat) LD50: >2000 mg/kg <sup>[1]</sup> Inhalation(Rat) LC50; >5.04 mg/4h <sup>[1]</sup> Oral (Rat) LD50; >2000 mg/kg <sup>[1]</sup>	Eye: no adverse effect observed (not irritating) <sup>[1]</sup> Skin: no adverse effect observed (not irritating) <sup>[1]</sup>
barium sulfate	<b>TOXICITY</b>	<b>IRRITATION</b>
	dermal (rat) LD50: >2000 mg/kg <sup>[1]</sup> Oral (Mouse) LD50; >3000 mg/kg <sup>[2]</sup>	Not Available
aluminium	<b>TOXICITY</b>	<b>IRRITATION</b>
	Inhalation(Rat) LC50; >2.3 mg/4h <sup>[1]</sup> Oral (Rat) LD50; >2000 mg/kg <sup>[1]</sup>	Eye: no adverse effect observed (not irritating) <sup>[1]</sup> Skin: no adverse effect observed (not irritating) <sup>[1]</sup>
<b>Legend:</b>	1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances	

<b>LEAD</b>	WARNING: Lead is a cumulative poison and has the potential to cause abortion and intellectual impairment to unborn children of pregnant workers.
<b>COPPER</b>	<p>WARNING: Inhalation of high concentrations of copper fume may cause "metal fume fever", an acute industrial disease of short duration. Symptoms are tiredness, influenza like respiratory tract irritation with fever.</p> <p>for copper and its compounds (typically copper chloride):</p> <p><b>Acute toxicity:</b> There are no reliable acute oral toxicity results available. In an acute dermal toxicity study (OECD TG 402), one group of 5 male rats and 5 groups of 5 female rats received doses of 1000, 1500 and 2000 mg/kg bw via dermal application for 24 hours. The LD50 values of copper monochloride were 2,000 mg/kg bw or greater for male (no deaths observed) and 1,224 mg/kg bw for female. Four females died at both 1500 and 2000 mg/kg bw, and one at 1,000 mg/kg bw. Symptom of the hardness of skin, an exudation of hardness site, the formation of scar and reddish changes were observed on application sites in all treated animals. Skin inflammation and injury were also noted. In addition, a reddish or black urine was observed in females at 2,000, 1,500 and 1,000 mg/kg bw. Female rats appeared to be more sensitive than male based on mortality and clinical signs.</p> <p>No reliable skin/eye irritation studies were available. The acute dermal study with copper monochloride suggests that it has a potential to cause skin irritation.</p> <p><b>Repeat dose toxicity:</b> In repeated dose toxicity study performed according to OECD TG 422, copper monochloride was given orally (gavage) to Sprague-Dawley rats for 30 days to males and for 39 - 51 days to females at concentrations of 0, 1.3, 5.0, 20, and 80 mg/kg bw/day. The NOAEL value was 5 and 1.3 mg/kg bw/day for male and female rats, respectively. No deaths were observed in male rats. One treatment-related death was observed in female rats in the high dose group. Erythropoietic toxicity (anaemia) was seen in both sexes at the 80 mg/kg bw/day. The frequency of squamous cell hyperplasia of the forestomach was increased in a dose-dependent manner in male and female rats at all treatment groups, and was statistically significant in males at doses of =20 mg/kg bw/day and in females at doses of =5 mg/kg bw/day doses. The observed effects are considered to be local, non-systemic effect on the forestomach which result from oral (gavage) administration of copper monochloride.</p> <p><b>Genotoxicity:</b> An in vitro genotoxicity study with copper monochloride showed negative results in a bacterial reverse mutation test with Salmonella typhimurium strains (TA 98, TA 100, TA 1535, and TA 1537) with and without S9 mix at concentrations of up to 1,000 ug/plate. An in vitro test for chromosome aberration in Chinese hamster lung (CHL) cells showed that copper monochloride induced structural and numerical aberrations at the concentration of 50, 70 and 100 ug/mL without S9 mix. In the presence of the metabolic activation system, significant increases of structural aberrations were observed at 50 and 70 ug/mL and significant increases of numerical aberrations were observed at 70 ug/mL. In an in vivo mammalian erythrocyte micronucleus assay, all animals dosed (15 - 60 mg/kg bw) with copper monochloride exhibited similar PCE/(PCE+NCE) ratios and MNPCE frequencies compared to those of the negative control animals. Therefore copper monochloride is not an in vivo mutagen.</p> <p><b>Carcinogenicity:</b> there was insufficient information to evaluate the carcinogenic activity of copper monochloride.</p> <p>Reproductive and developmental toxicity: In the combined repeated dose toxicity study with the reproduction/developmental toxicity screening test (OECD TG 422), copper monochloride was given orally (gavage) to Sprague-Dawley rats for 30 days to males and for 39-51 days to females at concentrations of 0, 1.3, 5.0, 20, and 80 mg/kg bw/day. The NOAEL of copper monochloride for fertility toxicity was 80 mg/kg bw/day for the parental animals. No treatment-related effects were observed on the reproductive organs and the fertility parameters assessed. For developmental toxicity the NOAEL was 20 mg/kg bw/day. Three of 120 pups appeared to have icterus at birth; 4 of 120 pups appeared runted at the highest dose tested (80 mg/kg bw/day).</p>
<b>LEAD STYPHNATE</b>	The following information refers to contact allergens as a group and may not be specific to this product. Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. The significance of the contact allergen is not simply determined by its sensitisation potential: the distribution of the substance and the opportunities for contact with it are equally important. A weakly sensitising substance which is widely distributed can be a more important allergen than one with stronger sensitising potential with which few individuals come into contact. From a clinical point of view, substances are noteworthy if they produce an allergic test reaction in more than 1% of the persons tested.
<b>TETRAZENE</b>	Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing, and the lack of minimal lymphocytic inflammation, without eosinophilia. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. On the other hand, industrial bronchitis is a disorder that occurs as a result of exposure due to high concentrations of irritating substance (often particles) and is completely reversible after exposure ceases. The disorder is characterized by difficulty breathing, cough and mucus production.

## Ammunitions with Inert Projectile (Cartridges for Small Arms)

<b>NITROGLYCERIN</b>	The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis. Substance has been investigated as a tumorigen, mutagen and reproductive effector. Equivocal tumorigen by RTECS criteria. Reproductive effector in rats.
<b>BARIUM NITRATE</b>	The material may produce moderate eye irritation leading to inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.
<b>ANTIMONY TRISULFIDE</b>	The substance is classified by IARC as Group 3: <b>NOT</b> classifiable as to its carcinogenicity to humans. Evidence of carcinogenicity may be inadequate or limited in animal testing. * REACH Dossier
<b>ZINC &amp; NITROCELLULOSE &amp; LEAD STYPHNATE &amp; TETRAZENE &amp; BARIUM SULFATE &amp; ALUMINIUM</b>	No significant acute toxicological data identified in literature search.
<b>ZINC &amp; NITROGLYCERIN &amp; BARIUM NITRATE</b>	The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.

<b>Acute Toxicity</b>	✓	<b>Carcinogenicity</b>	✗
<b>Skin Irritation/Corrosion</b>	✗	<b>Reproductivity</b>	✓
<b>Serious Eye Damage/Irritation</b>	✓	<b>STOT - Single Exposure</b>	✗
<b>Respiratory or Skin sensitisation</b>	✓	<b>STOT - Repeated Exposure</b>	✗
<b>Mutagenicity</b>	✗	<b>Aspiration Hazard</b>	✗

**Legend:** ✗ – Data either not available or does not fill the criteria for classification  
✓ – Data available to make classification

## SECTION 12 Ecological information

## Toxicity

Ammunitions with Inert Projectile (Cartridges for Small Arms)	Endpoint	Test Duration (hr)	Species	Value	Source	
		Not Available	Not Available	Not Available	Not Available	Not Available
lead	Endpoint	Test Duration (hr)	Species	Value	Source	
	NOEC(ECx)	Not Available	Crustacea	0.051mg/L	5	
	LC50	96h	Fish	1.17mg/l	4	
	EC50	72h	Algae or other aquatic plants	1.191mg/L	4	
	EC50	96h	Algae or other aquatic plants	0.282-0.864mg/l	4	
copper	Endpoint	Test Duration (hr)	Species	Value	Source	
	EC50(ECx)	24h	Algae or other aquatic plants	<0.001mg/L	4	
	LC50	96h	Fish	~0.005mg/L	4	
	EC50	72h	Algae or other aquatic plants	0.011-0.017mg/L	4	
	EC50	48h	Crustacea	<0.001mg/L	4	
zinc	Endpoint	Test Duration (hr)	Species	Value	Source	
	EC50(ECx)	72h	Algae or other aquatic plants	0.005mg/l	4	
	LC50	96h	Fish	0.16mg/L	4	
	EC50	72h	Algae or other aquatic plants	0.005mg/l	4	
	EC50	48h	Crustacea	1.4mg/l	2	
nitrocellulose	Endpoint	Test Duration (hr)	Species	Value	Source	
	EC50	96h	Algae or other aquatic plants	0.264-0.881mg/l	4	
	Not Available	Not Available	Not Available	Not Available	Not Available	
	lead styphnate	Endpoint	Test Duration (hr)	Species	Value	Source
		EC10(ECx)	48h	Crustacea	0.5mg/l	2
EC50		48h	Crustacea	7.02mg/l	2	
tetrazene	Endpoint	Test Duration (hr)	Species	Value	Source	
	Not Available	Not Available	Not Available	Not Available	Not Available	
pentaerythritol tetranitrate	Endpoint	Test Duration (hr)	Species	Value	Source	
	EC50(ECx)	24h	Crustacea	>49mg/l	4	

Continued...



## Ammunitions with Inert Projectile (Cartridges for Small Arms)

	LC50	96h	Fish	~926mg/l	2
	EC50	48h	Crustacea	>49mg/l	4
nitroglycerin	<b>Endpoint</b>	<b>Test Duration (hr)</b>	<b>Species</b>	<b>Value</b>	<b>Source</b>
	NOEC(ECx)	1440h	Fish	0.03mg/l	2
	LC50	96h	Fish	1.69-2.14mg/l	4
	EC50	48h	Crustacea	4655mg/l	1
	EC50	96h	Algae or other aquatic plants	0.1-1.3mg/l	4
lead dioxide	<b>Endpoint</b>	<b>Test Duration (hr)</b>	<b>Species</b>	<b>Value</b>	<b>Source</b>
	Not Available	Not Available	Not Available	Not Available	Not Available
barium nitrate	<b>Endpoint</b>	<b>Test Duration (hr)</b>	<b>Species</b>	<b>Value</b>	<b>Source</b>
	NOEC(ECx)	72h	Algae or other aquatic plants	>=1.15mg/l	2
	LC50	96h	Fish	>3.5mg/l	2
	EC50	72h	Algae or other aquatic plants	>1.15mg/l	2
	EC50	48h	Crustacea	>=16<=18mg/l	2
antimony trisulfide	<b>Endpoint</b>	<b>Test Duration (hr)</b>	<b>Species</b>	<b>Value</b>	<b>Source</b>
	NOEC(ECx)	2160h	Algae or other aquatic plants	0.032mg/l	2
	LC50	96h	Fish	0.93mg/l	2
	EC50	72h	Algae or other aquatic plants	>2.4mg/l	2
	EC50	48h	Crustacea	423.45mg/l	2
	EC50	96h	Algae or other aquatic plants	0.61mg/l	2
barium sulfate	<b>Endpoint</b>	<b>Test Duration (hr)</b>	<b>Species</b>	<b>Value</b>	<b>Source</b>
	NOEC(ECx)	72h	Algae or other aquatic plants	>=1.15mg/l	2
	LC50	96h	Fish	>3.5mg/l	2
	EC50	72h	Algae or other aquatic plants	>1.15mg/l	2
	EC50	48h	Crustacea	32mg/l	4
aluminium	<b>Endpoint</b>	<b>Test Duration (hr)</b>	<b>Species</b>	<b>Value</b>	<b>Source</b>
	NOEC(ECx)	48h	Crustacea	>100mg/l	1
	LC50	96h	Fish	0.078-0.108mg/l	2
	EC50	72h	Algae or other aquatic plants	0.2mg/l	2
	EC50	48h	Crustacea	1.5mg/l	2
	EC50	96h	Algae or other aquatic plants	0.024mg/l	2
<b>Legend:</b>	Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data				

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**DO NOT** discharge into sewer or waterways.

## Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
tetrazene	HIGH	HIGH
nitroglycerin	LOW (Half-life = 14 days)	LOW (Half-life = 0.73 days)

## Bioaccumulative potential

Ingredient	Bioaccumulation
tetrazene	LOW (LogKOW = -2.0204)

## Mobility in soil

Ingredient	Mobility
tetrazene	LOW (KOC = 238.4)

## SECTION 13 Disposal considerations

## Waste treatment methods

<b>Product / Packaging disposal</b>	<ul style="list-style-type: none"> <li>Containers may still present a chemical hazard/ danger when empty.</li> <li>Return to supplier for reuse/ recycling if possible.</li> </ul>
-------------------------------------	--

Continued...

## Ammunitions with Inert Projectile (Cartridges for Small Arms)

**Otherwise:**

- ▶ If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.
- ▶ Where possible retain label warnings and SDS and observe all notices pertaining to the product.

**For nitroglycerine and similar products:**

- ▶ Contaminated cloths and sawdust are disposed of at the burning ground by following the appropriate Factory Procedure.
- ▶ The spill area is decontaminated using NG Decontamination Solution'
- ▶ Buildings and equipment taken from service in an NG environment must be decontaminated and inspected.
- ▶ Explosives which are surplus, deteriorated or considered unsafe for transport, storage or use shall be destroyed and the statutory authorities shall be notified.
- ▶ Explosives must not be thrown away, buried, discarded or placed with garbage.
- ▶ This material may be disposed of by burning or detonation but the operation must be performed under the control of a person competent in the destruction of explosives.

**Disposal by detonation:**

- ▶ The explosives to be destroyed must be placed in direct contact with fresh priming charge in a hole which is at least 0.6 metre deep and then adequately stemmed.
- ▶ No detonators shall be inserted into defective explosives.
- ▶ Personnel must be evacuated to a safe distance prior to initiation/firing of the charge.

**Disposal by burning:**



- ▶ Make a sawdust bed or trail adequate for the quantity of explosives to be burned, approximately 400 mm wide and 40 mm deep, upon which the explosive will be laid.
- ▶ If sawdust is not available, newspaper may be used.
- ▶ Normal precautions shall be taken to avoid the spread of fire.
- ▶ Individual trails should not be closer together than 600 mm and should contain not more than 12 kg of explosive.
- ▶ Trails should be side by side, NOT in-line, and not more than four should be set up at one time.
- ▶ Remove any explosive that is not to be burnt to a distance of at least 300 metre.
- ▶ Sufficient diesel oil (never petrol or other highly flammable liquid) should be used to thoroughly wet the sawdust (or paper) at least 4 litre per trail is recommended.
- ▶ Light the trail from a long, rolled paper wick which should be placed downwind and in contact with the end 1m of trail that is not covered with explosive. The wind should blow so that the flame from the wick (and later from the burning explosive) will blow away from the unburned explosive as detonation is more likely to occur if the explosive is preheated by the flame.
- ▶ If plastic igniter cord (slow) is available, its use for lighting is recommended instead of paper. One end should be coiled into the sawdust or under the paper and the other end lit from a minimum distance of 7m from the trail.
- ▶ Retire at least 300m or to a safe place.
- ▶ **DO NOT return to the site for at least 30 minutes after the burning has apparently finished.**
- ▶ If the fire goes out do not approach for at least 15 minutes after all trace of fire has gone.
- ▶ **DO NOT add more diesel oil unless certain that the flame is completely extinguished.**

**[DYN0]**

- ▶ **DO NOT allow wash water from cleaning or process equipment to enter drains.**
- ▶ It may be necessary to collect all wash water for treatment before disposal.
- ▶ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- ▶ Where in doubt contact the responsible authority.

### SECTION 14 Transport information

#### Labels Required

	
Marine Pollutant	
HAZCHEM	1YE

#### Land transport (ADG)

UN number	0012	
UN proper shipping name	CARTRIDGES FOR WEAPONS, INERT PROJECTILE or CARTRIDGES, SMALL ARMS	
Transport hazard class(es)	Class	1.4S
	Subrisk	Not Applicable
Packing group	Not Applicable	
Environmental hazard	Environmentally hazardous	
Special precautions for user	Special provisions	364
	Limited quantity	5 kg

#### Air transport (ICAO-IATA / DGR)

UN number	0012	
UN proper shipping name	Cartridges for weapons, inert projectile	
Transport hazard class(es)	ICAO/IATA Class	1.4S
	ICAO / IATA Subrisk	Not Applicable

## Ammunitions with Inert Projectile (Cartridges for Small Arms)

	ERG Code	3L
<b>Packing group</b>	Not Applicable	
<b>Environmental hazard</b>	Environmentally hazardous	
<b>Special precautions for user</b>	Special provisions	A802
	Cargo Only Packing Instructions	130
	Cargo Only Maximum Qty / Pack	100 kg
	Passenger and Cargo Packing Instructions	130
	Passenger and Cargo Maximum Qty / Pack	25 kg
	Passenger and Cargo Limited Quantity Packing Instructions	Forbidden
	Passenger and Cargo Limited Maximum Qty / Pack	Forbidden

## Sea transport (IMDG-Code / GGVSee)

<b>UN number</b>	0012	
<b>UN proper shipping name</b>	CARTRIDGES FOR WEAPONS, INERT PROJECTILE or CARTRIDGES, SMALL ARMS	
<b>Transport hazard class(es)</b>	IMDG Class	1.4S
	IMDG Subrisk	Not Applicable
<b>Packing group</b>	Not Applicable	
<b>Environmental hazard</b>	Marine Pollutant	
<b>Special precautions for user</b>	EMS Number	F-B, S-X
	Special provisions	364
	Limited Quantities	5 kg

## Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

## Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
lead	Not Available
copper	Not Available
zinc	Not Available
nitrocellulose	Not Available
lead styphnate	Not Available
tetrazene	Not Available
pentaerythritol tetranitrate	Not Available
nitroglycerin	Not Available
lead dioxide	Not Available
barium nitrate	Not Available
antimony trisulfide	Not Available
barium sulfate	Not Available
aluminium	Not Available

## Transport in bulk in accordance with the ICG Code

Product name	Ship Type
lead	Not Available
copper	Not Available
zinc	Not Available
nitrocellulose	Not Available
lead styphnate	Not Available
tetrazene	Not Available
pentaerythritol tetranitrate	Not Available
nitroglycerin	Not Available
lead dioxide	Not Available
barium nitrate	Not Available
antimony trisulfide	Not Available
barium sulfate	Not Available
aluminium	Not Available

## SECTION 15 Regulatory information

## Ammunitions with Inert Projectile (Cartridges for Small Arms)

### Safety, health and environmental regulations / legislation specific for the substance or mixture

#### lead is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals  
 Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 4  
 Australian Inventory of Industrial Chemicals (AIIC)  
 Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs  
 International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 1: Carcinogenic to humans  
 International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 2B: Possibly carcinogenic to humans  
 International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

#### copper is found on the following regulatory lists

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 4  
 Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5  
 Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 6

Australian Inventory of Industrial Chemicals (AIIC)  
 International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

#### zinc is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals  
 Australian Inventory of Industrial Chemicals (AIIC)

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

#### nitrocellulose is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals  
 Australian Inventory of Industrial Chemicals (AIIC)

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

#### lead styphnate is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals  
 Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 10 / Appendix C  
 Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5  
 Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 6

Australian Inventory of Industrial Chemicals (AIIC)  
 Chemical Footprint Project - Chemicals of High Concern List  
 International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs  
 International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

#### tetrazene is found on the following regulatory lists

Australian Inventory of Industrial Chemicals (AIIC)

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

#### pentaerythritol tetranitrate is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals  
 Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 4  
 Australian Inventory of Industrial Chemicals (AIIC)

FEI Equine Prohibited Substances List - Banned Substances  
 FEI Equine Prohibited Substances List (EPSL)

#### nitroglycerin is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals  
 Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 3  
 Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 4

Australian Inventory of Industrial Chemicals (AIIC)  
 FEI Equine Prohibited Substances List - Controlled Medication  
 FEI Equine Prohibited Substances List (EPSL)

#### lead dioxide is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals  
 Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 10 / Appendix C  
 Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5  
 Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 6  
 Australian Inventory of Industrial Chemicals (AIIC)

Chemical Footprint Project - Chemicals of High Concern List  
 International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs  
 International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 2A: Probably carcinogenic to humans  
 International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

#### barium nitrate is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals  
 Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 6  
 Australian Inventory of Industrial Chemicals (AIIC)

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs  
 International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 2A: Probably carcinogenic to humans

#### antimony trisulfide is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals  
 Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 6  
 Australian Inventory of Industrial Chemicals (AIIC)

Chemical Footprint Project - Chemicals of High Concern List  
 International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs  
 International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

#### barium sulfate is found on the following regulatory lists

Australian Inventory of Industrial Chemicals (AIIC)

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

## Ammunitions with Inert Projectile (Cartridges for Small Arms)

## aluminium is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals  
Australian Inventory of Industrial Chemicals (AIIC)

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for  
Manufactured Nanomaterials (MNMS)

## National Inventory Status

National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	Yes
Canada - DSL	No (tetrazene)
Canada - NDSL	No (lead; copper; zinc; nitrocellulose; lead styphnate; pentaerythritol tetranitrate; nitroglycerin; lead dioxide; barium nitrate; antimony trisulfide; barium sulfate; aluminium)
China - IECSC	No (lead styphnate; tetrazene)
Europe - EINEC / ELINCS / NLP	No (nitrocellulose)
Japan - ENCS	No (lead; copper; zinc; tetrazene; aluminium)
Korea - KECI	No (tetrazene)
New Zealand - NZIoC	Yes
Philippines - PICCS	No (lead styphnate; tetrazene; pentaerythritol tetranitrate)
USA - TSCA	Yes
Taiwan - TCSI	No (tetrazene)
Mexico - INSQ	No (tetrazene)
Vietnam - NCI	No (lead styphnate; tetrazene)
Russia - FBEPH	No (lead styphnate; tetrazene)
<b>Legend:</b>	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

## SECTION 16 Other information

<b>Revision Date</b>	14/03/2022
<b>Initial Date</b>	14/03/2022

## SDS Version Summary

Version	Date of Update	Sections Updated
2.1	14/03/2022	Acute Health (eye), Acute Health (inhaled), Acute Health (skin), Acute Health (swallowed), Chronic Health, Classification, Fire Fighter (fire/explosion hazard)

## Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

## Definitions and abbreviations

PC—TWA: Permissible Concentration-Time Weighted Average  
PC—STEL: Permissible Concentration-Short Term Exposure Limit  
IARC: International Agency for Research on Cancer  
ACGIH: American Conference of Governmental Industrial Hygienists  
STEL: Short Term Exposure Limit  
TEEL: Temporary Emergency Exposure Limit.  
IDLH: Immediately Dangerous to Life or Health Concentrations  
ES: Exposure Standard  
OSF: Odour Safety Factor  
NOAEL :No Observed Adverse Effect Level  
LOAEL: Lowest Observed Adverse Effect Level  
TLV: Threshold Limit Value  
LOD: Limit Of Detection  
OTV: Odour Threshold Value  
BCF: BioConcentration Factors  
BEI: Biological Exposure Index  
AIIC: Australian Inventory of Industrial Chemicals  
DSL: Domestic Substances List  
NDSL: Non-Domestic Substances List  
IECSC: Inventory of Existing Chemical Substance in China  
EINECS: European Inventory of Existing Commercial chemical Substances  
ELINCS: European List of Notified Chemical Substances  
NLP: No-Longer Polymers  
ENCS: Existing and New Chemical Substances Inventory  
KECI: Korea Existing Chemicals Inventory  
NZIoC: New Zealand Inventory of Chemicals  
PICCS: Philippine Inventory of Chemicals and Chemical Substances  
TSCA: Toxic Substances Control Act  
TCSI: Taiwan Chemical Substance Inventory  
INSQ: Inventario Nacional de Sustancias Químicas

## **Ammunitions with Inert Projectile (Cartridges for Small Arms)**

NCI: National Chemical Inventory

FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.