

Li-MnO₂ Button Cell(Lithium Metal Battery) CR2032

TSA OUTDOORS

Chemwatch Hazard Alert Code: 4

Chemwatch: 5543-74

Version No: 2.1

Safety Data Sheet according to WHS Regulations (Hazardous Chemicals) Amendment 2020 and ADG requirements

Issue Date: 08/06/2022

Print Date: 09/06/2022

S.GHS.AUS.EN

SECTION 1 Identification of the substance / mixture and of the company / undertaking

Product Identifier

Product name	Li-MnO ₂ Button Cell(Lithium Metal Battery) CR2032
Chemical Name	Not Applicable
Synonyms	PLU 573817
Chemical formula	Not Applicable
Other means of identification	Not Available

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Power supply. NOTE: Hazard statement relates to battery contents. Potential for exposure should not exist unless the battery leaks, is exposed to high temperatures or is mechanically, physically or electrically abused.
--------------------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Details of the supplier of the safety data sheet

Registered company name	TSA OUTDOORS
Address	Unit 6/ 9 - 13 Winbourne Road Brookvale NSW 2100 Australia
Telephone	+61 2 9938 3244
Fax	+61 2 9939 2972
Website	Tsaoutdoors.com.au
Email	sales@tasco.com.au

Emergency telephone number

Association / Organisation	Aaron Millard	CHEMWATCH EMERGENCY RESPONSE
Emergency telephone numbers	+61 450 086 593 (Mon-Fri, 9 am-6pm)	+61 1800 951 288
Other emergency telephone numbers	Not Available	+61 3 9573 3188


Once connected and if the message is not in your preferred language then please dial 01

SECTION 2 Hazards identification

Classification of the substance or mixture

Poisons Schedule	Not Applicable
Classification [1]	Acute Toxicity (Oral) Category 4, Skin Corrosion/Irritation Category 2, Sensitisation (Skin) Category 1, Serious Eye Damage/Eye Irritation Category 2A, Acute Toxicity (Inhalation) Category 4, Carcinogenicity Category 1A, Reproductive Toxicity Category 1B, Specific Target Organ Toxicity - Repeated Exposure Category 1, Hazardous to the Aquatic Environment Long-Term Hazard Category 3
Legend:	1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI

Label elements

Hazard pictogram(s)	
Signal word	Danger

Hazard statement(s)

H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.

Li-MnO2 Button Cell(Lithium Metal Battery) CR2032

H350	May cause cancer.
H360FD	May damage fertility. May damage the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statement(s) Prevention

P201	Obtain special instructions before use.
P260	Do not breathe dust/fume.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves, protective clothing, eye protection and face protection.
P264	Wash all exposed external body areas thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P273	Avoid release to the environment.
P272	Contaminated work clothing should not be allowed out of the workplace.

Precautionary statement(s) Response

P308+P313	IF exposed or concerned: Get medical advice/ attention.
P302+P352	IF ON SKIN: Wash with plenty of water and soap.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P301+P312	IF SWALLOWED: Call a POISON CENTER/doctor/physician/first aider if you feel unwell.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P330	Rinse mouth.

Precautionary statement(s) Storage

P405	Store locked up.
------	------------------

Precautionary statement(s) Disposal

P501	Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.
------	----------------------------------------------------------------------------------------------------------------------------------

Not Applicable

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
Not Available		hermetically sealed metal case with
12597-68-1	50.5	<u>Stainless Steel</u>
1313-13-9	30.99	<u>manganese dioxide</u>
7791-03-9	4	<u>lithium perchlorate</u>
9003-07-0	3.76	<u>polypropylene</u>
108-32-7	3	<u>propylene carbonate</u>
7782-42-5	2.17	<u>graphite</u>
9002-84-0	2.17	<u>polytetrafluoroethylene</u>
7439-93-2	1.91	<u>lithium</u>
110-71-4	1.5	<u>1,2-dimethoxyethane</u>

Legend: 1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. Classification drawn from C&L; * EU IOELVs available

SECTION 4 First aid measures

Description of first aid measures

Eye Contact	<ul style="list-style-type: none"> ▶ Generally not applicable. ▶ If this product comes in contact with eyes: <ul style="list-style-type: none"> ▶ Wash out immediately with water. ▶ If irritation continues, seek medical attention. ▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
-------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Continued...

Li-MnO₂ Button Cell(Lithium Metal Battery) CR2032

Skin Contact	<ul style="list-style-type: none"> ▶ Generally not applicable. If skin or hair contact occurs: <ul style="list-style-type: none"> ▶ Flush skin and hair with running water (and soap if available). ▶ Seek medical attention in event of irritation.
Inhalation	<ul style="list-style-type: none"> ▶ Generally not applicable. ▶ If fumes, aerosols or combustion products are inhaled remove from contaminated area. ▶ Other measures are usually unnecessary.
Ingestion	<ul style="list-style-type: none"> ▶ Generally not applicable. Not considered a normal route of entry. <ul style="list-style-type: none"> ▶ If swallowed do NOT induce vomiting. ▶ If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. ▶ Observe the patient carefully. ▶ Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. ▶ Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. ▶ Seek medical advice.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 Firefighting measures**Extinguishing media**

- ▶ Dry chemical powder.
- ▶ BCF (where regulations permit).
- ▶ Carbon dioxide.

Special hazards arising from the substrate or mixture

Fire Incompatibility	None known. <ul style="list-style-type: none"> ▶ Keep dry ▶ NOTE: May develop pressure in containers; open carefully. Vent periodically.
-----------------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Advice for firefighters

Fire Fighting	Slight hazard when exposed to heat, flame and oxidisers.
Fire/Explosion Hazard	<ul style="list-style-type: none"> ▶ Non combustible. ▶ Not considered to be a significant fire risk. ▶ Heating may cause expansion or decomposition leading to violent rupture of containers. ▶ May emit acrid smoke. May emit corrosive and poisonous fumes. Articles and manufactured articles may constitute a fire hazard where polymers form their outer layers or where combustible packaging remains in place. Certain substances, found throughout their construction, may degrade or become volatile when heated to high temperatures. This may create a secondary hazard.
HAZCHEM	Not Applicable

SECTION 6 Accidental release measures**Personal precautions, protective equipment and emergency procedures**

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	Clean up all spills immediately. Avoid contact with skin and eyes. Place in suitable containers for disposal.
Major Spills	<ul style="list-style-type: none"> ▶ Clean up all spills immediately. ▶ Wear protective clothing, safety glasses, dust mask, gloves. ▶ Secure load if safe to do so. Bundle/collect recoverable product. ▶ Use dry clean up procedures and avoid generating dust. ▶ Vacuum up (consider explosion-proof machines designed to be grounded during storage and use). ▶ Water may be used to prevent dusting. ▶ Collect remaining material in containers with covers for disposal. ▶ Flush spill area with water.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage**Precautions for safe handling**

Safe handling	Do not connect the positive terminal to the negative terminal with electrical wire or chain. Avoid polarity reverse connection when installing the battery to an instrument. Do not wet the battery with water, seawater or acid; or expose to strong oxidizer. Do not damage or remove the external tube. Keep the battery away from heat and fire. Do not disassemble or reconstruct the battery; or solder the battery directly. Do not give a mechanical shock or deform. Do not use unauthorized charger or other charging method. This battery is manufactured in a charged state. It is NOT designed for recharging. Recharging can cause battery leakage or in some cases, high pressure rupture. Inadvertent charging can occur if
----------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Li-MnO2 Button Cell(Lithium Metal Battery) CR2032

	a battery is installed backwards. Use good occupational work practice. Observe manufacturer's storage and handling recommendations contained within this SDS. Avoid physical damage to containers.
Other information	<ul style="list-style-type: none"> ▶ Keep dry. ▶ Store under cover. ▶ Protect containers against physical damage. ▶ Observe manufacturer's storage and handling recommendations contained within this SDS. Keep out of reach of children. Store out of direct sunlight <ul style="list-style-type: none"> ▶ Store away from incompatible materials.

Conditions for safe storage, including any incompatibilities

Suitable container	Generally packaging as originally supplied with the article or manufactured item is sufficient to protect against physical hazards. If repackaging is required ensure the article is intact and does not show signs of wear. As far as is practicably possible, reuse the original packaging or something providing a similar level of protection to both the article and the handler.
Storage incompatibility	Avoid contamination of water, foodstuffs, feed or seed. <ul style="list-style-type: none"> ▶ Keep dry ▶ NOTE: May develop pressure in containers; open carefully. Vent periodically.

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Australia Exposure Standards	manganese dioxide	Manganese, dust & compounds (as Mn)	1 mg/m3	Not Available	Not Available	Not Available
Australia Exposure Standards	graphite	Graphite (all forms except fibres) (respirable dust) (natural & synthetic)	3 mg/m3	Not Available	Not Available	(e) Containing no asbestos and < 1% crystalline silica.

Emergency Limits

Ingredient	TEEL-1	TEEL-2	TEEL-3
manganese dioxide	4.7 mg/m3	7.9 mg/m3	690 mg/m3
manganese dioxide	4.2 mg/m3	6.9 mg/m3	41 mg/m3
lithium perchlorate	1.2 mg/m3	13 mg/m3	79 mg/m3
polypropylene	5.2 mg/m3	58 mg/m3	350 mg/m3
propylene carbonate	34 mg/m3	370 mg/m3	2,200 mg/m3
graphite	6 mg/m3	330 mg/m3	2,000 mg/m3
polytetrafluoroethylene	12 mg/m3	130 mg/m3	790 mg/m3
lithium	3.3 mg/m3	36 mg/m3	220 mg/m3
1,2-dimethoxyethane	13 ppm	140 ppm	840 ppm

Ingredient	Original IDLH	Revised IDLH
Stainless Steel	Not Available	Not Available
manganese dioxide	500 mg/m3	Not Available
lithium perchlorate	Not Available	Not Available
polypropylene	Not Available	Not Available
propylene carbonate	Not Available	Not Available
graphite	1,250 mg/m3	Not Available
polytetrafluoroethylene	Not Available	Not Available
lithium	Not Available	Not Available
1,2-dimethoxyethane	Not Available	Not Available

Occupational Exposure Banding


Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit
Stainless Steel	E	≤ 0.01 mg/m³
lithium perchlorate	E	≤ 0.01 mg/m³
propylene carbonate	E	≤ 0.1 ppm
lithium	C	> 0.1 to ≤ milligrams per cubic meter of air (mg/m³)
1,2-dimethoxyethane	E	≤ 0.1 ppm

Notes: Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.

Exposure controls

Appropriate engineering controls	General exhaust is adequate under normal operating conditions. Articles or manufactured items, in their original condition, generally don't require engineering controls during handling or in normal use. Exceptions may arise following extensive use and subsequent wear, during recycling or disposal operations where substances, found in the
-----------------------------------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Li-MnO₂ Button Cell(Lithium Metal Battery) CR2032

	article, may be released to the environment.
Personal protection	
Eye and face protection	None under normal operating conditions. OTHERWISE: ▶ Safety glasses.
Skin protection	See Hand protection below
Hands/feet protection	None under normal operating conditions. OTHERWISE: ▶ Rubber Gloves
Body protection	See Other protection below
Other protection	No special equipment needed when handling small quantities

Recommended material(s)**GLOVE SELECTION INDEX**

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the **computer-generated** selection:

Li-MnO₂ Button Cell(Lithium Metal Battery) CR2032

Material	CPI
BUTYL	A

* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

Respiratory protection

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required.

Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	A-AUS P3	-	A-PAPR-AUS / Class 1 P3
up to 50 x ES	-	A-AUS / Class 1 P3	-
up to 100 x ES	-	A-2 P3	A-PAPR-2 P3 ^

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO₂), G = Agricultural chemicals, K = Ammonia(NH₃), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

Respiratory protection not normally required due to the physical form of the product.

SECTION 9 Physical and chemical properties**Information on basic physical and chemical properties**

Appearance	Metallic solid with no odour; insoluble in water.		
Physical state	Manufactured	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Applicable
pH (as supplied)	Not Applicable	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Applicable
Initial boiling point and boiling range (°C)	Not Applicable	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	Not Applicable	Taste	Not Available
Evaporation rate	Not Applicable	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Applicable	Surface Tension (dyn/cm or mN/m)	Not Applicable
Lower Explosive Limit (%)	Not Applicable	Volatile Component (%vol)	Not Applicable
Vapour pressure (kPa)	Not Applicable	Gas group	Not Available
Solubility in water	Immiscible	pH as a solution (Not Available%)	Not Applicable
Vapour density (Air = 1)	Not Applicable	VOC g/L	Not Applicable

SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	<ul style="list-style-type: none"> ▶ Unstable in the presence of incompatible materials. ▶ Product is considered stable. ▶ Hazardous polymerisation will not occur.

Li-MnO₂ Button Cell(Lithium Metal Battery) CR2032

Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 Toxicological information

Information on toxicological effects

Inhaled	Vapors or fumes may cause respiratory tract irritation. Not normally a hazard due to physical form of product.
Ingestion	Considered an unlikely route of entry in commercial/industrial environments Ingestion may result in nausea, abdominal irritation, pain and vomiting
Skin Contact	The electrolyte causes severe skin burns and irritation. Not normally a hazard due to physical form of product.
Eye	The electrolyte causes eye irritation and damage. Not normally a hazard due to physical form of product.
Chronic	The chemicals in this product are contained in a sealed case and exposure does not occur during normal handling and use. Not normally a hazard due to physical form of product.

Li-MnO₂ Button Cell(Lithium Metal Battery) CR2032	TOXICITY	IRRITATION
	Not Available	Not Available
Stainless Steel	TOXICITY	IRRITATION
	Not Available	Not Available
manganese dioxide	TOXICITY	IRRITATION
	Oral (Rat) LD50; >3478 mg/kg ^[2]	Eye: no adverse effect observed (not irritating) ^[1] Skin: no adverse effect observed (not irritating) ^[1]
lithium perchlorate	TOXICITY	IRRITATION
	Oral (Rat) LD50; >300<2000 mg/kg ^[1]	Eye: adverse effect observed (irreversible damage) ^[1] Skin: adverse effect observed (corrosive) ^[1]
polypropylene	TOXICITY	IRRITATION
	Oral (Mouse) LD50; 3200 mg/kg ^[2]	Not Available
propylene carbonate	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: >=2000 mg/kg ^[1]	Eye (rabbit): 60 mg - moderate
	Oral (Rat) LD50; >5000 mg/kg ^[1]	Eye: adverse effect observed (irritating) ^[1] Skin (human): 100 mg/3d-I moderate Skin (rabbit): 500 mg moderate
		Skin: no adverse effect observed (not irritating) ^[1]
graphite	TOXICITY	IRRITATION
	Inhalation(Rat) LC50; >2 mg/L4h ^[1] Oral (Rat) LD50; >2000 mg/kg ^[1]	Not Available
polytetrafluoroethylene	TOXICITY	IRRITATION
	Oral (Rat) LD50; 1250 mg/kg ^[2]	Not Available
lithium	TOXICITY	IRRITATION
	Not Available	Eye: adverse effect observed (irritating) ^[1] Skin: adverse effect observed (corrosive) ^[1]
1,2-dimethoxyethane	TOXICITY	IRRITATION
	dermal (guinea pig) LD50: 5 mg/kg ^[2] Inhalation(Rat) LC50; 3000 ppm4h ^[2]	Not Available
	Oral (Rabbit) LD50; 320 mg/kg ^[2]	
Legend:	1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances	

STAINLESS STEEL	<p>The following information refers to contact allergens as a group and may not be specific to this product. Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. The significance of the contact allergen is not simply determined by its sensitisation potential: the distribution of the substance and the opportunities for contact with it are equally important. A weakly sensitising substance which is widely distributed can be a more important allergen than one with stronger sensitising potential with which few individuals come into contact. From a clinical point of view, substances are noteworthy if they produce an allergic test reaction in more than 1% of the persons tested. On skin and inhalation exposure, chromium and its compounds (except hexavalent) can be a potent sensitiser, as particulates. Studies show that they have a complex toxicity mechanism with hexavalent chromium associated with an increased risk of lung damage and respiratory cancers (primarily bronchogenic and nose cancers). However, there is no evidence that elemental, divalent, or trivalent chromium compounds causes cancer or genetic toxicity.</p>
POLYPROPYLENE	<p>* For pyrolyzate For poly-alpha-olefins (PAOs): PAOs are highly branched, isoparaffinic chemicals produced by oligomerisation of 1-octene, 1-decene and/or 1-dodecene. The crude polyalphaolefin mixture is then distilled into appropriate product fractions to meet specific viscosity specifications and hydrogenated. In existing data, there appears to be no data to show that these structural analogs cause health effects. In addition, there is evidence in the literature that alkanes with 30 or more carbon atoms are unlikely to be absorbed when given by mouth. The physical and chemical properties make it unlikely that significant absorption into the body will occur. There are also no functional groups on PAO molecules that are biologically active. PAOs also have low volatility, so that exposure is unlikely to occur by inhalation. The high viscosity of these substances also makes it hard to generate a high concentration of breathable particles in air. Acute toxicity: Animal testing shows that PAOs have relatively low acute toxicity. Repeat dose toxicity: Animal testing shows that PAOs show low repeat dose toxicity – some increased scaling of the skin occurred, with skin inflammation, after exposure at high doses. Reproductive toxicity: Animal testing suggested that application of PAO to skin did not impair reproductive performance. Genetic toxicity: Testing has not shown any evidence that PAOs cause mutations or chromosomal aberrations. Cancer-causing potentials: Animal testing has not shown any propensity to cause tumours. While alpha-olefin polymers have similar properties to mineral oils, they do not contain polycyclic aromatic hydrocarbons, or other known cancer-causing materials.</p>
PROPYLENE CARBONATE	<p>WARNING: This substance has been classified by the IARC as Group 2B: Possibly Carcinogenic to Humans. The material may produce moderate eye irritation leading to inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis. The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin. for propylene carbonate: Numerous adequate and reliable acute toxicity tests are available on propylene carbonate. Oral and dermal tests meet OECD and EPA test guidelines. Propylene carbonate is practically nontoxic following acute exposures; the oral LD50 is >.5000 mg/kg and the dermal LD50 is >3000 mg/kg. No further testing is recommended. Subchronic studies (13- 14 weeks) of propylene carbonate by inhalation (aerosol) and oral (gavage) routes were conducted in rats according to current guidelines. The oral study indicated low systemic toxicity from propylene carbonate (NOAEL = 5000 mg/kg/day). In the inhalation study, no systemic toxicity was seen at concentrations up to 1000 mg/m³; however, there was periorcular irritation and swelling in a few males at 500 and 1000 mg/m³. A dermal carcinogenicity study in mice did not indicate tumorigenic potential or systemic toxicity from 2 years of exposure to propylene carbonate. No further testing is recommended. There is a negative Ames <i>in vitro</i> mutagenicity assay of propylene carbonate. A single intraperitoneal injection of 1666 mg/kg propylene carbonate did not induce an increase in micronuclei when examined after 30,48 and 72 hours. The mutagenicity battery is satisfactorily filled; no further mutagenicity testing is recommended. Gavage administration of propylene carbonate to pregnant rats days 6-15 of gestation resulted in systemic toxicity at doses of 3000 and 5000 mg/kg/day, including mortality (not seen in 13 week study of non-pregnant rats). The NOAEL for maternal toxicity was 1000 mg/kg/day. This indicates that pregnant rats are more susceptible to propylene carbonate than are non-pregnant rats. There were no significant differences in live litter size, average fetal weight, percentage of males, or malformed fetuses. No studies of the effect of propylene carbonate on reproduction are available. However, no adverse effects on testis, ovaries, or accessory sex organs were noted in rats following oral or inhalation of propylene carbonate for 13 weeks. Therefore, reproductive effects from propylene carbonate are unlikely</p>
POLYTETRAFLUOROETHYLENE	<p>Perfluorinated compounds are potent peroxisome proliferators. The material may produce peroxisome proliferation. Peroxisomes are single, membrane limited organelles in the cytoplasm that are found in the cells of animals, plants, fungi, and protozoa.</p>
1,2-DIMETHOXYETHANE	<p>Animal testing shows material is a reproductive effector: For ethylene glycol monoalkyl ethers and their acetates (EGMAEs): Typical members of this category are ethylene glycol propylene ether (EGPE), ethylene glycol butyl ether (EGBE) and ethylene glycol hexyl ether (EGHE) and their acetates. EGMAEs are substrates for alcohol dehydrogenase isozyme ADH-3, which catalyzes the conversion of their terminal alcohols to aldehydes (which are transient metabolites). Further, rapid conversion of the aldehydes by aldehyde dehydrogenase produces alkoxyacetic acids, which are the predominant urinary metabolites of mono substituted glycol ethers. Acute Toxicity: Oral LD50 values in rats for all category members range from 739 (EGHE) to 3089 mg/kg bw (EGPE), with values increasing with decreasing molecular weight. Four to six hour acute inhalation toxicity studies were conducted for these chemicals in rats at the highest vapour concentrations practically achievable. Values range from LC0 > 85 ppm (508 mg/m³) for EGHE, LC50 > 400ppm (2620 mg/m³) for EGBEA to LC50 > 2132 ppm (9061 mg/m³) for EGPE. No lethality was observed for any of these materials under these conditions. Dermal LD50 values in rabbits range from 435 mg/kg bw (EGBE) to 1500 mg/kg bw (EGBEA). Overall these category members can be considered to be of low to moderate acute toxicity. All category members cause reversible irritation to skin and eyes, with EGBEA less irritating and EGHE more irritating than the other category members. EGPE and EGBE are not sensitizers in experimental animals or humans. Signs of acute toxicity in rats, mice and rabbits are consistent with haemolysis (with the exception of EGHE) and non-specific CNS depression typical of organic solvents in general. Alkoxyacetic acid metabolites, propoxyacetic acid (PAA) and butoxyacetic acid (BAA), are responsible for the red blood cell hemolysis. Signs of toxicity in humans deliberately ingesting cleaning fluids containing 9-22% EGBE are similar to those of rats, with the exception of haemolysis. Although decreased blood haemoglobin and/or haemoglobinuria were observed in some of the human cases, it is not clear if this was due to haemolysis or haemodilution as a result of administration of large volumes of fluid. Red blood cells of humans are many-fold more resistant to toxicity from EGPE and EGBE <i>in vitro</i> than those of rats. Repeat dose toxicity: The fact that the NOAEL for repeated dose toxicity of EGBE is less than that of EGPE is consistent with red blood cells being more sensitive to EGBE than EGPE. Blood from mice, rats, hamsters, rabbits and baboons were sensitive to the effects of BAA <i>in vitro</i> and displayed similar responses, which included erythrocyte swelling (increased haematocrit and mean corpuscular hemoglobin), followed by hemolysis. Blood from humans, pigs, dogs, cats, and guinea pigs was less sensitive to haemolysis by BAA <i>in vitro</i>. Mutagenicity: In the absence and presence of metabolic activation, EGBE tested negative for mutagenicity in Ames tests conducted in <i>S. typhimurium</i> strains TA97, TA98, TA100, TA1535 and TA1537 and EGHE tested negative in strains TA98, TA100, TA1535, TA1537 and TA1538. <i>In vitro</i> cytogenetic and sister chromatid exchange assays with EGBE and EGHE in Chinese Hamster Ovary Cells with and without metabolic activation and <i>in vivo</i> micronucleus tests with EGBE in rats and mice were negative, indicating that these glycol ethers are not genotoxic. Carcinogenicity: In a 2-year inhalation chronic toxicity and carcinogenicity study with EGBE in rats and mice a significant increase in the incidence of liver haemangiosarcomas was seen in male mice and forestomach tumours in female mice. It was decided that based on the</p>

Li-MnO₂ Button Cell(Lithium Metal Battery) CR2032

	<p>mode of action data available, there was no significant hazard for human carcinogenicity</p> <p>Reproductive and developmental toxicity. The results of reproductive and developmental toxicity studies indicate that the glycol ethers in this category are not selectively toxic to the reproductive system or developing fetus, developmental toxicity is secondary to maternal toxicity. The repeated dose toxicity studies in which reproductive organs were examined indicate that the members of this category are not associated with toxicity to reproductive organs (including the testes).</p> <p>Results of the developmental toxicity studies conducted via inhalation exposures during gestation periods on EGPE (rabbits -125, 250, 500 ppm or 531, 1062, or 2125 mg/m³ and rats - 100, 200, 300, 400 ppm or 425, 850, 1275, or 1700 mg/m³), EGBE (rat and rabbit - 25, 50, 100, 200 ppm or 121, 241, 483, or 966 mg/m³), and EGHE (rat and rabbit - 20.8, 41.4, 79.2 ppm or 124, 248, or 474 mg/m³) indicate that the members of the category are not teratogenic.</p> <p>The NOAELs for developmental toxicity are greater than 500 ppm or 2125 mg/m³ (rabbit-EGPE), 100 ppm or 425 mg/m³ (rat-EGPE), 50 ppm or 241 mg/m³ (rat EGBE) and 100 ppm or 483 mg/m³ (rabbit EGBE) and greater than 79.2 ppm or 474 mg/m³ (rat and rabbit-EGHE).</p> <p>For 1,2-dimethoxyethane (monoglyme): Monoglyme, an ethylene glycol ether, is of low toxicity. The vapours cause some irritation and loss of sensation at a sufficient concentration. In animals, degeneration of the testes and atrophy of the thymus gland have been reported, together with enlargement of the adrenal glands and increased spleen activity. Anaemia has occurred. Results of tests to determine the presence or absence of genetic toxicity have been mixed. As one of the breakdown products of monoglyme is known to interfere with sperm production, monoglyme appears to affect male (but not female) reproductive function. Monoglyme appears to cause developmental toxicity and foetal death but not major birth defects.</p> <p>Ethylene glycol esters and their ethers cause wasting of the testicles, reproductive changes, infertility and changes to kidney function. Shorter chain compounds are more dangerous.</p>
STAINLESS STEEL & LITHIUM PERCHLORATE & GRAPHITE & LITHIUM	<p>Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing, and the lack of minimal lymphocytic inflammation, without eosinophilia. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. On the other hand, industrial bronchitis is a disorder that occurs as a result of exposure due to high concentrations of irritating substance (often particles) and is completely reversible after exposure ceases. The disorder is characterized by difficulty breathing, cough and mucus production.</p>
STAINLESS STEEL & MANGANESE DIOXIDE & LITHIUM PERCHLORATE & GRAPHITE & LITHIUM	No significant acute toxicological data identified in literature search.
POLYPROPYLENE & POLYTETRAFLUOROETHYLENE	<p>The substance is classified by IARC as Group 3: NOT classifiable as to its carcinogenicity to humans. Evidence of carcinogenicity may be inadequate or limited in animal testing.</p>

Acute Toxicity	✓	Carcinogenicity	✓
Skin Irritation/Corrosion	✓	Reproductivity	✓
Serious Eye Damage/Irritation	✓	STOT - Single Exposure	✗
Respiratory or Skin sensitisation	✓	STOT - Repeated Exposure	✓
Mutagenicity	✗	Aspiration Hazard	✗

Legend: ✗ – Data either not available or does not fill the criteria for classification
✓ – Data available to make classification

SECTION 12 Ecological information

Toxicity

	Endpoint	Test Duration (hr)	Species	Value	Source
Li-MnO ₂ Button Cell(Lithium Metal Battery) CR2032	Not Available	Not Available	Not Available	Not Available	Not Available
	Not Available	Not Available	Not Available	Not Available	Not Available
Stainless Steel	Not Available	Not Available	Not Available	Not Available	Not Available
	Not Available	Not Available	Not Available	Not Available	Not Available
manganese dioxide	NOEC(EC _x)	48h	Crustacea	0.022mg/l	2
	EC50	48h	Crustacea	>0.022mg/l	2
lithium perchlorate	EC50(EC _x)	48h	Crustacea	>100mg/l	2
	EC50	72h	Algae or other aquatic plants	>120mg/l	2
	EC50	48h	Crustacea	>100mg/l	2
polypropylene	Not Available	Not Available	Not Available	Not Available	Not Available
	Not Available	Not Available	Not Available	Not Available	Not Available
propylene carbonate	EC50	72h	Algae or other aquatic plants	>900mg/l	1
	NOEC(EC _x)	72h	Algae or other aquatic plants	900mg/l	1
	EC50	48h	Crustacea	>1000mg/l	1

Continued...

Li-MnO₂ Button Cell(Lithium Metal Battery) CR2032

	LC50	96h	Fish	1000mg/l	1
graphite	Endpoint	Test Duration (hr)	Species	Value	Source
	NOEC(ECx)	72h	Algae or other aquatic plants	>=100mg/l	2
	EC50	72h	Algae or other aquatic plants	>100mg/l	2
	EC50	48h	Crustacea	>100mg/l	2
	LC50	96h	Fish	>100mg/l	2
polytetrafluoroethylene	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Available
lithium	Endpoint	Test Duration (hr)	Species	Value	Source
	NOEC(ECx)	72h	Algae or other aquatic plants	1.65mg/l	2
	EC50	72h	Algae or other aquatic plants	25.6mg/l	2
	EC50	48h	Crustacea	19.1mg/l	2
	LC50	96h	Fish	18mg/l	2
1,2-dimethoxyethane	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50	72h	Algae or other aquatic plants	9120mg/l	2
	NOEC(ECx)	504h	Crustacea	320mg/l	2
	EC50	48h	Crustacea	4000mg/l	2
	LC50	96h	Fish	>500mg/l	2
Legend:	Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data				

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
lithium perchlorate	HIGH	HIGH
polypropylene	LOW	LOW
propylene carbonate	HIGH	HIGH
polytetrafluoroethylene	HIGH	HIGH
1,2-dimethoxyethane	LOW	LOW

Bioaccumulative potential

Ingredient	Bioaccumulation
lithium perchlorate	LOW (LogKOW = -4.6296)
polypropylene	LOW (LogKOW = 1.6783)
propylene carbonate	LOW (LogKOW = -0.41)
polytetrafluoroethylene	LOW (LogKOW = 1.2142)
1,2-dimethoxyethane	LOW (LogKOW = -0.21)

Mobility in soil

Ingredient	Mobility
lithium perchlorate	LOW (KOC = 48.64)
polypropylene	LOW (KOC = 23.74)
propylene carbonate	LOW (KOC = 14.85)
polytetrafluoroethylene	LOW (KOC = 106.8)
1,2-dimethoxyethane	HIGH (KOC = 1)

SECTION 13 Disposal considerations

Waste treatment methods

Product / Packaging disposal	
	<ul style="list-style-type: none"> Recycle wherever possible or consult manufacturer for recycling options. Consult State Land Waste Management Authority for disposal.

SECTION 14 Transport information

Labels Required

Marine Pollutant	
	NO

Continued...

HAZCHEM | Not Applicable

Land transport (ADG): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS**Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS****Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS****Transport in bulk according to Annex II of MARPOL and the IBC code**

Not Applicable

Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
Stainless Steel	Not Available
manganese dioxide	Not Available
lithium perchlorate	Not Available
polypropylene	Not Available
propylene carbonate	Not Available
graphite	Not Available
polytetrafluoroethylene	Not Available
lithium	Not Available
1,2-dimethoxyethane	Not Available

Transport in bulk in accordance with the ICG Code

Product name	Ship Type
Stainless Steel	Not Available
manganese dioxide	Not Available
lithium perchlorate	Not Available
polypropylene	Not Available
propylene carbonate	Not Available
graphite	Not Available
polytetrafluoroethylene	Not Available
lithium	Not Available
1,2-dimethoxyethane	Not Available

SECTION 15 Regulatory information**Safety, health and environmental regulations / legislation specific for the substance or mixture****Stainless Steel is found on the following regulatory lists**

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 2

Australian Inventory of Industrial Chemicals (AIIC)

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

manganese dioxide is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals

Australian Inventory of Industrial Chemicals (AIIC)

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

lithium perchlorate is found on the following regulatory lists

Australian Inventory of Industrial Chemicals (AIIC)

polypropylene is found on the following regulatory lists

Australian Inventory of Industrial Chemicals (AIIC)

Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

propylene carbonate is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals

Australian Inventory of Industrial Chemicals (AIIC)

graphite is found on the following regulatory lists

Australian Inventory of Industrial Chemicals (AIIC)

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

polytetrafluoroethylene is found on the following regulatory lists

Australian Inventory of Industrial Chemicals (AIIC)

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

lithium is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals
 Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 2
 Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 4
 Australian Inventory of Industrial Chemicals (AIIC)

FEI Equine Prohibited Substances List - Banned Substances
 FEI Equine Prohibited Substances List (EPSL)
 International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

1,2-dimethoxyethane is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals
 Australian Inventory of Industrial Chemicals (AIIC)

Chemical Footprint Project - Chemicals of High Concern List

National Inventory Status

National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	Yes
Canada - DSL	Yes
Canada - NDSL	No (Stainless Steel; manganese dioxide; lithium perchlorate; polypropylene; propylene carbonate; graphite; polytetrafluoroethylene; lithium; 1,2-dimethoxyethane)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	No (polypropylene; polytetrafluoroethylene)
Japan - ENCS	No (Stainless Steel; graphite; lithium)
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	No (Stainless Steel; lithium perchlorate)
USA - TSCA	Yes
Taiwan - TCSI	Yes
Mexico - INSQ	No (Stainless Steel; lithium perchlorate)
Vietnam - NCI	Yes
Russia - FBEPH	No (Stainless Steel)
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

SECTION 16 Other information

Revision Date	08/06/2022
Initial Date	08/06/2022

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC—TWA: Permissible Concentration-Time Weighted Average
 PC—STEL: Permissible Concentration-Short Term Exposure Limit
 IARC: International Agency for Research on Cancer
 ACGIH: American Conference of Governmental Industrial Hygienists
 STEL: Short Term Exposure Limit
 TEEL: Temporary Emergency Exposure Limit
 IDLH: Immediately Dangerous to Life or Health Concentrations
 ES: Exposure Standard
 OSF: Odour Safety Factor
 NOAEL :No Observed Adverse Effect Level
 LOAEL: Lowest Observed Adverse Effect Level
 TLV: Threshold Limit Value
 LOD: Limit Of Detection
 OTV: Odour Threshold Value
 BCF: BioConcentration Factors
 BEI: Biological Exposure Index
 AIIC: Australian Inventory of Industrial Chemicals
 DSL: Domestic Substances List
 NDSL: Non-Domestic Substances List
 IECSC: Inventory of Existing Chemical Substance in China
 EINECS: European Inventory of Existing Commercial chemical Substances
 ELINCS: European List of Notified Chemical Substances
 NLP: No-Longer Polymers
 ENCS: Existing and New Chemical Substances Inventory
 KECI: Korea Existing Chemicals Inventory
 NZIoC: New Zealand Inventory of Chemicals
 PICCS: Philippine Inventory of Chemicals and Chemical Substances
 TSCA: Toxic Substances Control Act
 TCSI: Taiwan Chemical Substance Inventory
 INSQ: Inventario Nacional de Sustancias Químicas
 NCI: National Chemical Inventory

FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.