



## Shotshell Loaded Rounds

### TSA OUTDOORS

Chemwatch Hazard Alert Code: 3

Chemwatch: 5534-31

Version No: 2.1

Safety Data Sheet according to WHS Regulations (Hazardous Chemicals) Amendment 2020 and ADG requirements

Issue Date: 14/03/2022

Print Date: 21/06/2022

L.GHS.AUS.EN.E

#### SECTION 1 Identification of the substance / mixture and of the company / undertaking

##### Product Identifier

Product name	Shotshell Loaded Rounds
Chemical Name	Not Applicable
Synonyms	Not Available
Proper shipping name	CARTRIDGES FOR WEAPONS, INERT PROJECTILE or CARTRIDGES, SMALL ARMS
Chemical formula	Not Applicable
Other means of identification	Not Available

##### Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Shotshell loaded rounds.
--------------------------	--------------------------

##### Details of the supplier of the safety data sheet

Registered company name	TSA OUTDOORS
Address	Unit 6/ 9 - 13 Winbourne Road Brookvale NSW 2100 Australia
Telephone	+61 2 9938 3244
Fax	+61 2 9939 2972
Website	<a href="http://Tsaoutdoors.com.au">Tsaoutdoors.com.au</a>
Email	sales@tasco.com.au

##### Emergency telephone number

Association / Organisation	Aaron Millard
Emergency telephone numbers	+61 450 086 593 (Mon-Fri, 9 am-6pm)
Other emergency telephone numbers	Not Available

#### SECTION 2 Hazards identification

##### Classification of the substance or mixture

Poisons Schedule	Not Applicable
Classification [1]	Explosives Division 1.4, Acute Toxicity (Oral) Category 4, Acute Toxicity (Dermal) Category 3, Sensitisation (Skin) Category 1, Serious Eye Damage/Eye Irritation Category 2A, Acute Toxicity (Inhalation) Category 2, Reproductive Toxicity Category 1A, Reproductive Toxicity Effects on or via Lactation, Hazardous to the Aquatic Environment Long-Term Hazard Category 2
Legend:	1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI

##### Label elements

Hazard pictogram(s)	
Signal word	Danger

##### Hazard statement(s)

H204	Fire or projection hazard.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.

## Shotshell Loaded Rounds

<b>H330</b>	Fatal if inhaled.
<b>H360Df</b>	May damage the unborn child. Suspected of damaging fertility.
<b>H362</b>	May cause harm to breast-fed children.
<b>H411</b>	Toxic to aquatic life with long lasting effects.

### Precautionary statement(s) Prevention

<b>P201</b>	Obtain special instructions before use.
<b>P210</b>	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
<b>P234</b>	Keep only in original packaging.
<b>P250</b>	Do not subject to grinding/shock/sources of friction.
<b>P260</b>	Do not breathe dust/fume.
<b>P263</b>	Avoid contact during pregnancy and while nursing.
<b>P271</b>	Use only outdoors or in a well-ventilated area.
<b>P280</b>	Wear protective gloves, protective clothing, eye protection, face protection and hearing protection.
<b>P240</b>	Ground and bond container and receiving equipment.
<b>P270</b>	Do not eat, drink or smoke when using this product.
<b>P264</b>	Wash all exposed external body areas thoroughly after handling.
<b>P273</b>	Avoid release to the environment.
<b>P284</b>	[In case of inadequate ventilation] wear respiratory protection.
<b>P272</b>	Contaminated work clothing should not be allowed out of the workplace.

### Precautionary statement(s) Response

<b>P304+P340</b>	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
<b>P308+P313</b>	IF exposed or concerned: Get medical advice/ attention.
<b>P310</b>	Immediately call a POISON CENTER/doctor/physician/first aider.
<b>P370+P372+P380+P373</b>	In case of fire: Explosion risk. Evacuate area. DO NOT fight fire when fire reaches explosives.
<b>P370+P380+P375</b>	In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion.
<b>P302+P352</b>	IF ON SKIN: Wash with plenty of water and soap.
<b>P305+P351+P338</b>	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
<b>P333+P313</b>	If skin irritation or rash occurs: Get medical advice/attention.
<b>P337+P313</b>	If eye irritation persists: Get medical advice/attention.
<b>P361+P364</b>	Take off immediately all contaminated clothing and wash it before reuse.
<b>P391</b>	Collect spillage.
<b>P301+P312</b>	IF SWALLOWED: Call a POISON CENTER/doctor/physician/first aider if you feel unwell.
<b>P330</b>	Rinse mouth.

### Precautionary statement(s) Storage

<b>P403+P233</b>	Store in a well-ventilated place. Keep container tightly closed.
<b>P405</b>	Store locked up.
<b>P401</b>	Store in accordance with local/regional/national/international regulations.

### Precautionary statement(s) Disposal

<b>P501</b>	Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.
<b>P503</b>	Refer to manufacturer or supplier for information on disposal/recovery/recycling.

Not Applicable

## SECTION 3 Composition / information on ingredients

### Substances

See section below for composition of Mixtures

### Mixtures

CAS No	%[weight]	Name
7439-92-1	50-75	<u>lead</u>
9004-70-0	0-5	<u>nitrocellulose</u>
7439-89-6	0-5	<u>iron</u>
9002-88-4	0-5	<u>polyethylene</u>
7440-50-8	0-5	<u>copper</u>
7440-66-6	0-1	<u>zinc</u>
63918-97-8	0-1	<u>lead styphnate</u>

Continued...

CAS No	%[weight]	Name
109-27-3	0-1	<u>tetrazene</u>
10022-31-8	0-1	<u>barium nitrate</u>
1345-04-6	0-1	<u>antimony trisulfide</u>
7429-90-5	0-1	<u>aluminium</u>
55-63-0	0-1	<u>nitroglycerin</u>
<b>Legend:</b>	1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. Classification drawn from C&L; * EU IOELVs available	

## SECTION 4 First aid measures

### Description of first aid measures

<b>Eye Contact</b>	<p>If this product comes in contact with the eyes:</p> <ul style="list-style-type: none"> <li>▶ Immediately hold eyelids apart and flush the eye continuously with running water.</li> <li>▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.</li> <li>▶ Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.</li> <li>▶ Transport to hospital or doctor without delay.</li> <li>▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.</li> <li>▶ <b>DO NOT attempt to remove particles attached to or embedded in eye.</b></li> <li>▶ Lay victim down, on stretcher if available and pad <b>BOTH</b> eyes, make sure dressing does not press on the injured eye by placing thick pads under dressing, above and below the eye.</li> <li>▶ Seek urgent medical assistance, or transport to hospital.</li> </ul>
<b>Skin Contact</b>	<p>If skin or hair contact occurs:</p> <ul style="list-style-type: none"> <li>▶ Immediately flush body and clothes with large amounts of water, using safety shower if available.</li> <li>▶ Quickly remove all contaminated clothing, including footwear.</li> <li>▶ Wash skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre.</li> <li>▶ Transport to hospital, or doctor.</li> <li>▶ Immediately wash contaminated skin with plenty of soap and water.</li> <li>▶ Immediately seek medical advice.</li> <li>▶ Wearing gloves, remove all contaminated clothing and loosen remaining clothing.</li> <li>▶ Allow patient to assume comfortable position, keep warm.</li> <li>▶ Keep at rest until fully recovered.</li> <li>▶ If breathing has stopped or is shallow apply artificial respiration at once.</li> <li>▶ In the event of cardiac arrest apply external cardiac massage.</li> <li>▶ If breathing is laboured and patient cyanotic (blue), ensure airways are clear and have qualified person give oxygen through a face mask.</li> </ul> <p>For thermal burns:</p> <ul style="list-style-type: none"> <li>▶ Decontaminate area around burn.</li> <li>▶ Consider the use of cold packs and topical antibiotics.</li> </ul> <p>For first-degree burns (affecting top layer of skin)</p> <ul style="list-style-type: none"> <li>▶ Hold burned skin under cool (not cold) running water or immerse in cool water until pain subsides.</li> <li>▶ Use compresses if running water is not available.</li> <li>▶ Cover with sterile non-adhesive bandage or clean cloth.</li> <li>▶ Do NOT apply butter or ointments; this may cause infection.</li> <li>▶ Give over-the counter pain relievers if pain increases or swelling, redness, fever occur.</li> </ul> <p>For second-degree burns (affecting top two layers of skin)</p> <ul style="list-style-type: none"> <li>▶ Cool the burn by immerse in cold running water for 10-15 minutes.</li> <li>▶ Use compresses if running water is not available.</li> <li>▶ Do NOT apply ice as this may lower body temperature and cause further damage.</li> <li>▶ Do NOT break blisters or apply butter or ointments; this may cause infection.</li> <li>▶ Protect burn by cover loosely with sterile, nonstick bandage and secure in place with gauze or tape.</li> </ul> <p>To prevent shock: (unless the person has a head, neck, or leg injury, or it would cause discomfort):</p> <ul style="list-style-type: none"> <li>▶ Lay the person flat.</li> <li>▶ Elevate feet about 12 inches.</li> <li>▶ Elevate burn area above heart level, if possible.</li> <li>▶ Cover the person with coat or blanket.</li> <li>▶ Seek medical assistance.</li> </ul> <p>For third-degree burns Seek immediate medical or emergency assistance.</p> <p>In the mean time:</p> <ul style="list-style-type: none"> <li>▶ Protect burn area cover loosely with sterile, nonstick bandage or, for large areas, a sheet or other material that will not leave lint in wound.</li> <li>▶ Separate burned toes and fingers with dry, sterile dressings.</li> <li>▶ Do not soak burn in water or apply ointments or butter; this may cause infection.</li> <li>▶ To prevent shock see above.</li> <li>▶ For an airway burn, do not place pillow under the person's head when the person is lying down. This can close the airway.</li> <li>▶ Have a person with a facial burn sit up.</li> <li>▶ Check pulse and breathing to monitor for shock until emergency help arrives.</li> </ul>
<b>Inhalation</b>	<ul style="list-style-type: none"> <li>▶ If fumes or combustion products are inhaled remove from contaminated area.</li> <li>▶ Lay patient down. Keep warm and rested.</li> <li>▶ Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.</li> <li>▶ Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.</li> <li>▶ Transport to hospital, or doctor, without delay.</li> <li>▶ Remove victim from exposure - avoid becoming a casualty.</li> <li>▶ Seek immediate medical advice and treat as for skin absorption.</li> </ul>
<b>Ingestion</b>	<ul style="list-style-type: none"> <li>▶ Give a slurry of activated charcoal in water to drink. <b>NEVER GIVE AN UNCONSCIOUS PATIENT WATER TO DRINK.</b></li> <li>▶ At least 3 tablespoons in a glass of water should be given.</li> <li>▶ Although induction of vomiting may be recommended (<b>IN CONSCIOUS PERSONS ONLY</b>), such a first aid measure is dissuaded due to the risk of aspiration of stomach contents. (i) It is better to take the patient to a doctor who can decide on the necessity and method of emptying the stomach. (ii) Special circumstances may however exist; these include non-availability of charcoal and the ready availability of the doctor.</li> </ul> <p><b>NOTE:</b> If vomiting is induced, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.</p>

## Shotshell Loaded Rounds

**NOTE:** Wear protective gloves when inducing vomiting.

- ▶ REFER FOR MEDICAL ATTENTION WITHOUT DELAY.
- ▶ In the mean time, qualified first-aid personnel should treat the patient following observation and employing supportive measures as indicated by the patient's condition.
- ▶ If the services of a medical officer or medical doctor are readily available, the patient should be placed in his/her care and a copy of the SDS should be provided. Further action will be the responsibility of the medical specialist.
- ▶ If medical attention is not available on the worksite or surroundings send the patient to a hospital together with a copy of the SDS. (ICSC20305/20307)

#### Indication of any immediate medical attention and special treatment needed

Nitroglycerin is a sensitive explosive. If free Nitroglycerin or its analogues, are present, great care must be taken in carrying out first-aid procedures to ensure that it is not initiated through impact.

Treat symptomatically.

for copper intoxication:

- ▶ Unless extensive vomiting has occurred empty the stomach by lavage with water, milk, sodium bicarbonate solution or a 0.1% solution of potassium ferrocyanide (the resulting copper ferrocyanide is insoluble).
- ▶ Administer egg white and other demulcents.
- ▶ Maintain electrolyte and fluid balances.
- ▶ Morphine or meperidine (Demerol) may be necessary for control of pain.
- ▶ If symptoms persist or intensify (especially circulatory collapse or cerebral disturbances, try BAL intramuscularly or penicillamine in accordance with the supplier's recommendations.
- ▶ Treat shock vigorously with blood transfusions and perhaps vasopressor amines.
- ▶ If intravascular haemolysis becomes evident protect the kidneys by maintaining a diuresis with mannitol and perhaps by alkalinising the urine with sodium bicarbonate.
- ▶ It is unlikely that methylene blue would be effective against the occasional methaemoglobinemia and it might exacerbate the subsequent haemolytic episode.
- ▶ Institute measures for impending renal and hepatic failure.

[GOSSELIN, SMITH & HODGE: Commercial Toxicology of Commercial Products]

- ▶ A role for activated charcoals for emesis is, as yet, unproven.
- ▶ In severe poisoning CaNa<sub>2</sub>EDTA has been proposed.

[ELLENHORN & BARCELOUX: Medical Toxicology]

for dinitrophenols:

Marked fatigue, tremendous thirst, profuse sweating, flushing of the face are all characteristics of intoxication by dinitrophenol derivatives. These may be followed by restlessness, anxiety, excitement which may occasionally lead to convulsions. Rises in body temperature (proportional to dose) may result in severe hyperpyrexia. tachycardia, hyperpnoea, dyspnoea, cyanosis and muscle cramps characterise later symptomatology. Late complications include decreased urine output with albuminuria, casts, pigment, and sometimes blood cells due to toxic nephritis. Jaundice and liver tenderness also develop as a result of toxic hepatitis.

**TREATMENT** for dinitrophenol intoxications:

- ▶ Gastric lavage with large quantities of 5% sodium bicarbonate solution leaving 1-2 pints in the stomach.
- ▶ Saline cathartics e.g. 15-30 gm sodium or magnesium sulfate in water.
- ▶ Cold packs and alcohol sponges to reduce body temperature. Antipyretic drugs are ineffective here. Cold water enemas have been used. Intensive efforts to correct a dinitrophenol fever are justified. If it can be accomplished, mild hypothermia (rectal temperature between 33.5 and 36 deg. C) is desirable because dinitrophenol appears to lose its metabolic activity at reduced temperature. **[DO NOT give atropine, aspirin, and other salicylates to control hyperthermia, as these agents appear likely to enhance the toxicity of phenolic substances. Aspirin also enhances the uncoupling of oxidative phosphorylation.]**
- ▶ Fluids, orally or intravenously (e.g. glucose in saline, 1000 ml) to correct dehydration and acidosis.
- ▶ Because dinitrophenol is actively transported by the renal organic acid transport processes in some species, a trial of forced diuresis with alkalinisation of the urine is warranted.
- ▶ Oxygen therapy. Artificial ventilation is needed. [Administer oxygen by mask to minimise anoxia].
- ▶ Prophylactic measures in anticipation of kidney and liver insufficiency.

GOSSELIN, SMITH HODGE; Clinical Toxicology of Commercial Products 5th Ed.

Diazepam may be used, if necessary, for the treatment of convulsions, to reduce body heat and control agitation. Be prepared to counter respirator depression and hypotension which may occur following administration of anticonvulsants.

- ▶ Chelation with British Anti-Lewisite (BAL) for serious antimony exposures should be employed.
- ▶ Dialyse as needed. The role of exchange diffusion is not clear.
- ▶ Be sure to monitor for dysrhythmias.

[Ellenhorn and Barceloux: Medical Toxicology]

- ▶ Gastric acids solubilise lead and its salts and lead absorption occurs in the small bowel.
- ▶ Particles of less than 1 um diameter are substantially absorbed by the alveoli following inhalation.
- ▶ Lead is distributed to the red blood cells and has a half-life of 35 days. It is subsequently redistributed to soft tissue & bone-stores or eliminated. The kidney accounts for 75% of daily lead loss; integumentary and alimentary losses account for the remainder.
- ▶ Neurasthenic symptoms are the most common symptoms of intoxication. Lead toxicity produces a classic motor neuropathy. Acute encephalopathy appears infrequently in adults. Diazepam is the best drug for seizures.
- ▶ Whole-blood lead is the best measure of recent exposure; free erythrocyte protoporphyrin (FEP) provides the best screening for chronic exposure. Obvious clinical symptoms occur in adults when whole-blood lead exceeds 80 ug/dL.
- ▶ British Anti-Lewisite is an effective antidote and enhances faecal and urinary excretion of lead. The onset of action of BAL is about 30 minutes and most of the chelated metal complex is excreted in 4-6 hours, primarily in the bile. Adverse reaction appears in up to 50% of patients given BAL in doses exceeding 5 mg/kg. CaNa<sub>2</sub>EDTA has also been used alone or in concert with BAL as an antidote. D-penicillamine is the usual oral agent for mobilisation of bone lead; its use in the treatment of lead poisoning remains investigational. 2,3-dimercapto-1-propanesulfonic acid (DMPS) and dimercaptosuccinic acid (DMSA) are water soluble analogues of BAL and their effectiveness is undergoing review. As a rule, stop BAL if lead decreases below 50 ug/dL; stop CaNa<sub>2</sub>EDTA if blood lead decreases below 40 ug/dL or urinary lead drops below 2 mg/24hrs.

[Ellenhorn & Barceloux: Medical Toxicology]

#### BIOLOGICAL EXPOSURE INDEX - BEI

These represent the determinants observed in specimens collected from a healthy worker who has been exposed at the Exposure Standard (ES or TLV):

Determinant	Index	Sampling Time	Comments
1. Lead in blood	30 ug/100 ml	Not Critical	
2. Lead in urine	150 ug/gm creatinine	Not Critical	B
3. Zinc protoporphyrin in blood	250 ug/100 ml erythrocytes OR 100 ug/100 ml blood	After 1 month exposure	B

B: Background levels occur in specimens collected from subjects **NOT** exposed.

Symptoms of vasodilation and reflex tachycardia may present following organic nitrate overdose; most organic nitrates are extensively metabolised by hydrolysis to inorganic nitrites. Organic nitrates and nitrites are readily absorbed through the skin, lungs, mucosa and gastro-intestinal tract.

## SECTION 5 Firefighting measures

**Extinguishing media**

Metal dust fires need to be smothered with sand, inert dry powders.

**DO NOT USE WATER, CO<sub>2</sub> or FOAM.**

- ▶ Use DRY sand, graphite powder, dry sodium chloride based extinguishers, G-1 or Met L-X to smother fire.
- ▶ Confining or smothering material is preferable to applying water as chemical reaction may produce flammable and explosive hydrogen gas.
- ▶ Chemical reaction with CO<sub>2</sub> may produce flammable and explosive methane.
- ▶ If impossible to extinguish, withdraw, protect surroundings and allow fire to burn itself out.
- ▶ **DO NOT** use halogenated fire extinguishing agents.

**Special hazards arising from the substrate or mixture**

<b>Fire Incompatibility</b>	▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result
-----------------------------	--

**Advice for firefighters**

<b>Fire Fighting</b>	<p><b>WARNING: EXPLOSIVE MATERIALS / ARTICLES PRESENT!</b></p> <ul style="list-style-type: none"> <li>▶ Evacuate all personnel and move upwind.</li> <li>▶ Prevent re-entry.</li> <li>▶ Alert Fire Brigade and tell them location and nature of hazard.</li> <li>▶ May detonate and burning material may be propelled from fire.</li> <li>▶ Wear full-body protective clothing with breathing apparatus.</li> <li>▶ Prevent, by any means available, spillage and fire effluent from entering drains and water courses.</li> <li>▶ Fight fire from safe distances and from protected locations.</li> <li>▶ Use flooding quantities of water.</li> <li>▶ <b>DO NOT</b> approach containers or packages suspected to be hot.</li> <li>▶ Cool any exposed containers not involved in fire from a protected location.</li> <li>▶ Equipment should be thoroughly decontaminated after use.</li> </ul>
<b>Fire/Explosion Hazard</b>	<p>Division 1.4 Substances, mixtures and articles which present no significant hazard: substances, mixtures and articles which present only a small hazard in the event of ignition or initiation. The effects are largely confined to the package and no projection of fragments of appreciable size or range is to be expected. An external fire shall not cause virtually instantaneous explosion of almost the entire contents of the package.</p> <p>Combustion products include:</p> <ul style="list-style-type: none"> <li>carbon monoxide (CO)</li> <li>carbon dioxide (CO<sub>2</sub>)</li> <li>nitrogen oxides (NO<sub>x</sub>)</li> <li>metal oxides</li> <li>other pyrolysis products typical of burning organic material.</li> </ul>
<b>HAZCHEM</b>	1YE

**SECTION 6 Accidental release measures****Personal precautions, protective equipment and emergency procedures**

See section 8

**Environmental precautions**

See section 12

**Methods and material for containment and cleaning up**

<b>Minor Spills</b>	<p>For nitroglycerine and similar products:</p> <ul style="list-style-type: none"> <li>▶ Clean up spills immediately. Avoid all personal contact.</li> <li>▶ Wear protective clothing, impervious gloves and safety glasses.</li> <li>▶ Minor splashes should be wiped clean with an alcohol soaked cloth.</li> <li>▶ The spill area is decontaminated using 'NG Decontamination Solution'.</li> <li>▶ Do not use metal or spark producing implements during clean up.</li> </ul> <p><b>WARNING!: EXPLOSIVE.</b></p> <p>BLAST and/or PROJECTION and/or FIRE HAZARD</p> <ul style="list-style-type: none"> <li>▶ Clean up all spills immediately.</li> <li>▶ Avoid inhalation of the material and avoid contact with eyes and skin.</li> <li>▶ Wear impervious gloves and safety glasses.</li> <li>▶ Remove all ignition sources.</li> <li>▶ Use spark-free tools when handling.</li> <li>▶ Sweep into non-sparking containers or barrels and moisten with water.</li> <li>▶ Place spilled material in clean, sealable, labelled container for disposal.</li> <li>▶ Flush area with large amounts of water.</li> </ul>
<b>Major Spills</b>	<ul style="list-style-type: none"> <li>· Do not use compressed air to remove metal dusts from floors, beams or equipment</li> <li>· Vacuum cleaners, of flame-proof design, should be used to minimise dust accumulation.</li> <li>· Use non-sparking handling equipment, tools and natural bristle brushes.</li> <li>· Provide grounding and bonding where necessary to prevent accumulation of static charges during metal dust handling and transfer operations</li> <li>· Cover and reseal partially empty containers.</li> <li>· Do not allow chips, fines or dusts to contact water, particularly in enclosed areas.</li> </ul> <p>If molten:</p> <ul style="list-style-type: none"> <li>▶ Contain the flow using dry sand or salt flux as a dam.</li> <li>▶ All tooling (e.g., shovels or hand tools) and containers which come in contact with molten metal must be preheated or specially coated, rust free and approved for such use.</li> <li>▶ Allow the spill to cool before remelting scrap.</li> </ul> <p><b>WARNING!: EXPLOSIVE.</b></p> <ul style="list-style-type: none"> <li>▶ Clear area of personnel and move upwind.</li> <li>▶ Alert Fire Brigade and tell them location and nature of hazard.</li> <li>▶ May be violently or explosively reactive.</li> <li>▶ Wear full body protective clothing with breathing apparatus.</li> <li>▶ Consider evacuation (or protect in place).</li> <li>▶ In case of transport accident notify Police, Emergency Authority, Competent Explosives Authority or Manufacturer.</li> <li>▶ No smoking, naked lights, heat or ignition sources.</li> <li>▶ Increase ventilation.</li> </ul>

## Shotshell Loaded Rounds

- ▶ Use extreme caution to prevent physical shock.
- ▶ Use only spark-free shovels and explosion-proof equipment.
- ▶ Collect recoverable material and segregate from spilled material.
- ▶ Wash spill area with large quantities of water.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

## SECTION 7 Handling and storage

## Precautions for safe handling

<b>Safe handling</b>	<p>For molten metals:</p> <ul style="list-style-type: none"> <li>· Molten metal and water can be an explosive combination. The risk is greatest when there is sufficient molten metal to entrap or seal off water. Water and other forms of contamination on or contained in scrap or remelt ingot are known to have caused explosions in melting operations. While the products may have minimal surface roughness and internal voids, there remains the possibility of moisture contamination or entrapment. If confined, even a few drops can lead to violent explosions.</li> <li>· All tooling, containers, molds and ladles, which come in contact with molten metal must be preheated or specially coated, rust free and approved for such use.</li> <li>· Any surfaces that may contact molten metal (e.g. concrete) should be specially coated</li> <li>· Drops of molten metal in water (e.g. from plasma arc cutting), while not normally an explosion hazard, can generate enough flammable hydrogen gas to present an explosion hazard. Vigorous circulation of the water and removal of the particles minimise the hazard.</li> </ul> <p>During melting operations, the following minimum guidelines should be observed:</p> <ul style="list-style-type: none"> <li>· Inspect all materials prior to furnace charging and completely remove surface contamination such as water, ice, snow, deposits of grease and oil or other surface contamination resulting from weather exposure, shipment, or storage.</li> <li>· Store materials in dry, heated areas with any cracks or cavities pointed downwards.</li> <li>· Preheat and dry large objects adequately before charging in to a furnace containing molten metal. This is typically done by the use of a drying oven or homogenising furnace. The dry cycle should bring the metal temperature of the coldest item of the batch to 200 degree C (400 deg F) and then hold at that temperature for 6 hours.</li> <li>▶ Handle gently. Use good occupational work practice.</li> <li>▶ Observe manufacturer's storage and handling recommendations contained within this SDS.</li> <li>▶ Avoid all personal contact, including inhalation.</li> <li>▶ Avoid smoking, naked lights, heat or ignition sources.</li> <li>▶ Explosives must not be struck with metal implements.</li> <li>▶ Avoid mechanical and thermal shock and friction.</li> <li>▶ Use in a well ventilated area.</li> <li>▶ Avoid contact with incompatible materials.</li> <li>▶ <b>When handling DO NOT eat, drink or smoke.</b></li> <li>▶ Avoid physical damage to containers.</li> <li>▶ Always wash hands with soap and water after handling.</li> <li>▶ Work clothes should be laundered separately.</li> <li>▶ Organic powders when finely divided over a range of concentrations regardless of particulate size or shape and suspended in air or some other oxidizing medium may form explosive dust-air mixtures and result in a fire or dust explosion (including secondary explosions)</li> <li>▶ Minimise airborne dust and eliminate all ignition sources. Keep away from heat, hot surfaces, sparks, and flame.</li> <li>▶ Establish good housekeeping practices.</li> <li>▶ Remove dust accumulations on a regular basis by vacuuming or gentle sweeping to avoid creating dust clouds.</li> <li>▶ Use continuous suction at points of dust generation to capture and minimise the accumulation of dusts. Particular attention should be given to overhead and hidden horizontal surfaces to minimise the probability of a "secondary" explosion. According to NFPA Standard 654, dust layers 1/32 in.(0.8 mm) thick can be sufficient to warrant immediate cleaning of the area.</li> <li>▶ Do not use air hoses for cleaning.</li> <li>▶ Minimise dry sweeping to avoid generation of dust clouds. Vacuum dust-accumulating surfaces and remove to a chemical disposal area. Vacuums with explosion-proof motors should be used.</li> <li>▶ Control sources of static electricity. Dusts or their packages may accumulate static charges, and static discharge can be a source of ignition.</li> <li>▶ Solids handling systems must be designed in accordance with applicable standards (e.g. NFPA including 654 and 77) and other national guidance.</li> <li>▶ Do not empty directly into flammable solvents or in the presence of flammable vapors.</li> <li>▶ The operator, the packaging container and all equipment must be grounded with electrical bonding and grounding systems. Plastic bags and plastics cannot be grounded, and antistatic bags do not completely protect against development of static charges.</li> </ul> <p>Empty containers may contain residual dust which has the potential to accumulate following settling. Such dusts may explode in the presence of an appropriate ignition source.</p> <ul style="list-style-type: none"> <li>▶ <b>Do NOT cut, drill, grind or weld such containers.</b></li> <li>▶ In addition ensure such activity is not performed near full, partially empty or empty containers without appropriate workplace safety authorisation or permit.</li> </ul>
<b>Other information</b>	<ul style="list-style-type: none"> <li>▶ <b>DO NOT store near acids, or oxidising agents</b></li> <li>▶ Store cases in a well ventilated magazine licensed for the appropriate Class, Division and Compatibility Group.</li> <li>▶ Rotate stock to prevent ageing. Use on FIFO (first in-first out) basis.</li> <li>▶ Observe manufacturer's storage and handling recommendations contained within this SDS.</li> <li>▶ Store in a cool place in original containers.</li> <li>▶ Keep containers securely sealed.</li> <li>▶ No smoking, naked lights, heat or ignition sources.</li> <li>▶ Store in an isolated area away from other materials.</li> <li>▶ Keep storage area free of debris, waste and combustibles.</li> <li>▶ Protect containers against physical damage.</li> <li>▶ Check regularly for spills and leaks</li> </ul> <p><b>NOTE:</b> If explosives need to be destroyed contact the Competent Authority.</p>

## Conditions for safe storage, including any incompatibilities

<b>Suitable container</b>	<ul style="list-style-type: none"> <li>▶ Bulk bags: Reinforced bags required for dense materials.</li> <li>▶ All packaging for Class 1 Goods shall be in accordance with the requirements of the relevant Code for the transport of Dangerous Goods.</li> <li>▶ Class 1 is unique in that the type of packaging used frequently has a very decisive effect on the hazard and therefore on the assignment to a particular division</li> </ul>
<b>Storage incompatibility</b>	<p>Inorganic derivative of Group 11 metal. For aluminas (aluminium oxide): Incompatible with hot chlorinated rubber. In the presence of chlorine trifluoride may react violently and ignite. -May initiate explosive polymerisation of olefin oxides including ethylene oxide.</p>

## Shotshell Loaded Rounds

-Produces exothermic reaction above 200°C with halocarbons and an exothermic reaction at ambient temperatures with halocarbons in the presence of other metals.

-Produces exothermic reaction with oxygen difluoride.

-May form explosive mixture with oxygen difluoride.

-Forms explosive mixtures with sodium nitrate.

-Reacts vigorously with vinyl acetate.

Aluminium oxide is an amphoteric substance, meaning it can react with both acids and bases, such as hydrofluoric acid and sodium hydroxide, acting as an acid with a base and a base with an acid, neutralising the other and producing a salt.

The substance may be or contains a "metalloid"

The following elements are considered to be metalloids; boron, silicon, germanium, arsenic, antimony, tellurium and (possibly) polonium

The electronegativities and ionisation energies of the metalloids are between those of the metals and nonmetals, so the metalloids exhibit characteristics of both classes. The reactivity of the metalloids depends on the element with which they are reacting. For example, boron acts as a nonmetal when reacting with sodium yet as a metal when reacting with fluorine.

Unlike most metals, most metalloids are amphoteric- that is they can act as both an acid and a base. For instance, arsenic forms not only salts such as arsenic halides, by the reaction with certain strong acid, but it also forms arsenites by reactions with strong bases.

Most metalloids have a multiplicity of oxidation states or valences. For instance, tellurium has the oxidation states +2, -2, +4, and +6. Metalloids react like non-metals when they react with metals and act like metals when they react with non-metals.

Nitroglycerin:

- ▶ is heat-, UV-, acid-, friction-, mechanical-shock-high explosive
- ▶ is hydrolysed in water forming an explosive solution of nitric acid and glycerol
- ▶ is a strong oxidiser - reacts vigorously, with possible detonation, on contact with strong reducing agents
- ▶ explodes on contact with ozone or at temperatures above approximately 177 deg C
- ▶ thermal sensitivity may be increased in the presence of metal oxides
- ▶ may form explosive salts on reaction with organic bases
- ▶ Many metals may incandesce, react violently, ignite or react explosively upon addition of concentrated nitric acid.

Nitrophenols are:

- ▶ combustible solids which may form explosive mixtures with air when finely divided
- ▶ strong oxidisers which react violently with reducing agents
- ▶ reactive with combustible, organic and other easily oxidisable materials
- ▶ thermally unstable burning in the absence of air causing fast pressure rises; closed containers may explode
- ▶ able to form shock-sensitive explosive mixtures with chlorine trifluoride
- ▶ incompatible with strong acids, caustics, aliphatic amines, amides, diethylamine, potassium hydride, potassium hydroxide

- ▶ Sulfides are incompatible with acids, diazo and azo compounds, halocarbons, isocyanates, aldehydes, alkali metals, nitrides, hydrides, and other strong reducing agents.

- ▶ Many reactions of sulfides with these materials generate heat and in many cases hydrogen gas.

- ▶ Many sulfide compounds may liberate hydrogen sulfide upon reaction with an acid.

Metals exhibit varying degrees of activity. Reaction is reduced in the massive form (sheet, rod, or drop), compared with finely divided forms. The less active metals will not burn in air but:

- ▶ can react exothermically with oxidising acids to form noxious gases.
- ▶ catalyse polymerisation and other reactions, particularly when finely divided
- ▶ react with halogenated hydrocarbons (for example, copper dissolves when heated in carbon tetrachloride), sometimes forming explosive compounds.

- ▶ Many metals in elemental form react exothermically with compounds having active hydrogen atoms (such as acids and water) to form flammable hydrogen gas and caustic products.

- ▶ Elemental metals may react with azo/diazo compounds to form explosive products.

- ▶ Some elemental metals form explosive products with halogenated hydrocarbons.

- ▶ Explosion hazard may follow contact with incompatible materials

- ▶ Avoid strong acids, bases.

- ▶ Finely divided metal powders develop pyrophoricity when a critical specific surface area is exceeded; this is ascribed to high heat of oxide formation on exposure to air.

- ▶ Safe handling is possible in relatively low concentrations of oxygen in an inert gas.

- ▶ Several pyrophoric metals, stored in glass bottles have ignited when the container is broken on impact. Storage of these materials moist and in metal containers is recommended.

- ▶ The reaction residues from various metal syntheses (involving vacuum evaporation and co-deposition with a ligand) are often pyrophoric.

Factors influencing the pyrophoricity of metals are particle size, presence of moisture, nature of the surface of the particle, heat of formation of the oxide, or nitride, mass, hydrogen content, stress, purity and presence of oxide, among others.

- ▶ Phenols are incompatible with strong reducing substances such as hydrides, nitrides, alkali metals, and sulfides.

- ▶ Avoid use of aluminium, copper and brass alloys in storage and process equipment.

- ▶ Heat is generated by the acid-base reaction between phenols and bases.

- ▶ Phenols are sulfonated very readily (for example, by concentrated sulfuric acid at room temperature), these reactions generate heat.

- ▶ Phenols are nitrated very rapidly, even by dilute nitric acid.

- ▶ Nitrated phenols often explode when heated. Many of them form metal salts that tend toward detonation by rather mild shock.

## SECTION 8 Exposure controls / personal protection

## Control parameters

## Occupational Exposure Limits (OEL)

## INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Australia Exposure Standards	lead	Lead, inorganic dusts & fumes (as Pb)	0.05 mg/m3	Not Available	Not Available	Not Available
Australia Exposure Standards	copper	Copper (fume)	0.2 mg/m3	Not Available	Not Available	Not Available
Australia Exposure Standards	copper	Copper, dusts & mists (as Cu)	1 mg/m3	Not Available	Not Available	Not Available
Australia Exposure Standards	barium nitrate	Barium, soluble compounds (as Ba)	0.5 mg/m3	Not Available	Not Available	Not Available
Australia Exposure Standards	antimony trisulfide	Antimony & compounds (as Sb)	0.5 mg/m3	Not Available	Not Available	Not Available
Australia Exposure Standards	aluminium	Aluminium (welding fumes) (as Al)	5 mg/m3	Not Available	Not Available	Not Available
Australia Exposure Standards	aluminium	Aluminium (metal dust)	10 mg/m3	Not Available	Not Available	Not Available
Australia Exposure Standards	aluminium	Aluminium, pyro powders (as Al)	5 mg/m3	Not Available	Not Available	Not Available

## Shotshell Loaded Rounds

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Australia Exposure Standards	nitroglycerin	Nitroglycerine (NG)	0.05 ppm / 0.46 mg/m3	Not Available	Not Available	Not Available

## Emergency Limits

Ingredient	TEEL-1	TEEL-2	TEEL-3
lead	0.15 mg/m3	120 mg/m3	700 mg/m3
iron	3.2 mg/m3	35 mg/m3	150 mg/m3
polyethylene	16 mg/m3	170 mg/m3	1,000 mg/m3
copper	3 mg/m3	33 mg/m3	200 mg/m3
zinc	6 mg/m3	21 mg/m3	120 mg/m3
barium nitrate	2.9 mg/m3	350 mg/m3	2,100 mg/m3
nitroglycerin	0.1 mg/m3	2 mg/m3	75 mg/m3

Ingredient	Original IDLH	Revised IDLH
lead	Not Available	Not Available
nitrocellulose	Not Available	Not Available
iron	Not Available	Not Available
polyethylene	Not Available	Not Available
copper	100 mg/m3	Not Available
zinc	Not Available	Not Available
lead styphnate	100 mg/m3	Not Available
tetrazene	Not Available	Not Available
barium nitrate	50 mg/m3	Not Available
antimony trisulfide	50 mg/m3	Not Available
aluminium	Not Available	Not Available
nitroglycerin	75 mg/m3	Not Available

## Occupational Exposure Banding


Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit
lead styphnate	E	≤ 0.01 mg/m <sup>3</sup>
tetrazene	E	≤ 0.01 mg/m <sup>3</sup>

## Notes:

Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.

## MATERIAL DATA

## Exposure controls

<b>Appropriate engineering controls</b>	<p>Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are:</p> <p>Process controls which involve changing the way a job activity or process is done to reduce the risk.</p> <p>Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.</p> <p>Employers may need to use multiple types of controls to prevent employee overexposure.</p> <ul style="list-style-type: none"> <li>▶ Employees exposed to confirmed human carcinogens should be authorized to do so by the employer, and work in a regulated area.</li> <li>▶ Work should be undertaken in an isolated system such as a "glove-box". Employees should wash their hands and arms upon completion of the assigned task and before engaging in other activities not associated with the isolated system.</li> <li>▶ Within regulated areas, the carcinogen should be stored in sealed containers, or enclosed in a closed system, including piping systems, with any sample ports or openings closed while the carcinogens are contained within.</li> <li>▶ Open-vessel systems are prohibited.</li> <li>▶ Each operation should be provided with continuous local exhaust ventilation so that air movement is always from ordinary work areas to the operation.</li> <li>▶ Exhaust air should not be discharged to regulated areas, non-regulated areas or the external environment unless decontaminated. Clean make-up air should be introduced in sufficient volume to maintain correct operation of the local exhaust system.</li> <li>▶ For maintenance and decontamination activities, authorized employees entering the area should be provided with and required to wear clean, impervious garments, including gloves, boots and continuous-air supplied hood. Prior to removing protective garments the employee should undergo decontamination and be required to shower upon removal of the garments and hood.</li> <li>▶ Except for outdoor systems, regulated areas should be maintained under negative pressure (with respect to non-regulated areas).</li> <li>▶ Local exhaust ventilation requires make-up air be supplied in equal volumes to replaced air.</li> <li>▶ Laboratory hoods must be designed and maintained so as to draw air inward at an average linear face velocity of 0.76 m/sec with a minimum of 0.64 m/sec. Design and construction of the fume hood requires that insertion of any portion of the employees body, other than hands and arms, be disallowed.</li> </ul>
<b>Personal protection</b>	
<b>Eye and face protection</b>	<ul style="list-style-type: none"> <li>▶ Safety glasses with side shields.</li> <li>▶ Chemical goggles.</li> <li>▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing</li> </ul>



	<p>the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent]</p>
<b>Skin protection</b>	<p>See Hand protection below</p>
<b>Hands/feet protection</b>	<ul style="list-style-type: none"> <li>▶ Wear chemical protective gloves, e.g. PVC.</li> <li>▶ Wear safety footwear or safety gumboots, e.g. Rubber</li> </ul> <p><b>NOTE:</b></p> <ul style="list-style-type: none"> <li>▶ The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.</li> <li>▶ Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed.</li> </ul> <p>The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.</p> <p>The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.</p> <p>Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.</p> <p>Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include:</p> <ul style="list-style-type: none"> <li>· frequency and duration of contact,</li> <li>· chemical resistance of glove material,</li> <li>· glove thickness and</li> <li>· dexterity</li> </ul> <p>Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent).</p> <ul style="list-style-type: none"> <li>· When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.</li> <li>· When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.</li> <li>· Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for long-term use.</li> <li>· Contaminated gloves should be replaced.</li> </ul> <p>As defined in ASTM F-739-96 in any application, gloves are rated as:</p> <ul style="list-style-type: none"> <li>· Excellent when breakthrough time &gt; 480 min</li> <li>· Good when breakthrough time &gt; 20 min</li> <li>· Fair when breakthrough time &lt; 20 min</li> <li>· Poor when glove material degrades</li> </ul> <p>For general applications, gloves with a thickness typically greater than 0.35 mm, are recommended.</p> <p>It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times.</p> <p>Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers technical data should always be taken into account to ensure selection of the most appropriate glove for the task.</p> <p>Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example:</p> <ul style="list-style-type: none"> <li>· Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of.</li> <li>· Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential</li> </ul> <p>Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.</p> <ul style="list-style-type: none"> <li>▶ Protective gloves eg. Leather gloves or gloves with Leather facing <ul style="list-style-type: none"> <li>· Non-sparking or conductive footwear essential. Conductive footwear describes a boot or shoe with a sole made from a conductive compound chemically bound to the bottom components, for permanent control to electrically ground the foot and shall dissipate static electricity from the body to reduce the possibility of ignition of volatile compounds. Electrical resistance must range between 0 to 500,000 ohms. Conductive shoes should be stored in lockers close to the room in which they are worn. Personnel who have been issued conductive footwear should not wear them from their place of work to their homes and return.</li> </ul> </li> </ul>
<b>Body protection</b>	<p>See Other protection below</p>
<b>Other protection</b>	<ul style="list-style-type: none"> <li>▶ Employees working with confirmed human carcinogens should be provided with, and be required to wear, clean, full body protective clothing (smocks, coveralls, or long-sleeved shirt and pants), shoe covers and gloves prior to entering the regulated area. [AS/NZS ISO 6529:2006 or national equivalent]</li> <li>▶ Employees engaged in handling operations involving carcinogens should be provided with, and required to wear and use half-face filter-type respirators with filters for dusts, mists and fumes, or air purifying canisters or cartridges. A respirator affording higher levels of protection may be substituted. [AS/NZS 1715 or national equivalent]</li> <li>▶ Emergency deluge showers and eyewash fountains, supplied with potable water, should be located near, within sight of, and on the same level with locations where direct exposure is likely.</li> <li>▶ Prior to each exit from an area containing confirmed human carcinogens, employees should be required to remove and leave protective clothing and equipment at the point of exit and at the last exit of the day, to place used clothing and equipment in impervious containers at the point of exit for purposes of decontamination or disposal. The contents of such impervious containers must be identified with suitable labels. For maintenance and decontamination activities, authorized employees entering the area should be provided with and required to wear clean, impervious garments, including gloves, boots and continuous-air supplied hood.</li> <li>▶ Prior to removing protective garments the employee should undergo decontamination and be required to shower upon removal of the garments and hood.</li> </ul> <p>For handling explosives or explosive compositions:</p> <ul style="list-style-type: none"> <li>▶ Wear close-fitting flame-protection treated clothing closed at the neck and sleeves.</li> <li>▶ Cotton underwear, socks and conductive shoes are recommended to avoid human static discharge.</li> </ul> <ul style="list-style-type: none"> <li>· During repair or maintenance activities the potential exists for exposures to toxic metal particulate in excess of the occupational standards. Under these circumstances, protecting workers can require the use of specific work practices or procedures involving the combined use of ventilation, wet and vacuum cleaning methods, respiratory protection, decontamination, special protective clothing, and when necessary, restricted work zones.</li> <li>· Protective over-garments or work clothing must be worn by persons who may become contaminated with particulate during activities such as machining, furnace rebuilding, air cleaning equipment filter changes, maintenance, furnace tending, etc. Contaminated work clothing and over-garments must be managed in a controlled manner to prevent secondary exposure to workers of third parties, to prevent the spread of particulate to other areas, and to prevent particulate from being taken home by workers.</li> <li>· Personnel who handle and work with <b>molten metal</b> should utilise primary protective clothing like polycarbonate face shields, fire resistant tapper's jackets, neck shades (snoods), leggings, spats and similar equipment to prevent burn injuries. In addition to primary protection, secondary or day-to-day work clothing that is fire resistant and sheds metal splash is recommended for use with molten metal. Synthetic</li> </ul>

materials should never be worn even as secondary clothing (undergarments).

Manufacture may require:

- ▶ Non-static flame retardant treated clothing
- ▶ Access to deluge Safety shower
- ▶ Barrier cream.

### Respiratory protection

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required. Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	A-AUS P2	-	A-PAPR-AUS / Class 1 P2
up to 50 x ES	-	A-AUS / Class 1 P2	-
up to 100 x ES	-	A-2 P2	A-PAPR-2 P2 ^

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO<sub>2</sub>), G = Agricultural chemicals, K = Ammonia(NH<sub>3</sub>), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

- Respirators may be necessary when engineering and administrative controls do not adequately prevent exposures.
- The decision to use respiratory protection should be based on professional judgment that takes into account toxicity information, exposure measurement data, and frequency and likelihood of the worker's exposure - ensure users are not subject to high thermal loads which may result in heat stress or distress due to personal protective equipment (powered, positive flow, full face apparatus may be an option).
- Published occupational exposure limits, where they exist, will assist in determining the adequacy of the selected respiratory protection. These may be government mandated or vendor recommended.
- Certified respirators will be useful for protecting workers from inhalation of particulates when properly selected and fit tested as part of a complete respiratory protection program.
- Where protection from nuisance levels of dusts are desired, use type N95 (US) or type P1 (EN143) dust masks. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU)
- Use approved positive flow mask if significant quantities of dust becomes airborne.
- Try to avoid creating dust conditions.

Where significant concentrations of the material are likely to enter the breathing zone, a Class P3 respirator may be required.

Class P3 particulate filters are used for protection against highly toxic or highly irritant particulates.

Filtration rate: Filters at least 99.95% of airborne particles

Suitable for:

- Relatively small particles generated by mechanical processes eg. grinding, cutting, sanding, drilling, sawing.
- Sub-micron thermally generated particles e.g. welding fumes, fertilizer and bushfire smoke.
- Biologically active airborne particles under specified infection control applications e.g. viruses, bacteria, COVID-19, SARS
- Highly toxic particles e.g. Organophosphate Insecticides, Radionuclides, Asbestos

Note: P3 Rating can only be achieved when used with a Full Face Respirator or Powered Air-Purifying Respirator (PAPR). If used with any other respirator, it will only provide filtration protection up to a P2 rating.

## SECTION 9 Physical and chemical properties

### Information on basic physical and chemical properties

<b>Appearance</b>	Metallic cup with a plastic tube above; insoluble in water.		
<b>Physical state</b>	Manufactured	<b>Relative density (Water = 1)</b>	Not Available
<b>Odour</b>	Not Available	<b>Partition coefficient n-octanol / water</b>	Not Available
<b>Odour threshold</b>	Not Available	<b>Auto-ignition temperature (°C)</b>	Not Applicable
<b>pH (as supplied)</b>	Not Applicable	<b>Decomposition temperature</b>	Not Available
<b>Melting point / freezing point (°C)</b>	Not Available	<b>Viscosity (cSt)</b>	Not Applicable
<b>Initial boiling point and boiling range (°C)</b>	Not Applicable	<b>Molecular weight (g/mol)</b>	Not Applicable
<b>Flash point (°C)</b>	Not Applicable	<b>Taste</b>	Not Available
<b>Evaporation rate</b>	Not Available	<b>Explosive properties</b>	Not Available
<b>Flammability</b>	Not Applicable	<b>Oxidising properties</b>	Not Available
<b>Upper Explosive Limit (%)</b>	Not Applicable	<b>Surface Tension (dyn/cm or mN/m)</b>	Not Applicable
<b>Lower Explosive Limit (%)</b>	Not Applicable	<b>Volatile Component (%vol)</b>	Not Available
<b>Vapour pressure (kPa)</b>	Not Applicable	<b>Gas group</b>	Not Available
<b>Solubility in water</b>	Immiscible	<b>pH as a solution (Not Available%)</b>	Not Applicable
<b>Vapour density (Air = 1)</b>	Not Available	<b>VOC g/L</b>	Not Available

## SECTION 10 Stability and reactivity

<b>Reactivity</b>	See section 7
<b>Chemical stability</b>	<ul style="list-style-type: none"> <li>▶ Presence of shock and friction</li> <li>▶ Presence of heat source and ignition source</li> <li>▶ Product is considered stable under normal handling conditions.</li> <li>▶ Stable under normal storage conditions.</li> <li>▶ Hazardous polymerization will not occur.</li> </ul>

	Avoid contact with other chemicals.
<b>Possibility of hazardous reactions</b>	See section 7
<b>Conditions to avoid</b>	See section 7
<b>Incompatible materials</b>	See section 7
<b>Hazardous decomposition products</b>	See section 5

## SECTION 11 Toxicological information

### Information on toxicological effects

<b>Inhaled</b>	<p>The material is not thought to produce respiratory irritation (as classified by EC Directives using animal models). Nevertheless inhalation of dusts, or fumes, especially for prolonged periods, may produce respiratory discomfort and occasionally, distress.</p> <p>Inhalation of dusts, generated by the material during the course of normal handling, may produce severe damage to the health of the individual. Relatively small amounts absorbed from the lungs may prove fatal.</p> <p>Exposure by inhalation to levels between 0.04 and 0.5 ppm nitroglycerin have been reported to result in headaches. Considerable individual variability has been observed. A transient loss of vision has been reported in some cases following overexposure.</p> <p>Exposure to nitroglycerin and its analogues by any route causes dilation of blood vessels in the body and produces a reduction in blood pressure. Exposure to small amounts can result in headaches, dizziness, weakness and nausea. Large exposures can result in vomiting, cyanosis, convulsions, coma and possible circulatory collapse and respiratory paralysis. The prior ingestion of alcohol can potentiate these effects.</p> <p>Temporary tolerance to headache may develop following repeated exposure. This tolerance disappears rapidly, a short absence from exposure may lead to severe poisoning from amounts that were previously safe. Operatives are required to obtain Occupational Health Centre "classification" prior to working in nitroglycerin areas.</p> <p>Nitroglycerin is a potent vasodilator of both arterial and venous vascular smooth muscle. It is also known to cause the formation of methaemoglobinaemia in experimental animals.</p> <p>Copper poisoning following exposure to copper dusts and fume may result in headache, cold sweat and weak pulse. Capillary, kidney, liver and brain damage are the longer term manifestations of such poisoning. Inhalation of freshly formed metal oxide particles sized below 1.5 microns and generally between 0.02 to 0.05 microns may result in "metal fume fever". Symptoms may be delayed for up to 12 hours and begin with the sudden onset of thirst, and a sweet, metallic or foul taste in the mouth. Other symptoms include upper respiratory tract irritation accompanied by coughing and a dryness of the mucous membranes, lassitude and a generalised feeling of malaise. Mild to severe headache, nausea, occasional vomiting, fever or chills, exaggerated mental activity, profuse sweating, diarrhoea, excessive urination and prostration may also occur. Tolerance to the fumes develops rapidly, but is quickly lost. All symptoms usually subside within 24-36 hours following removal from exposure.</p> <p>Inhalation of antimony and its compounds may produce respiratory and gastrointestinal tract discomfort with sore throat, shallow respiration, coughing, headaches, breathing difficulties, dizziness, weight loss, gingivitis, anaemia, eosinophilia and enzyme inhibition. Inflammation of the upper and lower respiratory tract may occur. Pulmonary congestion and oedema may also occur. Other symptoms include rhinitis, eye irritation, vomiting and diarrhoea, weight loss, dysomnia, hair loss and haematological disorders. Death due to circulatory failure has been described, with pathology showing acute congestion of the heart (myocardial failure), liver and kidneys.</p>
<b>Ingestion</b>	Not normally a hazard due to physical form of product.
<b>Skin Contact</b>	<p>Skin contact with the material may produce toxic effects; systemic effects may result following absorption.</p> <p>Limited evidence exists, or practical experience predicts, that the material either produces inflammation of the skin in a substantial number of individuals following direct contact, and/or produces significant inflammation when applied to the healthy intact skin of animals, for up to four hours, such inflammation being present twenty-four hours or more after the end of the exposure period. Skin irritation may also be present after prolonged or repeated exposure; this may result in a form of contact dermatitis (nonallergic). The dermatitis is often characterised by skin redness (erythema) and swelling (oedema) which may progress to blistering (vesiculation), scaling and thickening of the epidermis. At the microscopic level there may be intercellular oedema of the spongy layer of the skin (spongiosis) and intracellular oedema of the epidermis. The material may accentuate any pre-existing dermatitis condition</p> <p>Open cuts, abraded or irritated skin should not be exposed to this material</p> <p>Exposure to copper, by skin, has come from its use in pigments, ointments, ornaments, jewellery, dental amalgams and IUDs and as an antifungal agent and an algicide. Although copper algicides are used in the treatment of water in swimming pools and reservoirs, there are no reports of toxicity from these applications. Reports of allergic contact dermatitis following contact with copper and its salts have appeared in the literature, however the exposure concentrations leading to any effect have been poorly characterised. In one study, patch testing of 1190 eczema patients found that only 13 (1.1%) cross-reacted with 2% copper sulfate in petrolatum. The investigators warned, however, that the possibility of contamination with nickel (an established contact allergen) might have been the cause of the reaction. Copper salts often produce an itching eczema in contact with skin. This is, likely, of a non-allergic nature.</p> <p>Entry into the blood-stream through, for example, cuts, abrasions, puncture wounds or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.</p>
<b>Eye</b>	<p>Evidence exists, or practical experience predicts, that the material may cause eye irritation in a substantial number of individuals and/or may produce significant ocular lesions which are present twenty-four hours or more after instillation into the eye(s) of experimental animals. Repeated or prolonged eye contact may cause inflammation characterised by temporary redness (similar to windburn) of the conjunctiva (conjunctivitis); temporary impairment of vision and/or other transient eye damage/ulceration may occur.</p>
<b>Chronic</b>	<p>Practical experience shows that skin contact with the material is capable either of inducing a sensitisation reaction in a substantial number of individuals, and/or of producing a positive response in experimental animals.</p> <p>Substances that can cause occupational asthma (also known as asthmagens and respiratory sensitisers) can induce a state of specific airway hyper-responsiveness via an immunological, irritant or other mechanism. Once the airways have become hyper-responsive, further exposure to the substance, sometimes even to tiny quantities, may cause respiratory symptoms. These symptoms can range in severity from a runny nose to asthma. Not all workers who are exposed to a sensitiser will become hyper-responsive and it is impossible to identify in advance who are likely to become hyper-responsive.</p> <p>Substances that can cause occupational asthma should be distinguished from substances which may trigger the symptoms of asthma in people with pre-existing air-way hyper-responsiveness. The latter substances are not classified as asthmagens or respiratory sensitisers</p> <p>Wherever it is reasonably practicable, exposure to substances that can cause occupational asthma should be prevented. Where this is not possible the primary aim is to apply adequate standards of control to prevent workers from becoming hyper-responsive.</p> <p>Activities giving rise to short-term peak concentrations should receive particular attention when risk management is being considered. Health surveillance is appropriate for all employees exposed or liable to be exposed to a substance which may cause occupational asthma and there should be appropriate consultation with an occupational health professional over the degree of risk and level of surveillance.</p> <p>There is sufficient evidence to establish a causal relationship between human exposure to the material and impaired fertility</p> <p>There is sufficient evidence to establish a causal relationship between human exposure to the material and subsequent developmental toxic effects in the off-spring.</p> <p>There is sufficient evidence to provide a strong presumption that human exposure to the material may result in impaired fertility on the basis of: - clear evidence in animal studies of impaired fertility in the absence of toxic effects, or evidence of impaired fertility occurring at around the same dose levels as other toxic effects but which is not a secondary non-specific consequence of other toxic effects.</p>

There is sufficient evidence to provide a strong presumption that human exposure to the material may result in developmental toxicity, generally on the basis of:

- clear results in appropriate animal studies where effects have been observed in the absence of marked maternal toxicity, or at around the same dose levels as other toxic effects but which are not secondary non-specific consequences of the other toxic effects.

Chronic exposure to aluminas (aluminium oxides) of particle size 1.2 microns did not produce significant systemic or respiratory system effects in workers. Epidemiologic surveys have indicated an excess of nonmalignant respiratory disease in workers exposed to aluminum oxide during abrasives production.

Very fine Al<sub>2</sub>O<sub>3</sub> powder was not fibrogenic in rats, guinea pigs, or hamsters when inhaled for 6 to 12 months and sacrificed at periods up to 12 months following the last exposure.

When hydrated aluminas were injected intratracheally, they produced dense and numerous nodules of advanced fibrosis in rats, a reticulin network with occasional collagen fibres in mice and guinea pigs, and only a slight reticulin network in rabbits. Shaver's disease, a rapidly progressive and often fatal interstitial fibrosis of the lungs, is associated with a process involving the fusion of bauxite (aluminium oxide) with iron, coke and silica at 2000 deg. C.

The weight of evidence suggests that catalytically active alumina and the large surface area aluminas can induce lung fibrosis (aluminosis) in experimental animals, but only when given by the intra-tracheal route. The pertinence of such experiments in relation to workplace exposure is doubtful especially since it has been demonstrated that the most reactive of the aluminas (i.e. the chi and gamma forms), when given by inhalation, are non-fibrogenic in experimental animals. However rats exposed by inhalation to refractory aluminium fibre showed mild fibrosis and possibly carcinogenic effects indicating that fibrous aluminas might exhibit different toxicology to non-fibrous forms. Aluminium oxide fibres administered by the intrapleural route produce clear evidence of carcinogenicity.

Saffil fibre an artificially produced form alumina fibre used as refractories, consists of over 95% alumina, 3-4 % silica. Animal tests for fibrogenic, carcinogenic potential and oral toxicity have included in-vitro, intraperitoneal injection, intrapleural injection, inhalation, and feeding. The fibre has generally been inactive in animal studies. Also studies of Saffil dust clouds show very low respirable fraction.

There is general agreement that particle size determines that the degree of pathogenicity (the ability of a micro-organism to produce infectious disease) of elementary aluminium, or its oxides or hydroxides when they occur as dusts, fumes or vapours. Only those particles small enough to enter the alveoli (sub 5 um) are able to produce pathogenic effects in the lungs.

Excessive exposure to lead can affect the blood, the nervous system, heart, endocrine organs and the immune system and the digestive system. The synthesis of haemoglobin is inhibited and can result in anaemia. If left untreated, neuromuscular dysfunction, possible paralysis and encephalopathy (brain tissue damage) may result. Other symptoms of overexposure include joint and muscle pain, weakness of the extensor muscles (frequently the hand and wrist), headache, dizziness, abdominal pain, diarrhoea, constipation, nausea, vomiting, blue line on the gums, insomnia and metallic taste. High body levels produce cerebrospinal pressure, brain damage with stupor leading to coma and, in some cases, death. Early symptoms of lead poisoning ("plumbism") include anorexia and loss of weight, constipation, apathy or irritability, occasional vomiting, fatigue, headache, weakness, and a metallic taste in the mouth. Advanced poisonings are characterised by intermittent vomiting, irritability, nervousness, myalgia of the arms and legs (often with wrist and foot drop). Severe poisonings may produce persistent vomiting, ataxia, stupor or lethargy, visual disturbances progressing to optic neuritis and atrophy, hyper-tension, papilloedema, cranial nerve paralysis, delirium, convulsions and coma. Neurological effects include mental retardation, seizures, cerebral palsy and marked muscular contractions that distort the spine, limbs, hips and sometimes the cranial innervated muscles (dystonia musculorum deformans). Industrial exposure has been associated with irreversible kidney damage.

Lead is a cumulative poison with adverse effects in pregnancy [NIOSH/TIC]

Lead salts have been reported to cross the placenta and induce embryo- and foeto-mortality. They also may have a teratogenic effect (causing birth deformities) in certain animal species. Organometallic lead may not produce these effects. Adverse effects of lead on human reproduction, embryonic and foetal development and postnatal mental development have also been recorded. Foetal exposure to lead may result in birth defects, mental retardation, behavioural disorders and death during the first year of childhood. Paternal effects may include reduced sex drive, impotence, sterility and adverse effects on the sperm which in turn may increase the potential for increased birth defects. Maternal effects may include miscarriage and stillbirth in exposed women, or women whose husbands might be exposed, sterility or decreased fertility, and abnormal menses. Exposure by both parents to lead may exacerbate the reproductive effects.

For copper and its compounds (typically copper chloride):

Acute toxicity: There are no reliable acute oral toxicity results available. Animal testing shows that skin in exposure to copper may lead to hardness of the skin, scar formation, exudation and reddish changes. Inflammation, irritation and injury of the skin were noted.

Repeat dose toxicity: Animal testing shows that very high levels of copper monochloride may cause anaemia.

Genetic toxicity: Copper monochloride does not appear to cause mutations in vivo, although chromosomal aberrations were seen at very high concentrations in vitro.

Cancer-causing potential: There was insufficient information to evaluate the cancer-causing activity of copper monochloride.

Repeated or prolonged exposure to antimony and its compounds may produce stomatitis, dry throat, metallic taste, gingivitis, septal and laryngeal perforation, laryngitis, headache, dyspnea, indigestion, nausea, vomiting, diarrhoea, anorexia, anaemia, weight loss, pain and chest tightness, sleeplessness, muscular pain and weakness, dizziness, pharyngitis, tracheitis, bronchitis, pneumonitis, benign pneumoconiosis (with obstructive lung disease and emphysema) and haematological disorders. Degenerative changes of the liver and kidney may occur. Symptoms can be variable, and may include fatigue, myopathy (muscle aches and inflammation), hypotension, angina and immune dysregulation and hypertrophy of splenic follicles.

Antimony's deposition in body tissues and its detrimental effects depend upon the oxidation state of the element. The trivalent antimony compounds are cardiotoxic. Trivalent antimony affects liver functions, impairs enzymes, and may interfere with sulfur chemistry. If antimony impairs phosphofructokinase (PFK), then purine metabolism may be disrupted, resulting in elevated blood and/or urine levels of hypoxanthine, uric acid and possibly ammonia. Pentavalent antimony deposits in bone, kidney, and in organs of the endocrine system.

Chronic exposure to antimony compounds may result in itchiness, papules and pustules around sweat and sebaceous glands ("antimony spots"), but rarely around the face, and dermatitis.

Collapse and sudden death due to anaphylactic-type reactions have occurred. Therapeutic doses given intravenously cause nausea, vomiting, cough and abdominal pain and diarrhoea. Other side-effects include anorexia, chest, muscle and joint pains, pruritus, skin rashes, dizziness and oedema. Renal and hepatic damage occur rarely and haemolytic anaemia has been reported. Continuous treatment with small doses of antimony may give rise to subacute poisoning similar to chronic arsenic poisoning.

Smelter workers often show skin rashes on the forearms and thighs resembling chicken pox pustules.

Workers exposed to inorganic antimony compounds show a benign pneumoconiosis and obstructive lung disease - these are probably non-specific. Woman appear to more susceptible to systemic effects following exposure. Antimony crosses the placenta, is present in amniotic fluids, and is excreted in breast milk. There are suggestions that exposure may produce an increased incidence of spontaneous late abortions, premature births, and gynecological problems among female antimony smelter workers. An excess of deaths from lung cancer has been reported in smelter workers with more than 7 years exposure to relatively high levels of dust and fume. Animal studies demonstrate that the dust may produce pathological changes in cardiac muscle and may produce an interstitial pneumonitis and endogenous pneumonia. One animal study has also suggested that inhalation of the dust by rats induced a significantly increased incidence of carcinogenic tumours of the lungs and thorax. Increased chromosome defects occur when human lymphocytes are incubated with a soluble antimony salt.

The inhalation data suggests that the myocardium is a target of antimony toxicity. It is possible that antimony affects circulating glucose by interfering with enzymes of the glycogenolysis and gluconeogenesis pathways. The mechanism of action of antimony remains unclear. However, some studies suggest that antimony combines with sulfhydryl groups including those in several enzymes important for tissue respiration. Congener substances such as 2,4-dinitrophenol were previously used to produce weight loss. Adverse effects of the treatment included skin eruption, peripheral neuritis, liver and kidney damage, granulocytopenia and, rarely, cataract formation. Repeated or prolonged contact may produce an allergic or irritant dermatitis. Chronic exposures may produce fatigue and weight loss. A yellow discolouration of the sclerae and urine may indicate adsorption of potentially harmful amounts of the substance.

Chronic exposure to nitrophenols may produce kidney and liver damage. Studies in mammals show changes in neurohumoral regulation and pathology. Colitis, enteritis, hepatitis, gastritis, hyperplasia of the spleen and neuritis may occur.

The major concern of possible long-term effects of exposure to nitrate and nitrite is associated with formation of nitroso compounds, many of

## Shotshell Loaded Rounds

	<p>which are carcinogenic. This formation may take place wherever nitrite and nitrosable compounds are present, but it is favoured by acidic conditions or the presence of some bacteria. The gastrointestinal tract and especially the stomach is regarded as the main formation site, but nitrosation reactions can also take place in an infected urinary bladder.</p> <p>Nitrite is mutagenic in a number of in vitro assays against microorganisms or cultured mammalian cells. Nitrates show no mutagenic activity in microbial tests under aerobic conditions. Activity has been reported under anaerobic conditions, probably due to reduction of nitrate into nitrite</p> <p>The mutagenic effects of nitrites were observed in an in vivo and in vitro experiment using Syrian hamsters. In vivo assays have been equivocal, both positive and negative results having been reported</p> <p>Exposure to sodium nitrite in drinking water resulted in an increased incidence of epithelial hyperplasia in the forestomach of male and female rats and in the glandular stomach of male mice.</p> <p>There was equivocal evidence of carcinogenic activity of sodium nitrite in female B6C3F1 mice based on the positive trend in the incidences of squamous cell papillomas or carcinomas (combined) of the forestomach. There was no evidence of carcinogenic activity in male and female F344/N rats or B6C3F1 male mice exposed to 750, 1500 or 3000 ppm.</p> <p>NTP Technical Report Series No. 495, May 2001</p> <p>Under certain conditions, nitrites can react with secondary amines, either alone or in biological systems, to form carcinogenic nitrosamines.</p> <p>Sodium nitrite (60 mg/kg) administered in drinking water to pregnant guinea pigs produced maternal anaemia and increased the incidences of abortion and foetal mortality. Administration of 2000-3000 mg/l sodium nitrite in drinking water, to pregnant rats, produced 30-53% foetal mortality. In rat dams given 0.025-0.5% in feed, sodium nitrite caused an increase in foetal and pup mortality and decreases in pre-weanling body weights.</p>
--	---

Shotshell Loaded Rounds	TOXICITY	IRRITATION
	Not Available	Not Available
lead	TOXICITY	IRRITATION
	dermal (rat) LD50: >2000 mg/kg <sup>[1]</sup>	Not Available
	Inhalation(Rat) LC50; >5.05 mg/l4h <sup>[1]</sup>	
Oral (Rat) LD50; >2000 mg/kg <sup>[1]</sup>		
nitrocellulose	TOXICITY	IRRITATION
	Oral (Rat) LD50; >5000 mg/kg <sup>[2]</sup>	Not Available
iron	TOXICITY	IRRITATION
	Oral (Rat) LD50; 98600 mg/kg <sup>[2]</sup>	Not Available
polyethylene	TOXICITY	IRRITATION
	dermal (rat) LD50: >2000 mg/kg <sup>[1]</sup>	Not Available
Oral (Rat) LD50; >2000 mg/kg <sup>[1]</sup>		
copper	TOXICITY	IRRITATION
	dermal (rat) LD50: >2000 mg/kg <sup>[1]</sup>	Eye: no adverse effect observed (not irritating) <sup>[1]</sup>
	Inhalation(Rat) LC50; 0.733 mg/l4h <sup>[1]</sup>	Skin: no adverse effect observed (not irritating) <sup>[1]</sup>
Oral (Mouse) LD50; 0.7 mg/kg <sup>[2]</sup>		
zinc	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: 1130 mg/kg <sup>[2]</sup>	Eye: no adverse effect observed (not irritating) <sup>[1]</sup>
Oral (Rat) LD50; >2000 mg/kg <sup>[1]</sup>	Skin: no adverse effect observed (not irritating) <sup>[1]</sup>	
lead styphnate	TOXICITY	IRRITATION
	dermal (rat) LD50: >2000 mg/kg <sup>[1]</sup>	Not Available
	Inhalation(Rat) LC50; >5.05 mg/l4h <sup>[1]</sup>	
Oral (Rat) LD50; >2000 mg/kg <sup>[1]</sup>		
tetrazene	TOXICITY	IRRITATION
	Not Available	Not Available
barium nitrate	TOXICITY	IRRITATION
	dermal (rat) LD50: >2000 mg/kg <sup>[1]</sup>	Eye (rabbit):100 mg/24h - moderate
Oral (Rat) LD50; >50<300 mg/kg <sup>[1]</sup>	Skin (rabbit): 500 mg/24h - mild	
antimony trisulfide	TOXICITY	IRRITATION
	dermal (rat) LD50: >2000 mg/kg <sup>[1]</sup>	Eye: no adverse effect observed (not irritating) <sup>[1]</sup>
	Inhalation(Rat) LC50; >5.04 mg/l4h <sup>[1]</sup>	Skin: no adverse effect observed (not irritating) <sup>[1]</sup>
Oral (Rat) LD50; >2000 mg/kg <sup>[1]</sup>		
aluminium	TOXICITY	IRRITATION
	Inhalation(Rat) LC50; >2.3 mg/l4h <sup>[1]</sup>	Eye: no adverse effect observed (not irritating) <sup>[1]</sup>
Oral (Rat) LD50; >2000 mg/kg <sup>[1]</sup>	Skin: no adverse effect observed (not irritating) <sup>[1]</sup>	

	TOXICITY	IRRITATION
nitroglycerin	dermal (rat) LD50: >9560 mg/kg <sup>[1]</sup>	Eye: no adverse effect observed (not irritating) <sup>[1]</sup>
	Oral (Rat) LD50; 105 mg/kg <sup>[2]</sup>	Skin: adverse effect observed (irritating) <sup>[1]</sup>
<b>Legend:</b>	1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. * Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances	

LEAD	<p>WARNING: Lead is a cumulative poison and has the potential to cause abortion and intellectual impairment to unborn children of pregnant workers.</p>
POLYETHYLENE	<p>polyethylene pyrolyzate for poly-alpha-olefins (PAOs):</p> <p>PAOs are highly branched isoparaffinic chemicals produced by oligomerisation of 1-octene, 1-decene, and/or 1-dodecene. The crude polyalphaolefin mixture is then distilled into appropriate product fractions to meet specific viscosity specifications and hydrogenated. Read across data exist for health effects endpoints from the following similar <i>hydrogenated</i> long chain branched alkanes derived from a C8, C10, and/or C12 alpha olefins:</p> <ul style="list-style-type: none"> <li>▶ Decene homopolymer</li> <li>▶ Decene/dodecene copolymer</li> <li>▶ Octene/decene/dodecene copolymer</li> <li>▶ Dodecene trimer</li> </ul> <p>The data for these structural analogs demonstrated no evidence of health effects. In addition, there is evidence in the literature that alkanes with 30 or more carbon atoms are unlikely to be absorbed when administered orally. The physicochemical data suggest that it is unlikely that significant absorption will occur. If a substance of the size and structure of a typical PAO is absorbed, then the principal mechanisms of absorption after oral administration are likely to be passive diffusion and absorption by way of the lymphatic system. The former requires both good lipid solubility and good water solubility as the substance has to partition from an aqueous environment through a lipophilic membrane into another aqueous environment during absorption. Absorption by way of the lymphatics occurs by mechanisms analogous to those that absorb fatty acids and is limited by the size of the molecule. Lipophilicity generally enhances the ability of chemicals to cross biological membranes. Biotransformation by mixed function oxidases often increases the water solubility of a substance; however, existing data suggest that these substances will not undergo oxidation to more hydrophilic metabolites. Finally, a chemical must have an active functional group that can interact chemically or physically with the target cell or receptor upon reaching it; there are no moieties in PAOs that represent a functional group that may have biological activity. The water solubilities of a C10 dimer PAO and a C12 trimer PAO were determined to be &lt;1 ppb and &lt;1 ppt respectively. The partition coefficient for a C12 trimer PAO was determined to be log Kow of &gt;7. Given the very low water solubility it is extremely unlikely that PAOs will be absorbed by passive diffusion following oral administration, and the size of the molecules suggest that the extent of lymphatic absorption is likely to be very low. Although PAOs are relatively large lipophilic compounds, and molecular size may be a critical limiting determinant for absorption, there is some evidence that these substances are absorbed. However, the lack of observed toxicity in the studies with PAOs suggests that these products are absorbed poorly, if at all. Furthermore, a review of the literature regarding the absorption and metabolism of long chain alkanes indicates that alkanes with 30+ carbon atoms are unlikely to be absorbed. For example the absorption of squalane, an analogous C30 product, administered orally to male CD rats was examined - essentially all of the squalane was recovered unchanged in the faeces. At the same time, the hydrophobic properties of PAOs suggest that, should they be absorbed, they would undergo limited distribution in the aqueous systemic circulation and reach potential target organs in limited concentrations.</p> <p>In addition to the general considerations discussed above, the low volatility of PAOs indicates that, under normal conditions of use or transportation, exposure by the inhalation route is unlikely. In particular, the high viscosity of these substances suggests that it would be difficult to generate a high concentration of respirable particles in the air.</p> <p><b>Acute toxicity:</b> PAOs (decene/dodecene copolymer, octene/decene/dodecene homo-polymer, and dodecene trimer) have been adequately tested for acute oral toxicity. There were no deaths when the test materials were administered at doses of 5,000 mg/kg (decene/dodecene copolymer and dodecene trimer) and at 2,000 mg/kg (octene/decene/dodecene copolymer) in rats. Overall, the acute oral LD50 for these substances was greater than the 2000 mg/kg limit dose, indicating a relatively low order of toxicity.</p> <p>PAOs (decene/dodecene copolymer, octene/decene/dodecene copolymer, and dodecene trimer) have been tested for acute dermal toxicity. No mortality was observed for any substance when administered at the limit dose of 2000 or 5000 mg/kg. Overall, the acute dermal LD50 for these substances was greater than the 2000 mg/kg limit dose, indicating a relatively low order of toxicity.</p> <p>1-Decene, homopolymer, is absorbed (unexpectedly for a high molecular weight polymer) to a moderate degree in rat skin and is eliminated slowly</p> <p>PAOs (decene homopolymer, decene/dodecene copolymer, and decene trimer) have been tested for acute inhalation toxicity. Rats were exposed to aerosols of the substances at nominal atmospheric concentrations of 2.5, 5.0, and 5.06 mg/L, respectively, for four hours. These levels were the maximum attainable concentrations under the conditions of the tests, due to the low volatility and high viscosity of the test material. No mortality was noted, and all animals fully recovered following depuration. The lack of mortality at concentrations at or above the limit dose of 2.0 mg/L indicates a relatively low order of toxicity for these substances.</p> <p><b>Repeat dose toxicity:</b> Eight repeated-dose toxicity studies using two different animal species, rats and mice, and oral and dermal routes of administration have been conducted with three structural analogs. These data suggest that the structural analogs exhibit a low order of toxicity following repeated applications, due to their similarity in chemical structures and physicochemical properties.</p> <p>One 28-day oral toxicity study in rats, one 90-day dermal and two 90-day dietary studies in rats, and a dermal carcinogenicity study in mice exist for decene homopolymer. A rat oral combined reproductive toxicity and 91-day systemic toxicity study was also conducted with decene homopolymer. In addition, 28-day rat oral toxicity studies exist for two structurally analogous substances (dodecene trimer and octene/decene/dodecene copolymer); and a 90-day rat dermal toxicity study exists for octene/decene/dodecene copolymer. Results from these studies show a low order of repeated dose toxicity. The dermal NOAEL for systemic toxicity studies was equal to or greater than 2000 mg/kg/day. The oral NOAEL for 1-decene homopolymer is between 5,000 and 20,000 mg/kg/day in Sprague-Dawley rats.</p> <p>Rats exposed repeatedly by dermal exposure at doses of 2000 mg/kg decene/dodecene copolymer showed increased incidences of hyperplasia of the sebaceous glands, hyperplasia/hyperkeratosis of the epidermis and dermal inflammation. These symptoms generally subsided within 2 weeks. Males showed decreased body weight gain and altered serum chemistry.</p> <p>In a 90-day feeding study rats receiving 20000 ppm of 1-decene, homopolymer, hydrogenated did not exhibit any clinical signs of systemic toxicity. Marginal effects on clinical chemistry (glucose and ALT in males; sodium, phosphorus and calcium in females) were seen.</p> <p><b>Reproductive toxicity:</b> Data are available for decene homopolymer. Results from these studies show a low order of reproductive/developmental toxicity. The NOAEL for reproductive toxicity was 1000 mg/kg/day, the highest concentration tested. The lack of effects on fertility in this study or effects on reproductive organs in this or other subchronic studies with closely related chemicals indicates that PAOs are unlikely to exert effects on reproduction.</p> <p><b>Developmental toxicity:</b> Decene homopolymer (with 10 ppm of an antioxidant) was administered once daily on gestation days 0-19 via dermal application to presumed-pregnant rats at doses of 0, 800, and 2000 mg/kg/day. Dermal administration of the test material did not adversely affect parameters of reproductive performance during gestation, nor did it adversely affect <i>in utero</i> survival and development of the offspring. The NOAEL in this study for developmental parameters was 2000 mg/kg/day.</p> <p><b>Genotoxicity:</b> Information for the following PAOs (decene homopolymer, octene/decene/dodecene copolymer, dodecene trimer; and decene/dodecene copolymer [prepared from 10% C12 and 90% C10 alpha olefins; approx. 33% trimer and 51% tetramer, 16% pentamer and higher]) is available. Either bacterial or mammalian gene mutation assays, <i>in vitro</i> chromosomal aberration assays, or <i>in vivo</i> chromosomal aberration assays have been conducted for these substances. Neither mutagenicity nor clastogenicity were exhibited by any of these substances in the referenced <i>in vivo</i> or <i>in vitro</i> tests, with or without metabolic activation.</p> <p><b>Carcinogenicity:</b> While alpha-olefin polymers have similar properties to mineral oils, they do not contain polycyclic aromatic hydrocarbons, or</p>

## Shotshell Loaded Rounds

	<p>other known possible carcinogens.</p> <p>Decene homopolymer produced no treatment-related tumors in C3H mice treated with a 50 ul/application twice weekly for 104 weeks. In addition, survival (56%) was greater than in any other group, including the untreated control.</p> <p>Inclusion of polyethylene in the diet of rats at 8 g/kg/day did not result in treatment-related effects. Polyethylene implanted into rats and mice has reportedly caused local tumorigenic activity at doses of 33 to 2120 mg/kg, but the relevance to human exposure is not certain.</p>		
COPPER	<p>WARNING: Inhalation of high concentrations of copper fume may cause "metal fume fever", an acute industrial disease of short duration. Symptoms are tiredness, influenza like respiratory tract irritation with fever.</p> <p>for copper and its compounds (typically copper chloride):</p> <p><b>Acute toxicity:</b> There are no reliable acute oral toxicity results available. In an acute dermal toxicity study (OECD TG 402), one group of 5 male rats and 5 groups of 5 female rats received doses of 1000, 1500 and 2000 mg/kg bw via dermal application for 24 hours. The LD50 values of copper monochloride were 2,000 mg/kg bw or greater for male (no deaths observed) and 1,224 mg/kg bw for female. Four females died at both 1500 and 2000 mg/kg bw, and one at 1,000 mg/kg bw. Symptom of the hardness of skin, an exudation of hardness site, the formation of scar and reddish changes were observed on application sites in all treated animals. Skin inflammation and injury were also noted. In addition, a reddish or black urine was observed in females at 2,000, 1,500 and 1,000 mg/kg bw. Female rats appeared to be more sensitive than male based on mortality and clinical signs.</p> <p>No reliable skin/eye irritation studies were available. The acute dermal study with copper monochloride suggests that it has a potential to cause skin irritation.</p> <p><b>Repeat dose toxicity:</b> In repeated dose toxicity study performed according to OECD TG 422, copper monochloride was given orally (gavage) to Sprague-Dawley rats for 30 days to males and for 39 - 51 days to females at concentrations of 0, 1.3, 5.0, 20, and 80 mg/kg bw/day. The NOAEL value was 5 and 1.3 mg/kg bw/day for male and female rats, respectively. No deaths were observed in male rats. One treatment-related death was observed in female rats in the high dose group. Erythropoietic toxicity (anaemia) was seen in both sexes at the 80 mg/kg bw/day. The frequency of squamous cell hyperplasia of the forestomach was increased in a dose-dependent manner in male and female rats at all treatment groups, and was statistically significant in males at doses of =20 mg/kg bw/day and in females at doses of =5 mg/kg bw/day doses. The observed effects are considered to be local, non-systemic effect on the forestomach which result from oral (gavage) administration of copper monochloride.</p> <p><b>Genotoxicity:</b> An in vitro genotoxicity study with copper monochloride showed negative results in a bacterial reverse mutation test with Salmonella typhimurium strains (TA 98, TA 100, TA 1535, and TA 1537) with and without S9 mix at concentrations of up to 1,000 ug/plate. An in vitro test for chromosome aberration in Chinese hamster lung (CHL) cells showed that copper monochloride induced structural and numerical aberrations at the concentration of 50, 70 and 100 ug/mL without S9 mix. In the presence of the metabolic activation system, significant increases of structural aberrations were observed at 50 and 70 ug/mL and significant increases of numerical aberrations were observed at 70 ug/mL. In an in vivo mammalian erythrocyte micronucleus assay, all animals dosed (15 - 60 mg/kg bw) with copper monochloride exhibited similar PCE/(PCE+NCE) ratios and MNPCE frequencies compared to those of the negative control animals. Therefore copper monochloride is not an in vivo mutagen.</p> <p><b>Carcinogenicity:</b> there was insufficient information to evaluate the carcinogenic activity of copper monochloride.</p> <p>Reproductive and developmental toxicity: In the combined repeated dose toxicity study with the reproduction/developmental toxicity screening test (OECD TG 422), copper monochloride was given orally (gavage) to Sprague-Dawley rats for 30 days to males and for 39-51 days to females at concentrations of 0, 1.3, 5.0, 20, and 80 mg/kg bw/day. The NOAEL of copper monochloride for fertility toxicity was 80 mg/kg bw/day for the parental animals. No treatment-related effects were observed on the reproductive organs and the fertility parameters assessed. For developmental toxicity the NOAEL was 20 mg/kg bw/day. Three of 120 pups appeared to have icterus at birth; 4 of 120 pups appeared runted at the highest dose tested (80 mg/kg bw/day).</p>		
LEAD STYPHNATE	<p>The following information refers to contact allergens as a group and may not be specific to this product.</p> <p>Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. The significance of the contact allergen is not simply determined by its sensitisation potential: the distribution of the substance and the opportunities for contact with it are equally important. A weakly sensitising substance which is widely distributed can be a more important allergen than one with stronger sensitising potential with which few individuals come into contact. From a clinical point of view, substances are noteworthy if they produce an allergic test reaction in more than 1% of the persons tested.</p>		
TETRAZENE	<p>Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing, and the lack of minimal lymphocytic inflammation, without eosinophilia. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. On the other hand, industrial bronchitis is a disorder that occurs as a result of exposure due to high concentrations of irritating substance (often particles) and is completely reversible after exposure ceases. The disorder is characterized by difficulty breathing, cough and mucus production.</p>		
BARIUM NITRATE	<p>The material may produce moderate eye irritation leading to inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.</p>		
ANTIMONY TRISULFIDE	<p>* REACH Dossier</p>		
NITROGLYCERIN	<p>The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.</p> <p>Substance has been investigated as a tumorigen, mutagen and reproductive effector. Equivocal tumorigen by RTECS criteria. Reproductive effector in rats.</p>		
NITROCELLULOSE & ZINC & LEAD STYPHNATE & TETRAZENE & ALUMINIUM	<p>No significant acute toxicological data identified in literature search.</p>		
POLYETHYLENE & ANTIMONY TRISULFIDE	<p>The substance is classified by IARC as Group 3: <b>NOT</b> classifiable as to its carcinogenicity to humans. Evidence of carcinogenicity may be inadequate or limited in animal testing.</p>		
ZINC & BARIUM NITRATE & NITROGLYCERIN	<p>The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) and swelling epidermis. Histologically there may be intercellular oedema of the spongy layer (spongiosis) and intracellular oedema of the epidermis.</p>		
Acute Toxicity	✓	Carcinogenicity	✗
Skin Irritation/Corrosion	✗	Reproductivity	✓
Serious Eye Damage/Irritation	✓	STOT - Single Exposure	✗
Respiratory or Skin sensitisation	✓	STOT - Repeated Exposure	✗

Shotshell Loaded Rounds

Mutagenicity ✘

Aspiration Hazard ✘

Legend: ✘ – Data either not available or does not fill the criteria for classification  
✔ – Data available to make classification

SECTION 12 Ecological information

Toxicity

Shotshell Loaded Rounds	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Available
lead	Endpoint	Test Duration (hr)	Species	Value	Source
	NOEC(ECx)	Not Available	Crustacea	0.051mg/L	5
	EC50	72h	Algae or other aquatic plants	1.191mg/L	4
	EC50	96h	Algae or other aquatic plants	0.282-0.864mg/l	4
	LC50	96h	Fish	1.17mg/l	4
nitrocellulose	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Available
iron	Endpoint	Test Duration (hr)	Species	Value	Source
	NOEC(ECx)	48h	Algae or other aquatic plants	0.1-4mg/l	4
	EC50	72h	Algae or other aquatic plants	18mg/l	2
	EC50	48h	Crustacea	>100mg/l	2
	LC50	96h	Fish	0.05mg/l	2
polyethylene	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Available
copper	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50(ECx)	24h	Algae or other aquatic plants	<0.001mg/L	4
	EC50	72h	Algae or other aquatic plants	0.011-0.017mg/L	4
	EC50	48h	Crustacea	<0.001mg/L	4
	EC50	96h	Algae or other aquatic plants	0.03-0.058mg/l	4
	LC50	96h	Fish	0.005-0.06mg/l	4
zinc	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50(ECx)	72h	Algae or other aquatic plants	0.005mg/l	4
	EC50	72h	Algae or other aquatic plants	0.005mg/l	4
	EC50	48h	Crustacea	1.4mg/l	2
	EC50	96h	Algae or other aquatic plants	0.264-0.881mg/l	4
	LC50	96h	Fish	0.16mg/L	4
lead styphnate	Endpoint	Test Duration (hr)	Species	Value	Source
	EC10(ECx)	48h	Crustacea	0.5mg/l	2
	EC50	48h	Crustacea	7.02mg/l	2
tetrazene	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Available
barium nitrate	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50	72h	Algae or other aquatic plants	>1.15mg/l	2
	NOEC(ECx)	72h	Algae or other aquatic plants	>=1.15mg/l	2
	EC50	48h	Crustacea	>=16<=18mg/l	2
	LC50	96h	Fish	>3.5mg/l	2
antimony trisulfide	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50	72h	Algae or other aquatic plants	>2.4mg/l	2
	NOEC(ECx)	2160h	Algae or other aquatic plants	0.032mg/l	2
	EC50	48h	Crustacea	423.45mg/l	2
	EC50	96h	Algae or other aquatic plants	0.61mg/l	2

Continued...



	LC50	96h	Fish	0.93mg/l	2
aluminium	<b>Endpoint</b>	<b>Test Duration (hr)</b>	<b>Species</b>	<b>Value</b>	<b>Source</b>
	LC50	96h	Fish	0.078-0.108mg/l	2
	NOEC(ECx)	48h	Crustacea	>100mg/l	1
	EC50	72h	Algae or other aquatic plants	0.2mg/l	2
	EC50	48h	Crustacea	1.5mg/l	2
	EC50	96h	Algae or other aquatic plants	0.024mg/l	2
nitroglycerin	<b>Endpoint</b>	<b>Test Duration (hr)</b>	<b>Species</b>	<b>Value</b>	<b>Source</b>
	NOEC(ECx)	1440h	Fish	0.03mg/l	2
	EC50	48h	Crustacea	4655mg/l	1
	EC50	96h	Algae or other aquatic plants	0.1-1.3mg/l	4
	LC50	96h	Fish	1.69-2.14mg/l	4
<b>Legend:</b>	Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data				

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**DO NOT** discharge into sewer or waterways.

#### Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
polyethylene	LOW	LOW
tetrazene	HIGH	HIGH
nitroglycerin	LOW (Half-life = 14 days)	LOW (Half-life = 0.73 days)

#### Bioaccumulative potential

Ingredient	Bioaccumulation
polyethylene	LOW (LogKOW = 1.2658)
tetrazene	LOW (LogKOW = -2.0204)

#### Mobility in soil

Ingredient	Mobility
polyethylene	LOW (KOC = 14.3)
tetrazene	LOW (KOC = 238.4)

## SECTION 13 Disposal considerations

#### Waste treatment methods



<b>Product / Packaging disposal</b>	<ul style="list-style-type: none"> <li>▶ Containers may still present a chemical hazard/ danger when empty.</li> <li>▶ Return to supplier for reuse/ recycling if possible.</li> </ul> <p>Otherwise:</p> <ul style="list-style-type: none"> <li>▶ If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.</li> <li>▶ Where possible retain label warnings and SDS and observe all notices pertaining to the product.</li> </ul> <p>For nitroglycerine and similar products:</p> <ul style="list-style-type: none"> <li>▶ Contaminated cloths and sawdust are disposed of at the burning ground by following the appropriate Factory Procedure.</li> <li>▶ The spill area is decontaminated using NG Decontamination Solution'</li> <li>▶ Buildings and equipment taken from service in an NG environment must be decontaminated and inspected.</li> <li>▶ Explosives which are surplus, deteriorated or considered unsafe for transport, storage or use shall be destroyed and the statutory authorities shall be notified.</li> <li>▶ Explosives must not be thrown away, buried, discarded or placed with garbage.</li> <li>▶ This material may be disposed of by burning or detonation but the operation must be performed under the control of a person competent in the destruction of explosives.</li> </ul> <p>Disposal by detonation:</p> <ul style="list-style-type: none"> <li>▶ The explosives to be destroyed must be placed in direct contact with fresh priming charge in a hole which is at least 0.6 metre deep and then adequately stemmed.</li> <li>▶ No detonators shall be inserted into defective explosives.</li> <li>▶ Personnel must be evacuated to a safe distance prior to initiation/firing of the charge.</li> </ul> <p>Disposal by burning:</p> <ul style="list-style-type: none"> <li>▶ Make a sawdust bed or trail adequate for the quantity of explosives to be burned, approximately 400 mm wide and 40 mm deep, upon which the explosive will be laid.</li> <li>▶ If sawdust is not available, newspaper may be used.</li> <li>▶ Normal precautions shall be taken to avoid the spread of fire.</li> <li>▶ Individual trails should not be closer together than 600 mm and should contain not more than 12 kg of explosive.</li> <li>▶ Trails should be side by side, NOT in-line, and not more than four should be set up at one time.</li> <li>▶ Remove any explosive that is not to be burnt to a distance of at least 300 metre.</li> <li>▶ Sufficient diesel oil (never petrol or other highly flammable liquid) should be used to thoroughly wet the sawdust (or paper) at least 4 litre per trail is recommended.</li> <li>▶ Light the trail from a long, rolled paper wick which should be placed downwind and in contact with the end 1m of trail that is not covered with</li> </ul>
-------------------------------------	---

Shotshell Loaded Rounds

	<p>explosive. The wind should blow so that the flame from the wick (and later from the burning explosive) will blow away from the unburned explosive as detonation is more likely to occur if the explosive is preheated by the flame.</p> <ul style="list-style-type: none"> <li>▶ If plastic igniter cord (slow) is available, its use for lighting is recommended instead of paper. One end should be coiled into the sawdust or under the paper and the other end lit from a minimum distance of 7m from the trail.</li> <li>▶ Retire at least 300m or to a safe place.</li> <li>▶ <b>DO NOT return to the site for at least 30 minutes after the burning has apparently finished.</b></li> <li>▶ If the fire goes out do not approach for at least 15 minutes after all trace of fire has gone.</li> <li>▶ <b>DO NOT add more diesel oil unless certain that the flame is completely extinguished.</b></li> </ul> <p>[DYNO]</p> <ul style="list-style-type: none"> <li>▶ <b>DO NOT allow wash water from cleaning or process equipment to enter drains.</b></li> <li>▶ It may be necessary to collect all wash water for treatment before disposal.</li> <li>▶ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.</li> <li>▶ Where in doubt contact the responsible authority.</li> </ul>
--	---

SECTION 14 Transport information

Labels Required

	
Marine Pollutant	
HAZCHEM	1YE

Land transport (ADG)

UN number	0012	
UN proper shipping name	CARTRIDGES FOR WEAPONS, INERT PROJECTILE or CARTRIDGES, SMALL ARMS	
Transport hazard class(es)	Class	1.4S
	Subrisk	Not Applicable
Packing group	Not Applicable	
Environmental hazard	Environmentally hazardous	
Special precautions for user	Special provisions	364
	Limited quantity	5 kg

Air transport (ICAO-IATA / DGR)

UN number	0012	
UN proper shipping name	Cartridges for weapons, inert projectile	
Transport hazard class(es)	ICAO/IATA Class	1.4S
	ICAO / IATA Subrisk	Not Applicable
	ERG Code	3L
Packing group	Not Applicable	
Environmental hazard	Environmentally hazardous	
Special precautions for user	Special provisions	A802
	Cargo Only Packing Instructions	130
	Cargo Only Maximum Qty / Pack	100 kg
	Passenger and Cargo Packing Instructions	130
	Passenger and Cargo Maximum Qty / Pack	25 kg
	Passenger and Cargo Limited Quantity Packing Instructions	Forbidden
	Passenger and Cargo Limited Maximum Qty / Pack	Forbidden

Sea transport (IMDG-Code / GGVSee)

UN number	0012	
UN proper shipping name	CARTRIDGES FOR WEAPONS, INERT PROJECTILE or CARTRIDGES, SMALL ARMS	
Transport hazard class(es)	IMDG Class	1.4S
	IMDG Subrisk	Not Applicable
Packing group	Not Applicable	
Environmental hazard	Marine Pollutant	

<b>Special precautions for user</b>	EMS Number	F-B, S-X
	Special provisions	364
	Limited Quantities	5 kg

**Transport in bulk according to Annex II of MARPOL and the IBC code**

Not Applicable

**Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code**

Product name	Group
lead	Not Available
nitrocellulose	Not Available
iron	Not Available
polyethylene	Not Available
copper	Not Available
zinc	Not Available
lead styphnate	Not Available
tetrazene	Not Available
barium nitrate	Not Available
antimony trisulfide	Not Available
aluminium	Not Available
nitroglycerin	Not Available

**Transport in bulk in accordance with the ICG Code**

Product name	Ship Type
lead	Not Available
nitrocellulose	Not Available
iron	Not Available
polyethylene	Not Available
copper	Not Available
zinc	Not Available
lead styphnate	Not Available
tetrazene	Not Available
barium nitrate	Not Available
antimony trisulfide	Not Available
aluminium	Not Available
nitroglycerin	Not Available

**SECTION 15 Regulatory information****Safety, health and environmental regulations / legislation specific for the substance or mixture****lead is found on the following regulatory lists**

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals  
 Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 4  
 Australian Inventory of Industrial Chemicals (AIIC)  
 Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs  
 International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 1: Carcinogenic to humans  
 International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 2B: Possibly carcinogenic to humans  
 International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

**nitrocellulose is found on the following regulatory lists**

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals  
 Australian Inventory of Industrial Chemicals (AIIC)

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

**iron is found on the following regulatory lists**

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 2  
 Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 4  
 Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 6  
 Australian Inventory of Industrial Chemicals (AIIC)  
 International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

**polyethylene is found on the following regulatory lists**

Australian Inventory of Industrial Chemicals (AIIC)  
 International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

**copper is found on the following regulatory lists**

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 4

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 6

#### zinc is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals  
Australian Inventory of Industrial Chemicals (AIIC)

#### lead styphnate is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals  
Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 10 / Appendix C

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 6

#### tetrazene is found on the following regulatory lists

Australian Inventory of Industrial Chemicals (AIIC)

#### barium nitrate is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals  
Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 6

Australian Inventory of Industrial Chemicals (AIIC)

#### antimony trisulfide is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals  
Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 6

Australian Inventory of Industrial Chemicals (AIIC)

#### aluminium is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals  
Australian Inventory of Industrial Chemicals (AIIC)

#### nitroglycerin is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals  
Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 3

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 4

Australian Inventory of Industrial Chemicals (AIIC)

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

Australian Inventory of Industrial Chemicals (AIIC)

Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 2A: Probably carcinogenic to humans

Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

Australian Inventory of Industrial Chemicals (AIIC)

FEI Equine Prohibited Substances List - Controlled Medication

FEI Equine Prohibited Substances List (EPSL)

### National Inventory Status

National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	Yes
Canada - DSL	No (tetrazene)
Canada - NDSL	No (lead; nitrocellulose; iron; polyethylene; copper; zinc; lead styphnate; barium nitrate; antimony trisulfide; aluminium; nitroglycerin)
China - IECSC	No (lead styphnate; tetrazene)
Europe - EINEC / ELINCS / NLP	No (nitrocellulose; polyethylene)
Japan - ENCS	No (lead; iron; copper; zinc; tetrazene; aluminium)
Korea - KECI	No (tetrazene)
New Zealand - NZIoC	Yes
Philippines - PICCS	No (lead styphnate; tetrazene)
USA - TSCA	Yes
Taiwan - TCSI	No (tetrazene)
Mexico - INSQ	No (tetrazene)
Vietnam - NCI	No (lead styphnate; tetrazene)
Russia - FBEPH	No (lead styphnate; tetrazene)
<b>Legend:</b>	<i>Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.</i>

### SECTION 16 Other information

Revision Date	14/03/2022
Initial Date	14/03/2022

### SDS Version Summary

Version	Date of Update	Sections Updated
2.1	14/03/2022	Acute Health (eye), Acute Health (inhaled), Acute Health (skin), Acute Health (swallowed), Chronic Health, Classification, Fire Fighter (fire/explosion hazard), Physical Properties

#### Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

#### Definitions and abbreviations

PC—TWA: Permissible Concentration-Time Weighted Average  
 PC—STEL: Permissible Concentration-Short Term Exposure Limit  
 IARC: International Agency for Research on Cancer  
 ACGIH: American Conference of Governmental Industrial Hygienists  
 STEL: Short Term Exposure Limit  
 TEEL: Temporary Emergency Exposure Limit.  
 IDLH: Immediately Dangerous to Life or Health Concentrations  
 ES: Exposure Standard  
 OSF: Odour Safety Factor  
 NOAEL :No Observed Adverse Effect Level  
 LOAEL: Lowest Observed Adverse Effect Level  
 TLV: Threshold Limit Value  
 LOD: Limit Of Detection  
 OTV: Odour Threshold Value  
 BCF: BioConcentration Factors  
 BEI: Biological Exposure Index  
 AIIC: Australian Inventory of Industrial Chemicals  
 DSL: Domestic Substances List  
 NDSL: Non-Domestic Substances List  
 IECSC: Inventory of Existing Chemical Substance in China  
 EINECS: European INventory of Existing Commercial chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 NLP: No-Longer Polymers  
 ENCS: Existing and New Chemical Substances Inventory  
 KECI: Korea Existing Chemicals Inventory  
 NZIoC: New Zealand Inventory of Chemicals  
 PICCS: Philippine Inventory of Chemicals and Chemical Substances  
 TSCA: Toxic Substances Control Act  
 TCSI: Taiwan Chemical Substance Inventory  
 INSQ: Inventario Nacional de Sustancias Químicas  
 NCI: National Chemical Inventory  
 FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.