

Li-ion Rechargeable Battery - NL1834R TSA OUTDOORS

Chemwatch Hazard Alert Code: 2

Issue Date: 19/11/2021 Print Date: 22/11/2021 L.GHS.AUS.EN

Chemwatch: 5511-48
Version No: 2.1
Safety Data Sheet according to WHS Regulations (Hazardous Chemicals) Amendment 2020 and ADG requirements

SECTION 1 Identification of the substance / mixture and of the company / undertaking

Product	Identifier
---------	------------

1 Todaot Idontino	
Product name	Li-ion Rechargeable Battery - NL1834R
Chemical Name	Not Applicable
Synonyms	Rating: 3.6V, 3400mAh, 12.24Wh, Weight: Approx. 47.9g
Proper shipping name	LITHIUM ION BATTERIES (including lithium ion polymer batteries)
Chemical formula	Not Applicable
Other means of identification	Not Available

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Rechargeable Lithium-Ion Battery. NOTE: Chemical materials are stored in sealed case. The toxic properties of the electrode materials are hazardous only if the materials are released by damaging the cell or if exposed to fire. The sealed battery is not hazardous in normal use. The chemical hazards are related to the leaked battery contents.

Use according to manufacturer's directions.

Details of the supplier of the safety data sheet

Registered company name	TSA OUTDOORS
Address	Unit 6/ 9 - 13 Winbourne Road Brookvale NSW 2100 Australia
Telephone	+61 2 9938 3244
Fax	+61 2 9939 2972
Website	<u>Tsaoutdoors.com.au</u>
Email	sales@tasco.com.au

Emergency telephone number

Association / Organisation	Aaron Millard
Emergency telephone numbers	+61 450 086 593 (Mon-Fri, 9 am-6pm)
Other emergency telephone numbers	Not Available

SECTION 2 Hazards identification

Classification of the substance or mixture

Poisons Schedule	Not Applicable
Classification [1]	Skin Corrosion/Irritation Category 1B, Sensitisation (Skin) Category 1, Serious Eye Damage/Eye Irritation Category 1, Sensitisation (Respiratory) Category 1, Carcinogenicity Category 2, Specific Target Organ Toxicity - Repeated Exposure Category 2
Legend:	1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI

Label elements

Hazard pictogram(s)





Signal word Dange

Hazard statement(s)

H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H351	Suspected of causing cancer.

Chemwatch: **5511-48**Version No: **2.1**

Page 2 of 15

Li-ion Rechargeable Battery - NL1834R

Issue Date: 19/11/2021 Print Date: 22/11/2021

H373

May cause damage to organs through prolonged or repeated exposure.

Precautionary statement(s) Prevention

P201	Obtain special instructions before use.
P260	Do not breathe dust/fume.
P264	Wash all exposed external body areas thoroughly after handling.
P280	Wear protective gloves, protective clothing, eye protection and face protection.
P284	[In case of inadequate ventilation] wear respiratory protection.
P272	Contaminated work clothing should not be allowed out of the workplace.

Precautionary statement(s) Response

P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice/ attention.
P310	Immediately call a POISON CENTER/doctor/physician/first aider.
P342+P311	If experiencing respiratory symptoms: Call a POISON CENTER/doctor/physician/first aider.
P302+P352	IF ON SKIN: Wash with plenty of water and soap.
P363	Wash contaminated clothing before reuse.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.

Precautionary statement(s) Storage

P405 Store locked up.

Precautionary statement(s) Disposal

P501 Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
Not Available		sealed metal case containing
7440-02-0	5	nickel
7440-48-4	15	cobalt
7440-50-8	10	copper
7440-44-0	15	carbon, activated
7439-93-2	7	lithium
9003-07-0	5.3	polypropylene
7429-90-5	4.2	aluminium
96-49-1	4	ethylene carbonate
Not Available	3.7	Carbonic acid, dimethyl ester.
7439-96-5	3.7	manganese
21324-40-3	2.57	lithium fluorophosphate
24937-79-9	0.5	vinylidene fluoride homopolymer
Legend:	1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. Classification drawn from C&L * EU IOELVs available	

SECTION 4 First aid measures

Description of first aid measures

Eye Contact

Generally not applicable.

If this product comes in contact with the eyes:

- Immediately hold eyelids apart and flush the eye continuously with running water.
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
 - Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.
- Transport to hospital or doctor without delay.
- ▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

Chemwatch: **5511-48**Version No: **2.1**

Li-ion Rechargeable Battery - NL1834R

Issue Date: 19/11/2021 Print Date: 22/11/2021

Skin Contact	 Generally not applicable. If skin contact occurs: Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.
Inhalation	 If fumes or combustion products are inhaled remove from contaminated area. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Transport to hospital, or doctor, without delay.
Ingestion	 Not considered a normal route of entry. For advice, contact a Poisons Information Centre or a doctor at once. Urgent hospital treatment is likely to be needed. If swallowed do NOT induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Observe the patient carefully. Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. Transport to hospital or doctor without delay.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 Firefighting measures

Extinguishing media

- ▶ There is no restriction on the type of extinguisher which may be used.
- Use extinguishing media suitable for surrounding area.

Special hazards arising from the substrate or mixture

Fire Incompatibility	Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result	
Advice for firefighters		
Fire Fighting	 Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves in the event of a fire. Prevent, by any means available, spillage from entering drains or water courses. Use fire fighting procedures suitable for surrounding area. DO NOT approach containers suspected to be hot. Cool fire exposed containers with water spray from a protected location. If safe to do so, remove containers from path of fire. Equipment should be thoroughly decontaminated after use. 	
Fire/Explosion Hazard	▶ Non combustible. ▶ Not considered a significant fire risk, however containers may burn. Decomposition may produce toxic fumes of: carbon dioxide (CO2) fluorides phosphorus oxides (POx) metal oxides other pyrolysis products typical of burning organic material.	
HAZCHEM	2Y	

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	 Clean up all spills immediately. Secure load if safe to do so. Bundle/collect recoverable product. Collect remaining material in containers with covers for disposal.
Major Spills	 Clean up all spills immediately. Wear protective clothing, safety glasses, dust mask, gloves. Secure load if safe to do so. Bundle/collect recoverable product. Use dry clean up procedures and avoid generating dust. Vacuum up (consider explosion-proof machines designed to be grounded during storage and use). Water may be used to prevent dusting. Collect remaining material in containers with covers for disposal. Flush spill area with water.

Chemwatch: 5511-48 Version No: 2.1

Li-ion Rechargeable Battery - NL1834R

Issue Date: 19/11/2021 Print Date: 22/11/2021

SECTION 7 Handling and storage

Precautions for safe handling

Before handling the batteries, the users should read the product specification carefully. Do not crush, pierce the battery terminals with conductive goods. Not directly heat or solder. Do not throw in fire. Do not mix batteries of different types. Do not mix new and used batteries. Keep batteries in non-conductive trays.

- ► Limit all unnecessary personal contact.
- Wear protective clothing when risk of exposure occurs.
- - When handling DO NOT eat, drink or smoke.
 - Always wash hands with soap and water after handling.
 - Avoid physical damage to containers.
 - Use good occupational work practice.
 - Doserve manufacturer's storage and handling recommendations contained within this SDS.

Store away from incompatible materials.

Other information

- Keep dry.Store under cover.
- Protect containers against physical damage.
- ▶ Observe manufacturer's storage and handling recommendations contained within this SDS.

Keep out of reach of children. Store out of direct sunlight

Conditions for safe storage, including any incompatibilities

Suitable container

Keep batteries in original packaging until use.
▶ Packaging as recommended by manufacturer.

Storage incompatibility Av

- ▶ Avoid reaction with oxidising agents
- Avoid strong bases.

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Australia Exposure Standards	nickel	Nickel, metal	1 mg/m3	Not Available	Not Available	Not Available
Australia Exposure Standards	nickel	Nickel, powder	1 mg/m3	Not Available	Not Available	Not Available
Australia Exposure Standards	cobalt	Cobalt, metal dust & fume (as Co)	0.05 mg/m3	Not Available	Not Available	Not Available
Australia Exposure Standards	copper	Copper (fume)	0.2 mg/m3	Not Available	Not Available	Not Available
Australia Exposure Standards	copper	Copper, dusts & mists (as Cu)	1 mg/m3	Not Available	Not Available	Not Available
Australia Exposure Standards	aluminium	Aluminium, pyro powders (as Al)	5 mg/m3	Not Available	Not Available	Not Available
Australia Exposure Standards	aluminium	Aluminium (welding fumes) (as Al)	5 mg/m3	Not Available	Not Available	Not Available
Australia Exposure Standards	aluminium	Aluminium (metal dust)	10 mg/m3	Not Available	Not Available	Not Available
Australia Exposure Standards	manganese	Manganese, fume (as Mn)	1 mg/m3	3 mg/m3	Not Available	Not Available

Emergency Limits

Ingredient	TEEL-1	TEEL-2	TEEL-3
nickel	4.5 mg/m3	50 mg/m3	99 mg/m3
cobalt	0.18 mg/m3	2 mg/m3	20 mg/m3
copper	3 mg/m3	33 mg/m3	200 mg/m3
carbon, activated	6 mg/m3	330 mg/m3	2,000 mg/m3
lithium	3.3 mg/m3	36 mg/m3	220 mg/m3
polypropylene	5.2 mg/m3	58 mg/m3	350 mg/m3
ethylene carbonate	30 mg/m3	330 mg/m3	2,000 mg/m3
manganese	3 mg/m3	5 mg/m3	1,800 mg/m3
lithium fluorophosphate	7.5 mg/m3	83 mg/m3	500 mg/m3

Ingredient	Original IDLH	Revised IDLH
nickel	10 mg/m3	Not Available
cobalt	20 mg/m3	Not Available
copper	100 mg/m3	Not Available
carbon, activated	Not Available	Not Available
lithium	Not Available	Not Available
polypropylene	Not Available	Not Available
aluminium	Not Available	Not Available
ethylene carbonate	Not Available	Not Available
manganese	500 mg/m3	Not Available

Version No: 2.1

Li-ion Rechargeable Battery - NL1834R

Issue Date: 19/11/2021 Print Date: 22/11/2021

Ingredient	Original IDLH	Revised IDLH
lithium fluorophosphate	Not Available	Not Available
vinylidene fluoride homopolymer	Not Available	Not Available

Occupational Exposure Banding

Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit	
lithium	С	> 0.1 to ≤ milligrams per cubic meter of air (mg/m³)	
ethylene carbonate	E	≤ 0.01 mg/m³	
lithium fluorophosphate	E	≤ 0.01 mg/m³	
Notes:	Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health		

MATERIAL DATA

Exposure controls

posure controls	
Appropriate engineering	General exhaust is adequate under normal operating conditions.
controls	Provide adequate ventilation in warehouse or closed storage areas.
Personal protection	
Eye and face protection	None under normal operating conditions. OTHERWISE: Safety glasses.
Skin protection	See Hand protection below
Hands/feet protection	None under normal operating conditions. OTHERWISE: Wear chemical protective gloves, e.g. PVC. Wear safety footwear or safety gumboots, e.g. Rubber
Body protection	See Other protection below
Other protection	None under normal operating conditions. OTHERWISE: Overalls. PVC Apron. PVC protective suit may be required if exposure severe. Eyewash unit. Ensure there is ready access to a safety shower.

Respiratory protection

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required. Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	A-AUS P2	-	A-PAPR-AUS / Class 1 P2
up to 50 x ES	-	A-AUS / Class 1 P2	-
up to 100 x ES	-	A-2 P2	A-PAPR-2 P2 ^

^{^ -} Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Yellow and Black colour hermetically sealed solid object; immiscible with water.		
Physical state	Manufactured	Relative density (Water = 1)	Not Applicable
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Applicable
pH (as supplied)	Not Applicable	Decomposition temperature	Not Applicable
Melting point / freezing point (°C)	Not Applicable	Viscosity (cSt)	Not Applicable
Initial boiling point and boiling range (°C)	Not Applicable	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	Not Applicable	Taste	Not Available
Evaporation rate	Not Applicable	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available

Version No: 2.1

Li-ion Rechargeable Battery - NL1834R

Issue Date: **19/11/2021**Print Date: **22/11/2021**

Upper Explosive Limit (%)	Not Applicable	Surface Tension (dyn/cm or mN/m)	Not Applicable
Lower Explosive Limit (%)	Not Applicable	Volatile Component (%vol)	Not Applicable
Vapour pressure (kPa)	Not Applicable	Gas group	Not Available
Solubility in water	Immiscible	pH as a solution (%)	Not Applicable
Vapour density (Air = 1)	Not Applicable	VOC g/L	Not Applicable

SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	Product is considered stable and hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 Toxicological information

nformation	nn	tovico	Indical	offacte

Vapor generated from burning batteries may cause throat irritation. Not normally a hazard due to physical form of product.

Inhaled

Acidic corrosives produce respiratory tract irritation with coughing, choking and mucous membrane damage. Symptoms of exposure may include dizziness, headache, nausea and weakness. In more severe exposures, pulmonary oedema may be evident either immediately or after a latent period of 5-72 hours. Symptoms of pulmonary oedema include a tightness in the chest, dyspnoea, frothy sputum and cyanosis. Examination may reveal hypotension, a weak and rapid pulse and moist rates. Death, due to anoxia, may occur several hours after onset of the pulmonary oedema.

Ingestion

Not normally a hazard due to physical form of product.

Skin Contact

Not normally a hazard due to physical form of product.

Entry into the blood-stream through, for example, cuts, abrasions, puncture wounds or lesions, may produce systemic injury with harmful effects.

Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

The material may produce severe skin irritation after prolonged or repeated exposure, and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) thickening of the epidermis.

Histologically there may be intercellular oedema of the spongy layer (spongiosis) and intracellular oedema of the epidermis. Prolonged contact is unlikely, given the severity of response, but repeated exposures may produce severe ulceration.

Eve

Not normally a hazard due to physical form of product.

The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

The normal handling of sealed cells or batteries is not hazardous. Exposure to battery content causes severe eye irritation, skin irritation and harmful effect if swallowed.

Practical experience shows that skin contact with the material is capable either of inducing a sensitisation reaction in a substantial number of individuals, and/or of producing a positive response in experimental animals.

Substances that can cause occupational asthma (also known as asthmagens and respiratory sensitisers) can induce a state of specific airway hyper-responsiveness via an immunological, irritant or other mechanism. Once the airways have become hyper-responsive, further exposure to the substance, sometimes even to tiny quantities, may cause respiratory symptoms. These symptoms can range in severity from a runny nose to asthma. Not all workers who are exposed to a sensitiser will become hyper-responsive and it is impossible to identify in advance who are likely to become hyper-responsive.

Substances than can cuase occupational asthma should be distinguished from substances which may trigger the symptoms of asthma in people with pre-existing air-way hyper-responsiveness. The latter substances are not classified as asthmagens or respiratory sensitisers Wherever it is reasonably practicable, exposure to substances that can cuase occupational asthma should be prevented. Where this is not possible the primary aim is to apply adequate standards of control to prevent workers from becoming hyper-responsive.

Chronic

Activities giving rise to short-term peak concentrations should receive particular attention when risk management is being considered. Health surveillance is appropriate for all employees exposed or liable to be exposed to a substance which may cause occupational asthma and there should be appropriate consultation with an occupational health professional over the degree of risk and level of surveillance.

Practical evidence shows that inhalation of the material is capable of inducing a sensitisation reaction in a substantial number of individuals at a greater frequency than would be expected from the response of a normal population.

Pulmonary sensitisation, resulting in hyperactive airway dysfunction and pulmonary allergy may be accompanied by fatigue, malaise and aching. Significant symptoms of exposure may persist for extended periods, even after exposure ceases. Symptoms can be activated by a variety of nonspecific environmental stimuli such as automobile exhaust, perfumes and passive smoking.

On the basis, primarily, of animal experiments, concern has been expressed that the material may produce carcinogenic or mutagenic effects; in respect of the available information, however, there presently exists inadequate data for making a satisfactory assessment.

Harmful: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed. Serious damage (clear functional disturbance or morphological change which may have toxicological significance) is likely to be caused by repeated or prolonged exposure. As a rule the material produces, or contains a substance which produces severe lesions. Such damage may become apparent following direct application in subchronic (90 day) toxicity studies or following sub-acute (28 day) or chronic (two-year) toxicity tests.

Li-ion Rechargeable Battery - NL1834R	TOXICITY Not Available	IRRITATION Not Available
nickel	TOXICITY Oral(Rat) LD50; 5000 mg/kg ^[2]	IRRITATION Eye: no adverse effect observed (not irritating) ^[1]

Page 7 of 15

Li-ion Rechargeable Battery - NL1834R

Issue Date: 19/11/2021 Print Date: 22/11/2021

Skin: no adverse effect observed (not irritating) $^{[1]}$ TOXICITY IRRITATION dermal (rat) LD50: >2000 $mg/kg^{[1]}$ Eye: adverse effect observed (irritating) $^{[1]}$ cobalt Skin: no adverse effect observed (not irritating) [1]Inhalation(Rat) LC50; <=0.05 mg/l4h[1] Oral(Rat) LD50; ~550 mg/kg[1] TOXICITY IRRITATION dermal (rat) LD50: >2000 mg/kg^[1] Eye: no adverse effect observed (not irritating)^[1] copper Inhalation(Rat) LC50; 0.733 mg/l4h^[1] Skin: no adverse effect observed (not irritating)^[1] Oral(Mouse) LD50; 0.7 mg/kg^[2] IRRITATION TOXICITY Eye: no adverse effect observed (not irritating)[1]carbon, activated Oral(Rat) LD50; >2000 mg/kg[1] Skin: no adverse effect observed (not irritating)^[1] TOXICITY IRRITATION Not Available Eye: adverse effect observed (irritating)[1] lithium Skin: adverse effect observed (corrosive)^[1] TOXICITY IRRITATION polypropylene Not Available Oral(Mouse) LD50; 3200 mg/kg[2] TOXICITY IRRITATION Inhalation(Rat) LC50; >2.3 mg/l4h[1] Eye: no adverse effect observed (not irritating)^[1] aluminium Oral(Rat) LD50; >2000 mg/kg[1] Skin: no adverse effect observed (not irritating)^[1] IRRITATION TOXICITY dermal (rat) LD50: >2000 mg/kg[1] Eye (rabbit): 20 mg - mild Oral(Rat) LD50; >2000 mg/kg[1] Eye: adverse effect observed (irritating)^[1] ethylene carbonate Skin (rabbit): 660 mg - moderate Skin: no adverse effect observed (not irritating)[1]TOXICITY IRRITATION Inhalation(Rat) LC50; >5.14 mg/l4h^[1] Eye (rabbit): 500 mg/24h - mild Oral(Rat) LD50; >2000 mg/kg^[1] Eye: no adverse effect observed (not irritating)^[1] manganese Skin (rabbit): 500 mg/24h - mild Skin: no adverse effect observed (not irritating)^[1] TOXICITY IRRITATION lithium fluorophosphate Oral(Rat) LD50; 50-300 mg/kg $^{[1]}$ Not Available TOXICITY IRRITATION vinvlidene fluoride homopolymer Not Available Not Available Legend: 1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances Oral (rat) TDLo: 500 mg/kg/5D-I Inhalation (rat) TCLo: 0.1 mg/m3/24H/17W-C NICKEL Tenth Annual Report on Carcinogens: Substance anticipated to be Carcinogen [National Toxicology Program: U.S. Dep. of Health & Human Services 2002] Allergic reactions which develop in the respiratory passages as bronchial asthma or rhinoconjunctivitis, are mostly the result of reactions of the allergen with specific antibodies of the IgE class and belong in their reaction rates to the manifestation of the immediate type. In addition to the allergen-specific potential for causing respiratory sensitisation, the amount of the allergen, the exposure period and the genetically determined disposition of the exposed person are likely to be decisive. Factors which increase the sensitivity of the mucosa may play a role in predisposing a person to allergy. They may be genetically determined or acquired, for example, during infections or exposure to irritant substances COBALT Immunologically the low molecular weight substances become complete allergens in the organism either by binding to peptides or proteins (haptens) or after metabolism (prohaptens). Particular attention is drawn to so-called atopic diathesis which is characterised by an increased susceptibility to allergic rhinitis, allergic bronchial asthma and atopic eczema (neurodermatitis) which is associated with increased IgE synthesis. Exogenous allergic alveolitis is induced essentially by allergen specific immune-complexes of the IgG type; cell-mediated reactions (T lymphocytes) may be involved. Such allergy is of the delayed type with onset up to four hours following exposure. WARNING: Inhalation of high concentrations of copper fume may cause "metal fume fever", an acute industrial disease of short duration. Symptoms are tiredness, influenza like respiratory tract irritation with fever COPPER for copper and its compounds (typically copper chloride):

Acute toxicity: There are no reliable acute oral toxicity results available. In an acute dermal toxicity study (OECD TG 402), one group of 5 male

Chemwatch: 5511-48 Page 8 of 15

Version No: 2.1

Li-ion Rechargeable Battery - NL1834R

Issue Date: **19/11/2021**Print Date: **22/11/2021**

rats and 5 groups of 5 female rats received doses of 1000, 1500 and 2000 mg/kg bw via dermal application for 24 hours. The LD50 values of copper monochloride were 2,000 mg/kg bw or greater for male (no deaths observed) and 1,224 mg/kg bw for female. Four females died at both 1500 and 2000 mg/kg bw, and one at 1,000 mg/kg bw. Symptom of the hardness of skin, an exudation of hardness site, the formation of scar and reddish changes were observed on application sites in all treated animals. Skin inflammation and injury were also noted. In addition, a reddish or black urine was observed in females at 2,000, 1,500 and 1,000 mg/kg bw. Female rats appeared to be more sensitive than male based on mortality and clinical signs.

No reliable skin/eye irritation studies were available. The acute dermal study with copper monochloride suggests that it has a potential to cause skin irritation.

Repeat dose toxicity: In repeated dose toxicity study performed according to OECD TG 422, copper monochloride was given orally (gavage) to Sprague-Dawley rats for 30 days to males and for 39 - 51 days to females at concentrations of 0, 1.3, 5.0, 20, and 80 mg/kg bw/day. The NOAEL value was 5 and 1.3 mg/kg bw/day for male and female rats, respectively. No deaths were observed in male rats. One treatment-related death was observed in female rats in the high dose group. Erythropoietic toxicity (anaemia) was seen in both sexes at the 80 mg/kg bw/day. The frequency of squamous cell hyperplasia of the forestomach was increased in a dose-dependent manner in male and female rats at all treatment groups, and was statistically significant in males at doses of =20 mg/kg bw/day and in females at doses of =5 mg/kg bw/day doses. The observed effects are considered to be local, non-systemic effect on the forestomach which result from oral (gavage) administration of copper monochloride. Genotoxicity: An in vitro genotoxicity study with copper monochloride showed negative results in a bacterial reverse mutation test with Salmonella typhimurium strains (TA 98, TA 100, TA 1535, and TA 1537) with and without S9 mix at concentrations of up to 1,000 ug/plate. An in vitro test for chromosome aberration in Chinese hamster lung (CHL) cells showed that copper monochloride induced structural and numerical aberrations at the concentration of 50, 70 and 100 ug/mL without S9 mix. In the presence of the metabolic activation system, significant increases of structural aberrations were observed at 50 and 70 ug/mL and significant increases of numerical aberrations were observed at 70 ug/mL. In an in vivo mammalian erythrocyte micronucleus assay, all animals dosed (15 - 60 mg/kg bw) with copper monochloride exhibited similar PCE/(PCE+NCE) ratios and MNPCE frequencies compared to those of the negative control animals. Therefore copper monochloride is not an in vivo mutagen.

Carcinogenicity: there was insufficient information to evaluate the carcinogenic activity of copper monochloride.

Reproductive and developmental toxicity. In the combined repeated dose toxicity study with the reproduction/developmental toxicity screening test (OECD TG 422), copper monochloride was given orally (gavage) to Sprague-Dawley rats for 30 days to males and for 39-51 days to females at concentrations of 0, 1.3, 5.0, 20, and 80 mg/kg bw/day. The NOAEL of copper monochloride for fertility toxicity was 80 mg/kg bw/day for the parental animals. No treatment-related effects were observed on the reproductive organs and the fertility parameters assessed. For developmental toxicity the NOAEL was 20 mg/kg bw/day. Three of 120 pups appeared to have icterus at birth; 4 of 120 pups appeared runted at the highest dose tested (80 mg/kg bw/day).

* For pyrolyzate

for poly-alpha-olefins (PAOs):

PAOs are highly branched isoparaffinic chemicals produced by oligomerisation of 1-octene, 1-decene, and/or 1-dodecene. The crude polyalphaolefin mixture is then distilled into appropriate product fractions to meet specific viscosity specifications and hydrogenated. Read across data exist for health effects endpoints from the following similar *hydrogenated* long chain branched alkanes derived from a C8, C10, and/or C12 alpha olefins:

- Decene homopolymer
- ► Decene/dodecene copolymer
- ► Octene/decene/dodecene copolymer
- ► Dodecene trimer

The data for these structural analogs demonstrated no evidence of health effects. In addition, there is evidence in the literature that alkanes with 30 or more carbon atoms are unlikely to be absorbed when administered orally. The physicochemical data suggest that it is unlikely that significant absorption will occur. If a substance of the size and structure of a typical PAO is absorbed, then the principal mechanisms of absorption after oral administration are likely to be passive diffusion and absorption by way of the lymphatic system. The former requires both good lipid solubility and good water solubility as the substance has to partition from an agueous environment through a lipophilic membrane into another aqueous environment during absorption. Absorption by way of the lymphatics occurs by mechanisms analogous to those that absorb fatty acids and is limited by the size of the molecule. Lipophilicity generally enhances the ability of chemicals to cross biological membranes. Biotransformation by mixed function oxidases often increases the water solubility of a substance; however, existing data suggest that these substances will not undergo oxidation to more hydrophilic metabolites. Finally, a chemical must have an active functional group that can interact chemically or physically with the target cell or receptor upon reaching it; there are no moieties in PAOs that represent a functional group that may have biological activity. The water solubilities of a C10 dimer PAO and a C12 trimer PAO were determined to be <1 ppb and < 1 ppt respectively. The partition coefficient for a C12 trimer PAO was determined to be log Kow of >7. Given the very low water solubility it is extremely unlikely that PAOs will be absorbed by passive diffusion following oral administration, and the size of the molecules suggest that the extent of lymphatic absorption is likely to be very low. Although PAOs are relatively large lipophilic compounds, and molecular size may be a critical limiting determinant for absorption, there is some evidence that these substances are absorbed. However, the lack of observed toxicity in the studies with PAOs suggests that these products are absorbed poorly, if at all. Furthermore, a review of the literature regarding the absorption and metabolism of long chain alkanes indicates that alkanes with 30+ carbon atoms are unlikely to be absorbed. For example the absorption of squalane, an analogous C30 product, administered orally to male CD rats was examined - essentially all of the squalane was recovered unchanged in the faeces. At the same time, the hydrophobic properties of PAOs suggest that, should they be absorbed, they would undergo limited distribution in the aqueous systemic circulation and reach potential target organs in limited concentrations.

POLYPROPYLENE

In addition to the general considerations discussed above, the low volatility of PAOs indicates that, under normal conditions of use or transportation, exposure by the inhalation route is unlikely. In particular, the high viscosity of these substances suggests that it would be difficult to generate a high concentration of respirable particles in the air.

Acute toxicity: PAOs (decene/dodecene copolymer, octene/decene/dodecene homo-polymer, and dodecene trimer) have been adequately tested for acute oral toxicity. There were no deaths when the test materials were administered at doses of 5,000 mg/kg (decene/dodecene copolymer and dodecene trimer) and at 2,000 mg/kg (octene/decene/dodecene copolymer) in rats. Overall, the acute oral LD50 for these substances was greater than the 2000 mg/kg limit dose, indicating a relatively low order of toxicity.

PAOs (decene/dodecene copolymer, octene/decene/dodecene copolymer, and dodecene trimer) have been tested for acute dermal toxicity. No mortality was observed for any substance when administered at the limit dose of 2000 or 5000 mg/kg. Overall, the acute dermal LD50 for these substances was greater than the 2000 mg/kg limit dose, indicating a relatively low order of toxicity.

1-Decene, homopolymer, is absorbed (unexpectedly for a high molecular weight polymer) to a moderate degree in rat skin and is eliminated slowly

PAOs (decene homopolymer, decene/dodecene copolymer, and decene trimer) have been tested for acute inhalation toxicity. Rats were exposed to aerosols of the substances at nominal atmospheric concentrations of 2.5, 5.0, and 5.06 mg/L, respectively, for four hours. These levels were the maximum attainable concentrations under the conditions of the tests, due to the low volatility and high viscosity of the test material. No mortality was noted, and all animals fully recovered following depuration. The lack of mortality at concentrations at or above the limit dose of 2.0 mg/L indicates a relatively low order of toxicity for these substances.

Repeat dose toxicity: Eight repeated-dose toxicity studies using two different animal species, rats and mice, and oral and dermal routes of administration have been conducted with three structural analogs. These data suggest that the structural analogs exhibit a low order of toxicity following repeated applications, due to their similarity in chemical structures and physicochemical properties.

One 28-day oral toxicity study in rats, one 90-day dermal and two 90-day dietary studies in rats, and a dermal carcinogenicity study in mice exist for decene homopolymer. A rat oral combined reproductive toxicity and 91-day systemic toxicity study was also conducted with decene homopolymer. In addition, 28-day rat oral toxicity studies exist for two structurally analogous substances (dodecene trimer and octene/decene /dodecene copolymer); and a 90-day rat dermal toxicity study exists for octene/decene/dodecene copolymer. Results from these studies show a low order of repeated dose toxicity. The dermal NOAEL for systemic toxicity studies was equal to or greater than 2000 mg/kg/day.

The oral NOAEL for 1-decene homopolymer is between 5,000 and 20,000 mg/kg/day in Sprague-Dawley rats.

Rats exposed repeatedly by dermal exposure at doses of 2000 mg/kg decene/dodecene copolymer showed increased incidences of hyperplasia of the sebaceous glands, hyperplasia/hyperkeratosis of the epidermis and dermal inflammation. These symptoms generally subsided within 2

Chemwatch: 5511-48 Page 9 of 15 Issue Date: 19/11/2021 Version No: 2.1 Print Date: 22/11/2021

Li-ion Rechargeable Battery - NL1834R

weeks. Males showed decreased body weight gain and altered serum chemistry.

In a 90-day feeding study rats receiving 20000 ppm of 1-decene, homopolymer, hydrogenated did not exhibit any clinical signs of systemic toxicity. Marginal effects on clinical chemistry (glucose and ALT in males; sodium, phosphorus and calcium in females) were seen.

Reproductive toxicity: Data are available for decene homopolymer. Results from these studies show a low order of reproductive/ developmental toxicity. The NOAEL for reproductive toxicity was 1000 mg/kg/day, the highest concentration tested. The lack of effects on fertility in this study or effects on reproductive organs in this or other subchronic studies with closely related chemicals indicates that PAOs are unlikely to exert effects on reproduction.

Developmental toxicity: Decene homopolymer (with 10 ppm of an antioxidant) was administered once daily on gestation days 0-19 via dermal application to presumed-pregnant rats at doses of 0, 800, and 2000 mg/kg/day. Dermal administration of the test material did not adversely affect parameters of reproductive performance during gestation, nor did it adversely affect in utero survival and development of the offspring. The NOAEL in this study for developmental parameters was 2000 mg/kg/day.

Genotoxicity: Information for the following PAOs (decene homopolymer, octene/decene/dodecene copolymer, dodecene trimer; and decene/dodecene copolymer [prepared from 10% C12 and 90% C10 alpha olefins; approx. 33% trimer and 51% tetramer, 16% pentamer and higher]) is available. Either bacterial or mammalian gene mutation assays, in vitro chromosomal aberration assays, or in vivo chromosomal aberration assays have been conducted for these substances. Neither mutagenicity nor clastogenicity were exhibited by any of these substances in the referenced in vivo or in vitro tests, with or without metabolic activation.

Carcinogenicity: While alpha-olefin polymers have similar properties to mineral oils, they do not contain polycyclic aromatic hydrocarbons, or other known possible carcinogens.

Decene homopolymer produced no treatment-related tumors in C3H mice treated with a 50 ul/application twice weekly for 104 weeks. In addition, survival (56%) was greater than in any other group, including the untreated control.

The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis

for ethylene carbonate

Mammalian toxicity: Reliable acute toxicity tests are available on ethylene carbonate. Ethylene carbonate is practically nontoxic following acute oral exposure in a test that meets OECD and EPA test guidelines; the LD50 is >5000 mg/kg. The dermal LD50 is >2000 mg/kg, in a test that meets OECD and EPA test guidelines.

Ethylene carbonate is rapidly metabolized to ethylene glycol. Following gavage administration to rats, ethylene carbonate is rapidly converted into ethylene divcol; the half-life for disappearance of ethylene carbonate from blood was 0.25 hours. As a result, the mammalian toxicity of ethylene carbonate is nearly identical to that of ethylene glycol for endpoints where both have been tested

Ethylene carbonate was mixed in the diet of 26 male and 26 female Crl: CD(SD) rats for 18 months at concentrations of 25,000 ppm for males and females and 50,000 ppm for females; males were also fed 50,000 ppm for 42 weeks, and 40,000 ppm for 16 weeks. Survivors were observed to 24 months. Compound intake (mg/kg/day) was not reported, but is estimated to be approximately 250 and 500 mg/kg/day. No toxic effects were found in females, but increased mortality was seen in males at both dose levels. No high-dose males survived week 60 and only 10 low-dose males survived to week 78. Males had severe nephrotoxicity, characteristic of ethylene glycol toxicity.

The following in vitro genotoxicity tests were conducted on ethylene carbonate, without indications of genotoxicity: an Ames mutagenicity assay, an unscheduled DNA synthesis assay using rat hepatocytes, and a cell transformation assay using BALB/3T3 cells. No in vivo genotoxicity studies on ethylene carbonate were found; however, ethylene glycol has been tested and was negative in a rat dominant lethal assay. Gavage administration of ethylene carbonate to pregnant rats days 6-15 of gestation resulted in systemic toxicity at doses of 3000 mg/kg/day, including post-dose salivation. The NOAEL for maternal toxicity was 1500 mg/kg/day. Similar to ethylene glycol, there were increased soft tissue (hydrocephalus, umbilical herniation, gastroschisis, cleft palate, misshapen and compressed stomach) and skeletal malformations at 3000 mg/kg/day, but not at 1500 mg/kg/day,

For ethylene glycol:

Ethylene glycol is quickly and extensively absorbed through the gastrointestinal tract. Limited information suggests that it is also absorbed through the respiratory tract; dermal absorption is apparently slow. Following absorption, ethylene glycol is distributed throughout the body according to total body water. In most mammalian species, including humans, ethylene glycol is initially metabolised by alcohol. dehydrogenase to form glycolaldehyde, which is rapidly converted to glycolic acid and glyoxal by aldehyde oxidase and aldehyde dehydrogenase. These metabolites are oxidised to glyoxylate; glyoxylate may be further metabolised to formic acid, oxalic acid, and glycine. Breakdown of both glycine and formic acid can generate CO2, which is one of the major elimination products of ethylene glycol. In addition to exhaled CO2, ethylene glycol is eliminated in the urine as both the parent compound and glycolic acid. Elimination of ethylene glycol from the plasma in both humans and laboratory animals is rapid after oral exposure; elimination half-lives are in the range of 1-4 hours in most species tested.

Respiratory Effects. Respiratory system involvement occurs 12-24 hours after ingestion of sufficient amounts of ethylene glycol and is considered to be part of a second stage in ethylene glycol poisoning The symptoms include hyperventilation, shallow rapid breathing, and generalized pulmonary edema with calcium oxalate crystals occasionally present in the lung parenchyma. Respiratory system involvement appears to be dose-dependent and occurs concomitantly with cardiovascular changes. Pulmonary infiltrates and other changes compatible with adult respiratory distress syndrome (ARDS) may characterise the second stage of ethylene glycol poisoning Pulmonary oedema can be secondary to cardiac failure, ARDS, or aspiration of gastric contents. Symptoms related to acidosis such as hyperpnea and tachypnea are frequently observed; however, major respiratory morbidities such as pulmonary edema and bronchopneumonia are relatively rare and usually only observed with extreme poisoning (e.g., in only 5 of 36 severely poisoned cases).

Cardiovascular Effects. Cardiovascular system involvement in humans occurs at the same time as respiratory system involvement, during the second phase of oral ethylene glycol poisoning, which is 12-24 hours after acute exposure. The symptoms of cardiac involvement include tachycardia, ventricular gallop and cardiac enlargement. Ingestion of ethylene glycol may also cause hypertension or hypotension, which may progress to cardiogenic shock. Myocarditis has been observed at autopsy in cases of people who died following acute ingestion of ethylene glycol. As in the case of respiratory effects, cardiovascular involvement occurs with ingestion of relatively high doses of ethylene glycol. Nevertheless, circulatory disturbances are a rare occurrence, having been reported in only 8 of 36 severely poisoned cases. Therefore, it appears that acute exposure to high levels of ethylene glycol can cause serious cardiovascular effects in humans. The effects of a long-term, low-dose

Gastrointestinal Effects. Nausea, vomiting with or without blood, pyrosis, and abdominal cramping and pain are common early effects of acute ethylene glycol ingestion. Acute effects of ethylene glycol ingestion in one patient included intermittent diarrhea and abdominal pain, which were attributed to mild colonic ischaemia; severe abdominal pain secondary to colonic stricture and perforation developed 3 months after ingestion, and histology of the resected colon showed birefringent crystals highly suggestive of oxalate deposition.

Musculoskeletal Effects. Reported musculoskeletal effects in cases of acute ethylene glycol poisoning have included diffuse muscle tenderness and myalgias associated with elevated serum creatinine phosphokinase levels, and myoclonic jerks and tetanic contractions associated with

Hepatic Effects. Central hydropic or fatty degeneration, parenchymal necrosis, and calcium oxalate crystals in the liver have been observed at autopsy in cases of people who died following acute ingestion of ethylene glycol.

Renal Effects. Adverse renal effects after ethylene glycol ingestion in humans can be observed during the third stage of ethylene glycol toxicity 24-72 hours after acute exposure. The hallmark of renal toxicity is the presence of birefringent calcium oxalate monohydrate crystals deposited in renal tubules and their presence in urine after ingestion of relatively high amounts of ethylene glycol. Other signs of nephrotoxicity can include tubular cell degeneration and necrosis and tubular interstitial inflammation. If untreated, the degree of renal damage caused by high doses of ethylene glycol progresses and leads to haematuria, proteinuria, decreased renal function, oliguria, anuria, and ultimately renal failure. These changes in the kidney are linked to acute tubular necrosis but normal or near normal renal function can return with adequate supportive therapy. Metabolic Effects. One of the major adverse effects following acute oral exposure of humans to ethylene glycol involves metabolic changes.

ETHYLENE CARBONATE

Chemwatch: 5511-48 Page 10 of 15

Version No: 2.1

Li-ion Rechargeable Battery - NL1834R

Issue Date: 19/11/2021 Print Date: 22/11/2021

These changes occur as early as 12 hours after ethylene glycol exposure. Ethylene glycol intoxication is accompanied by metabolic acidosis which is manifested by decreased pH and bicarbonate content of serum and other bodily fluids caused by accumulation of excess glycolic acid. Other characteristic metabolic effects of ethylene glycol poisoning are increased serum anion gap, increased osmolal gap, and hypocalcaemia. Serum anion gap is calculated from concentrations of sodium, chloride, and bicarbonate, is normally 12-16 mM, and is typically elevated after ethylene glycol ingestion due to increases in unmeasured metabolite anions (mainly glycolate).

Neurological Effects: Adverse neurological reactions are among the first symptoms to appear in humans after ethylene glycol ingestion. These early neurotoxic effects are also the only symptoms attributed to unmetabolised ethylene glycol. Together with metabolic changes, they occur during the period of 30 minutes to 12 hours after exposure and are considered to be part of the first stage in ethylene glycol intoxication. In cases of acute intoxication, in which a large amount of ethylene glycol is ingested over a very short time period, there is a progression of neurological manifestations which, if not treated, may lead to generalized seizures and coma. Ataxia, slurred speech, confusion, and somnolence are common during the initial phase of ethylene glycol intoxication as are irritation, restlessness, and disorientation. Cerebral edema and crystalline deposits of calcium oxalate in the walls of small blood vessels in the brain were found at autopsy in people who died after acute ethylene glycol ingestion. Effects on cranial nerves appear late (generally 5-20 days post-ingestion), are relatively rare, and according to some investigators constitute a fourth, late cerebral phase in ethylene glycol intoxication. Clinical manifestations of the cranial neuropathy commonly involve lower motor neurons of the facial and bulbar nerves and are reversible over many months.

Reproductive Effects: Reproductive function after intermediate-duration oral exposure to ethylene glycol has been tested in three multigeneration studies (one in rats and two in mice) and several shorter studies (15-20 days in rats and mice). In these studies, effects on fertility, foetal viability, and male reproductive organs were observed in mice, while the only effect in rats was an increase in gestational duration. Developmental Effects: The developmental toxicity of ethylene glycol has been assessed in several acute-duration studies using mice, rats, and rabbits. Available studies indicate that malformations, especially skeletal malformations occur in both mice and rats exposed during gestation; mice are apparently more sensitive to the developmental effects of ethylene glycol. Other evidence of embyrotoxicity in laboratory animals exposed to ethylene glycol exposure includes reduction in foetal body weight.

Cancer: No studies were located regarding cancer effects in humans or animals after dermal exposure to ethylene glycol. Genotoxic Effects: Studies in humans have not addressed the genotoxic effects of ethylene glycol. However, available in vivo and in vitro laboratory studies provide consistently negative genotoxicity results for ethylene glycol.

MANGANESE

The material may be irritating to the eye, with prolonged contact causing inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

NICKEL & COBALT

The following information refers to contact allergens as a group and may not be specific to this product. Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. The significance of the contact allergen is not simply determined by its sensitisation potential: the distribution of the substance and the opportunities for contact with it are equally important. A weakly sensitising substance which is widely distributed can be a more important allergen than one with stronger sensitising potential with which few individuals come into contact. From a clinical point of view, substances are noteworthy if they produce an allergic test reaction in more than 1% of the persons tested.

WARNING: This substance has been classified by the IARC as Group 2B: Possibly Carcinogenic to Humans.

CARBON, ACTIVATED & LITHIUM & ALUMINIUM & LITHIUM **FLUOROPHOSPHATE &** VINYLIDENE FLUORIDE HOMOPOLYMER

No significant acute toxicological data identified in literature search.

CARBON, ACTIVATED & POLYPROPYLENE

The substance is classified by IARC as Group 3: NOT classifiable as to its carcinogenicity to humans.

Evidence of carcinogenicity may be inadequate or limited in animal testing.

LITHIUM & ETHYLENE **CARBONATE & LITHIUM FLUOROPHOSPHATE**

Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. Industrial bronchitis, on the other hand, is a disorder that occurs as result of exposure due to high concentrations of irritating substance (often particulate in nature) and is completely reversible after exposure ceases. The disorder is characterised by dyspnea, cough and mucus

ETHYLENE CARBONATE & MANGANESE

The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) and swelling epidermis. Histologically there may be intercellular oedema of the spongy layer (spongiosis) and intracellular oedema of the epidermis

Acute Toxicity	×	Carcinogenicity	✓
Skin Irritation/Corrosion	✓	Reproductivity	×
Serious Eye Damage/Irritation	✓	STOT - Single Exposure	×
Respiratory or Skin sensitisation	~	STOT - Repeated Exposure	✓
Mutagenicity	×	Aspiration Hazard	×

Leaend:

— Data either not available or does not fill the criteria for classification

- Data available to make classification

SECTION 12 Ecological information

Toxicity

Li-ion Rechargeable Battery - NL1834R	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Available
	Endpoint	Test Duration (hr)	Species	Value	Source
nickel	EC50(ECx)	72h	Algae or other aquatic plants	0.18mg/l	1

Page **11** of **15**

Li-ion Rechargeable Battery - NL1834R

Issue Date: 19/11/2021 Print Date: 22/11/2021

	EC50 LC50	72h 96h	Algae or other aquatic plants Fish	0.18mg/l 0.168mg/	1 L 4
	EC50 EC50	48h 96h	Crustacea Algae or other aquatic plants	>100mg/ 0.36mg/l	2
		3011	Algae of other aquatic plants	0.30mg/i	
	Endpoint	Test Duration (hr)	Species	Value	Sour
	NOEC(ECx)	72h	Algae or other aquatic plants	0.01-0.015mg	_l /l 1
cobalt	LC50	96h	Fish	1.512mg/l	2
	EC50	48h	Crustacea	5.89mg/l	2
	EC50	96h	Algae or other aquatic plants	23.8mg/l	2
	Endpoint	Test Duration (hr)	Species	Value	Sour
	EC50(ECx)	24h	Algae or other aquatic plants	<0.001mg/L	4
	EC50	72h	Algae or other aquatic plants	0.011-0.017mg	
copper	LC50	96h	Fish	~0.005mg/L	4
	EC50	48h	Crustacea	<0.001mg/L	4
	EC50	96h	Algae or other aquatic plants	0.03-0.058mg/l	4
		3011	Aigat of other aquatic plants	0.00 0.000mg/1	7
carbon activated	Endpoint	Test Duration (hr)	Species	Value	Sour
carbon, activated	NOEC(ECx)	72h	Algae or other aquatic plants	50mg/	L 4
	Endpoint	Test Duration (hr)	Species	Value	Sour
	NOEC(ECx)	72h	Algae or other aquatic plants	1.65mg	
lithium	EC50	72h	Algae or other aquatic plants	25.6mg	
lithium			-		2
	LC50	96h	Fish	18mg/l	
	EC50	48h	Crustacea	19.1mg	ı/l 2
	Endpoint	Test Duration (hr)	Species	Value	Sourc
polypropylene	Not Available	Not Available	Not Available	Not Available	Not Availa
	Endneint	Took Duration (hr)	Cassian	Value	Sour
	NOEC(ECx)	Test Duration (hr) 48h	Species Crustacea	Value >100mg/l	1
aluminium	EC50	72h	Algae or other aquatic plants	0.2mg/l	2
	LC50	96h	Fish	0.078-0.108mg	
	EC50	48h	Crustacea	1.5mg/l	2
	EC50	96h	Algae or other aquatic plants	0.024mg/l	2
	Endpoint	Test Duration (hr)	Species	Value	Sour
	EC50(ECx)	72h	Algae or other aquatic plants	>100mg	/l 2
ethylene carbonate	EC50	72h	Algae or other aquatic plants	>100mg	/l 2
	LC50	96h	Fish	>100mg	/l 2
	EC50	48h	Crustacea	>100mg	/I 2
	Endpoint	Test Duration (hr)	Species	Value	Sour
	NOEC(ECx)	504h	Algae or other aquatic plants	0.05-3.7mg	
man.aa.aa	EC50	72h	Algae or other aquatic plants		2
manganese	LC50	96h	Fish	2.8mg/l	2
	EC50	48h	Crustacea	>3.6mg/l >1.6mg/l	2
				- 3	
	Endpoint	Test Duration (hr)	Species	Value	
	NOEC(ECx)	528h	Fish	0.2mg	/1 2
lithium fluorophosphate	EC50	72h	Algae or other aquatic plants	62mg	
	LC50	96h	Fish	42mg	
	EC50	48h	Crustacea	98mg	1 2
	EC50	96h	Algae or other aquatic plants	43mg	1 2
	Endpoint	Test Duration (hr)	Species	Value	Sourc
vinylidene fluoride	Not		·	Not	Not
homopolymer	Available	Not Available	Not Available	Available	

Li-ion Rechargeable Battery - NL1834R

Issue Date: 19/11/2021 Print Date: 22/11/2021

DO NOT discharge into sewer or waterways.

Persistence and degradability

Version No: 2.1

Ingredient	Persistence: Water/Soil	Persistence: Air
polypropylene	LOW	LOW
ethylene carbonate	HIGH	HIGH
vinylidene fluoride homopolymer	LOW	LOW

Bioaccumulative potential

Ingredient	Bioaccumulation
polypropylene	LOW (LogKOW = 1.6783)
ethylene carbonate	LOW (LogKOW = -0.3388)
vinylidene fluoride homopolymer	LOW (LogKOW = 1.24)

Mobility in soil

Ingredient	Mobility
polypropylene	LOW (KOC = 23.74)
ethylene carbonate	LOW (KOC = 9.168)
vinylidene fluoride homopolymer	LOW (KOC = 35.04)

SECTION 13 Disposal considerations

Waste treatment methods

Product / Packaging disposal

Pick up and transfer to properly labeled containers.

- ▶ Recycle wherever possible or consult manufacturer for recycling options.
- ► Consult State Land Waste Management Authority for disposal.
- ▶ Bury residue in an authorised landfill.
- Recycle containers if possible, or dispose of in an authorised landfill.

SECTION 14 Transport information

Labels Required



Marine Pollutant	NO
HAZCHEM	2Y

Land transport (ADG)

UN number	3480	
UN proper shipping name	LITHIUM ION BATTERIES (including lithium ion polymer batteries)	
Transport hazard class(es)	Class 9 Subrisk Not Applicable	
Packing group	Not Applicable	
Environmental hazard	Not Applicable	
Special precautions for user	Special provisions 188 230 310 348 376 377 384 387 390 Limited quantity 0	

Air transport (ICAO-IATA / DGR)

• `	•			
UN number	3480			
UN proper shipping name	Lithium ion batteries (inc	Lithium ion batteries (including lithium ion polymer batteries)		
Transport hazard class(es)	ICAO/IATA Class ICAO / IATA Subrisk ERG Code	ICAO / IATA Subrisk Not Applicable		
Packing group	Not Applicable			
Environmental hazard	Not Applicable			
Special precautions for user	Special provisions Cargo Only Packing Ir	nstructions	A88 A99 A154 A164 A183 A201 A206 A213 A331 A334 A802 See 965	

Li-ion Rechargeable Battery - NL1834R

Issue Date: 19/11/2021 Print Date: 22/11/2021

Cargo Only Maximum Qty / Pack

Passenger and Cargo Packing Instructions

Passenger and Cargo Maximum Qty / Pack

Passenger and Cargo Limited Quantity Packing Instructions

Passenger and Cargo Limited Maximum Qty / Pack

Forbidden

Passenger and Cargo Limited Maximum Qty / Pack

Forbidden

Sea transport (IMDG-Code / GGVSee)

UN number	3480	
UN proper shipping name	LITHIUM ION BATTER	IES (including lithium ion polymer batteries)
Transport hazard class(es)	IMDG Class 9 IMDG Subrisk No	ot Applicable
Packing group	Not Applicable	
Environmental hazard	Not Applicable	
Special precautions for user	EMS Number Special provisions Limited Quantities	F-A , S-I 188 230 310 348 376 377 384 387 0

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
nickel	Not Available
cobalt	Not Available
copper	Not Available
carbon, activated	Not Available
lithium	Not Available
polypropylene	Not Available
aluminium	Not Available
ethylene carbonate	Not Available
manganese	Not Available
lithium fluorophosphate	Not Available
vinylidene fluoride homopolymer	Not Available

Transport in bulk in accordance with the ICG Code

Product name	Ship Type
nickel	Not Available
cobalt	Not Available
copper	Not Available
carbon, activated	Not Available
lithium	Not Available
polypropylene	Not Available
aluminium	Not Available
ethylene carbonate	Not Available
manganese	Not Available
lithium fluorophosphate	Not Available
vinylidene fluoride homopolymer	Not Available

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

nickel is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals
Australian Inventory of Industrial Chemicals (AIIC)
Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 2B: Possibly carcinogenic to humans

cobalt is found on the following regulatory lists

Chemwatch: 5511-48 Page 14 of 15

Version No: 2.1

Issue Date: 19/11/2021 Print Date: 22/11/2021 Li-ion Rechargeable Battery - NL1834R

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) -Schedule 4

Australian Inventory of Industrial Chemicals (AIIC)

Chemical Footprint Project - Chemicals of High Concern List

FEI Equine Prohibited Substances List - Controlled Medication

FEI Equine Prohibited Substances List (EPSL)

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 2B: Possibly carcinogenic to humans

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) -

copper is found on the following regulatory lists

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) -Schedule 4

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) -Schedule 5

Australian Inventory of Industrial Chemicals (AIIC)

carbon, activated is found on the following regulatory lists

Australian Inventory of Industrial Chemicals (AIIC)

lithium is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) -Schedule 2

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) -Schedule 4

Australian Inventory of Industrial Chemicals (AIIC)

FEI Equine Prohibited Substances List - Banned Substances

FEI Equine Prohibited Substances List (EPSL)

polypropylene is found on the following regulatory lists

Australian Inventory of Industrial Chemicals (AIIC)

Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

aluminium is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals

Australian Inventory of Industrial Chemicals (AIIC)

ethylene carbonate is found on the following regulatory lists

Australian Inventory of Industrial Chemicals (AIIC)

manganese is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals

Australian Inventory of Industrial Chemicals (AIIC)

lithium fluorophosphate is found on the following regulatory lists

Australian Inventory of Industrial Chemicals (AIIC)

vinylidene fluoride homopolymer is found on the following regulatory lists

Australian Inventory of Industrial Chemicals (AIIC)

National Inventory Status

National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	Yes
Canada - DSL	No (lithium fluorophosphate)
Canada - NDSL	No (nickel; cobalt; copper; carbon, activated; lithium; polypropylene; aluminium; ethylene carbonate; manganese; vinylidene fluoride homopolymer)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	No (polypropylene; vinylidene fluoride homopolymer)
Japan - ENCS	No (nickel; cobalt; copper; carbon, activated; lithium; aluminium; manganese; lithium fluorophosphate)
Korea - KECI	Yes
New Zealand - NZIoC	No (lithium fluorophosphate)
Philippines - PICCS	Yes
USA - TSCA	Yes
Taiwan - TCSI	Yes
Mexico - INSQ	No (ethylene carbonate; lithium fluorophosphate; vinylidene fluoride homopolymer)
Vietnam - NCI	Yes
Russia - FBEPH	No (lithium fluorophosphate)
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

SECTION 16 Other information

Revision Date	19/11/2021
Initial Date	19/11/2021

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or

Chemwatch: **5511-48** Page **15** of **15**

Version No: 2.1

Li-ion Rechargeable Battery - NL1834R

Issue Date: 19/11/2021 Print Date: 22/11/2021

other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

 ${\sf PC-TWA: Permissible \ Concentration-Time \ Weighted \ Average}$

PC-STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit。

IDLH: Immediately Dangerous to Life or Health Concentrations

ES: Exposure Standard
OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value BCF: BioConcentration Factors

BEI: Biological Exposure Index AIIC: Australian Inventory of Industrial Chemicals

DSL: Domestic Substances List

NDSL: Non-Domestic Substances List

IECSC: Inventory of Existing Chemical Substance in China

EINECS: European INventory of Existing Commercial chemical Substances

ELINCS: European List of Notified Chemical Substances

NLP: No-Longer Polymers

ENCS: Existing and New Chemical Substances Inventory

KECI: Korea Existing Chemicals Inventory NZIoC: New Zealand Inventory of Chemicals

PICCS: Philippine Inventory of Chemicals and Chemical Substances

TSCA: Toxic Substances Control Act
TCSI: Taiwan Chemical Substance Inventory

INSQ: Inventario Nacional de Sustancias Químicas

NCI: National Chemical Inventory

FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.