

High Performance Rechargeable Battery - NL2140 TSA OUTDOORS

Chemwatch Hazard Alert Code: 3

Issue Date: 01/12/2021 Print Date: 21/06/2022 L.GHS.AUS.EN.E

Chemwatch: **5515-04**Version No: **2.1**Safety Data Sheet according to WHS Regulations (Hazardous Chemicals) Amendment 2020 and ADG requirements

SECTION 1 Identification of the substance / mixture and of the company / undertaking

Product Identifier			
Product name	High Performance Rechargeable Battery - NL2140		
Chemical Name	ot Applicable		
Synonyms	ating: 3.6V, 4000mAh, 14.4Wh, Weight: Approx. 72.8g		
Proper shipping name	LITHIUM ION BATTERIES (including lithium ion polymer batteries)		
Chemical formula	Not Applicable		
Other means of identification	Not Available		

Relevant identified uses of the substance or mixture and uses advised against

are stored in sealed case. The toxic properties of the electrode materials are hazardous only if f exposed to fire. The sealed battery is not hazardous in normal use. The chemical hazards

Details of the supplier of the safety data sheet

Registered company name	TSA OUTDOORS	
Address	it 6/ 9 - 13 Winbourne Road Brookvale NSW 2100 Australia	
Telephone	2 9938 3244	
Fax	61 2 9939 2972	
Website	Tsaoutdoors.com.au	
Email	sales@tasco.com.au	

Emergency telephone number

Association / Organisation	Aaron Millard	
Emergency telephone numbers	+61 450 086 593 (Mon-Fri, 9 am-6pm)	
Other emergency telephone numbers	Not Available	

SECTION 2 Hazards identification

Classification of the substance or mixture

Poisons Schedule	Not Applicable	
Classification ^[1]	Acute Toxicity (Oral) Category 4, Skin Corrosion/Irritation Category 1B, Sensitisation (Skin) Category 1, Serious Eye Damage/Eye Irritation Category 1, Sensitisation (Respiratory) Category 1, Specific Target Organ Toxicity - Single Exposure (Respiratory Tract Irritation) Category 3, Carcinogenicity Category 1B, Specific Target Organ Toxicity - Repeated Exposure Category 2, Hazardous to the Aquatic Environment Long-Term Hazard Category 4	
Legend:	1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI	

Label elements

Hazard pictogram(s)







Signal word	Dang
-------------	------

Hazard statement(s)

nazaru statement(s)	
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.

Chemwatch: 5515-04 Page 2 of 10 Issue Date: 01/12/2021 Version No: 2.1 Print Date: 21/06/2022

High Performance Rechargeable Battery - NL2140

H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.		
H335	May cause respiratory irritation.		
H350	May cause cancer.		
H373	May cause damage to organs through prolonged or repeated exposure.		
HA13	May cause long lasting harmful effects to aquatic life		

Precautionary statement(s) Prevention

P201	Obtain special instructions before use.	
P260	o not breathe dust/fume.	
P264	ash all exposed external body areas thoroughly after handling.	
P271	e only outdoors or in a well-ventilated area.	
P280	Vear protective gloves, protective clothing, eye protection and face protection.	
P284	[In case of inadequate ventilation] wear respiratory protection.	
P270	P270 Do not eat, drink or smoke when using this product.	
P273	Avoid release to the environment.	
P272	P272 Contaminated work clothing should not be allowed out of the workplace.	

Precautionary statement(s) Response

· · · · · · · · · · · · · · · · · · ·			
P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.		
P303+P361+P353	F ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].		
P304+P340	F INHALED: Remove person to fresh air and keep comfortable for breathing.		
P305+P351+P338	F IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.		
P308+P313	F exposed or concerned: Get medical advice/ attention.		
P310	Immediately call a POISON CENTER/doctor/physician/first aider.		
P342+P311	If experiencing respiratory symptoms: Call a POISON CENTER/doctor/physician/first aider.		
P302+P352	IF ON SKIN: Wash with plenty of water and soap.		
P363	Wash contaminated clothing before reuse.		
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.		
P362+P364	Take off contaminated clothing and wash it before reuse.		
P301+P312	IF SWALLOWED: Call a POISON CENTER/doctor/physician/first aider if you feel unwell.		

Precautionary statement(s) Storage

P405	Store locked up.	
P403+P233	Store in a well-ventilated place. Keep container tightly closed.	

Precautionary statement(s) Disposal

P501 Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

Not Applicable

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
Not Available		sealed metal case containing
12190-79-3	35	lithium cobaltate
7429-90-5	10	aluminium
7782-42-5	25	graphite
Not Available	15	copper foil.
21324-40-3	12	lithium fluorophosphate
Not Available	3	other.
Legend:	1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. Classification drawn from C&L * EU IOEL's available	

SECTION 4 First aid measures

Description of first aid measures

► Generally not applicable. If this product comes in contact with the eyes:

Eye Contact

Immediately hold eyelids apart and flush the eye continuously with running water.

Chemwatch: 5515-04 Page 3 of 10 Issue Date: 01/12/2021 Version No: 2.1 Print Date: 21/06/2022

High Performance Rechargeable Battery - NL2140

	 Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. Transport to hospital or doctor without delay. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	 Generally not applicable. If skin contact occurs: Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.
Inhalation	 If fumes or combustion products are inhaled remove from contaminated area. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Transport to hospital, or doctor, without delay.
Ingestion	 Not considered a normal route of entry. For advice, contact a Poisons Information Centre or a doctor at once. Urgent hospital treatment is likely to be needed. If swallowed do NOT induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Observe the patient carefully. Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. Transport to hospital or doctor without delay.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 Firefighting measures

Extinguishing media

- ▶ There is no restriction on the type of extinguisher which may be used.
- Use extinguishing media suitable for surrounding area.

Special hazards arising from the substrate or mixture

Fire Incompatibility	Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result
Advice for firefighters	
Fire Fighting	 Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves in the event of a fire. Prevent, by any means available, spillage from entering drains or water courses. Use fire fighting procedures suitable for surrounding area. DO NOT approach containers suspected to be hot. Cool fire exposed containers with water spray from a protected location. If safe to do so, remove containers from path of fire. Equipment should be thoroughly decontaminated after use.
	 Non combustible. Not considered a significant fire risk, however containers may burn. Decomposition may produce toxic fumes of:

Fire/Explosion Hazard

carbon dioxide (CO2)

fluorides

phosphorus oxides (POx)

metal oxides

other pyrolysis products typical of burning organic material.

HAZCHEM

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	 Clean up all spills immediately. Secure load if safe to do so. Bundle/collect recoverable product. Collect remaining material in containers with covers for disposal.
Major Spills	 Clean up all spills immediately. Wear protective clothing, safety glasses, dust mask, gloves. Secure load if safe to do so. Bundle/collect recoverable product. Use dry clean up procedures and avoid generating dust. Vacuum up (consider explosion-proof machines designed to be grounded during storage and use). Water may be used to prevent dusting. Collect remaining material in containers with covers for disposal. Flush spill area with water.

Version No: 2.1

Issue Date: 01/12/2021 Print Date: 21/06/2022

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling

Before handling the batteries, the users should read the product specification carefully. Do not crush, pierce the battery terminals with conductive goods. Not directly heat or solder. Do not throw in fire. Do not mix batteries of different types. Do not mix new and used batteries. Keep batteries in non-conductive trays.

- Limit all unnecessary personal contact.
- Wear protective clothing when risk of exposure occurs.
- Safe handling ▶ Use in a well-ventilated area.
 - When handling DO NOT eat, drink or smoke.
 - Always wash hands with soap and water after handling.
 - Avoid physical damage to containers.
 - Use good occupational work practice.
 - ▶ Observe manufacturer's storage and handling recommendations contained within this SDS.

High Performance Rechargeable Battery - NL2140

- ► Store away from incompatible materials.
 - Keep dry.
- Other information
- Store under cover.
- Protect containers against physical damage. Observe manufacturer's storage and handling recommendations contained within this SDS.

Keep out of reach of children.

Store out of direct sunlight

Conditions for safe storage, including any incompatibilities

Suitable container

Keep batteries in original packaging until use.

Packaging as recommended by manufacturer. Avoid reaction with oxidising agents

Storage incompatibility

Avoid strong bases.

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Australia Exposure Standards	aluminium	Aluminium (welding fumes) (as Al)	5 mg/m3	Not Available	Not Available	Not Available
Australia Exposure Standards	aluminium	Aluminium, pyro powders (as Al)	5 mg/m3	Not Available	Not Available	Not Available
Australia Exposure Standards	aluminium	Aluminium (metal dust)	10 mg/m3	Not Available	Not Available	Not Available
Australia Exposure Standards	graphite	Graphite (all forms except fibres) (respirable dust) (natural & synthetic)	3 mg/m3	Not Available	Not Available	(e) Containing no asbestos and < 1% crystalline silica.

Emergency Limits

Ingredient	TEEL-1	TEEL-2	TEEL-3
graphite	6 mg/m3	330 mg/m3	2,000 mg/m3
lithium fluorophosphate	7.5 mg/m3	83 mg/m3	500 mg/m3

Ingredient	Original IDLH	Revised IDLH
lithium cobaltate	Not Available	Not Available
aluminium	Not Available	Not Available
graphite	1,250 mg/m3	Not Available
lithium fluorophosphate	Not Available	Not Available

Occupational Exposure Banding

Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit	
lithium cobaltate	E	≤ 0.01 mg/m³	
lithium fluorophosphate	E	≤ 0.01 mg/m³	
Notes:	Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.		

MATERIAL DATA

Exposure controls

Appropriate engineering	j
controls	š

General exhaust is adequate under normal operating conditions. Provide adequate ventilation in warehouse or closed storage areas. Version No: 2.1 High Performance Rechargeable Battery - NL2140

Issue Date: 01/12/2021 Print Date: 21/06/2022

Personal protection None under normal operating conditions. Eye and face protection OTHERWISE: Safety glasses. Skin protection See Hand protection below None under normal operating conditions.

Hands/feet protection

OTHERWISE:

Wear chemical protective gloves, e.g. PVC. ▶ Wear safety footwear or safety gumboots, e.g. Rubber

None under normal operating conditions.

Body protection See Other protection below

OTHERWISE: Overalls.

Other protection

- PVC Apron.
- ▶ PVC protective suit may be required if exposure severe.
- Eyewash unit.

Not Applicable

▶ Ensure there is ready access to a safety shower.

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

information on basic physical	normation on basic physical and chemical properties				
Appearance	Yellow colour hermetically sealed solid object; immiscible with water.				
Physical state	Manufactured	Relative density (Water = 1)	Not Applicable		
Odour	Not Available	Partition coefficient n-octanol / water	Not Available		
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Applicable		
pH (as supplied)	Not Applicable	Decomposition temperature	Not Applicable		
Melting point / freezing point (°C)	Not Applicable	Viscosity (cSt)	Not Applicable		
Initial boiling point and boiling range (°C)	Not Applicable	Molecular weight (g/mol)	Not Applicable		
Flash point (°C)	Not Applicable	Taste	Not Available		
Evaporation rate	Not Applicable	Explosive properties	Not Available		
Flammability	Not Applicable	Oxidising properties	Not Available		
Upper Explosive Limit (%)	Not Applicable	Surface Tension (dyn/cm or mN/m)	Not Applicable		
Lower Explosive Limit (%)	Not Applicable	Volatile Component (%vol)	Not Applicable		
Vapour pressure (kPa)	Not Applicable	Gas group	Not Available		
Solubility in water	Immiscible	pH as a solution (Not Available%)	Not Applicable		

SECTION 10 Stability and reactivity

Vapour density (Air = 1)

Reactivity	See section 7	
Chemical stability	Product is considered stable and hazardous polymerisation will not occur.	
Possibility of hazardous reactions	See section 7	
Conditions to avoid	See section 7	
Incompatible materials	See section 7	
Hazardous decomposition products	See section 5	

SECTION 11 Toxicological information

Information on toxicological effects

Vapor generated from burning batteries may cause throat irritation. Not normally a hazard due to physical form of product.

Inhaled

Acidic corrosives produce respiratory tract irritation with coughing, choking and mucous membrane damage. Symptoms of exposure may include dizziness, headache, nausea and weakness. In more severe exposures, pulmonary oedema may be evident either immediately or after a latent period of 5-72 hours. Symptoms of pulmonary oedema include a tightness in the chest, dyspnoea, frothy sputum and cyanosis. Examination may reveal hypotension, a weak and rapid pulse and moist rates. Death, due to anoxia, may occur several hours after onset of the pulmonary oedema

VOC g/L

Not Applicable

Chemwatch: 5515-04 Page 6 of 10 Issue Date: 01/12/2021 Version No: 2.1

High Performance Rechargeable Battery - NL2140

Print Date: 21/06/2022

Ingestion	Ingestion of the smaller size batteries can be harmful. Contents of an open battery can cause serious chemical burns of mouth, esophagus and gastrointestinal tract. Not normally a hazard due to physical form of product. Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual.			
Skin Contact	Contents of an opened battery can cause moderate irritation and chemical burns. Not normally a hazard due to physical form of product. Entry into the blood-stream through, for example, cuts, abrasions, puncture wounds or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.			
Eye	Contents of an opened battery can cause severe irritation and possible corneal burns. Not normally a hazard due to physical form of product.			
Chronic	Under normal conditions of use the battery is hermetically Contents of a cell if opened destructively and swallowed of and gastrointestinal tract. Potassium hydroxide (KOH) is content and gastrointestinal tract. Potassium hydroxide (KOH) is content and the practical experience shows that skin contact with the materindividuals, and/or of producing a positive response in exp Substances that can cause occupational asthma (also known hyper-responsiveness via an immunological, irritant or other the substance, sometimes even to tiny quantities, may caus asthma. Not all workers who are exposed to a sensitiser who become hyper-responsive. Substances than can cuase occupational asthma should be with pre-existing air-way hyper-responsiveness. The latter Wherever it is reasonably practicable, exposure to substant possible the primary aim is to apply adequate standards of Activities giving rise to short-term peak concentrations show surveillance is appropriate for all employees exposed or lies should be appropriate consultation with an occupational here.	erial is capable either of inducing a sensitisation reaction in a substantial number of perimental animals. In a sasthmagens and respiratory sensitisers) can induce a state of specific airway er mechanism. Once the airways have become hyper-responsive, further exposure to use respiratory symptoms. These symptoms can range in severity from a runny nose to rill become hyper-responsive and it is impossible to identify in advance who are likely to be distinguished from substances which may trigger the symptoms of asthma in people substances are not classified as asthmagens or respiratory sensitisers notes that can cuase occupational asthma should be prevented. Where this is not for control to prevent workers from becoming hyper-responsive. Build receive particular attention when risk management is being considered. Health able to be exposed to a substance which may cause occupational asthma and there ealth professional over the degree of risk and level of surveillance.		
	Harmful: danger of serious damage to health by prolonged Serious damage (clear functional disturbance or morpholo repeated or prolonged exposure. As a rule the material pro	ntly exists inadequate data for making a satisfactory assessment. d exposure through inhalation, in contact with skin and if swallowed. gical change which may have toxicological significance) is likely to be caused by oduces, or contains a substance which produces severe lesions. Such damage may c (90 day) toxicity studies or following sub-acute (28 day) or chronic (two-year) toxicity		
High Performance	Harmful: danger of serious damage to health by prolonged Serious damage (clear functional disturbance or morpholo repeated or prolonged exposure. As a rule the material probecome apparent following direct application in subchronic tests.	d exposure through inhalation, in contact with skin and if swallowed. gical change which may have toxicological significance) is likely to be caused by oduces, or contains a substance which produces severe lesions. Such damage may c (90 day) toxicity studies or following sub-acute (28 day) or chronic (two-year) toxicity		
High Performance Rechargeable Battery - NL2140	Harmful: danger of serious damage to health by prolonged Serious damage (clear functional disturbance or morpholo repeated or prolonged exposure. As a rule the material probecome apparent following direct application in subchronic	d exposure through inhalation, in contact with skin and if swallowed. Igical change which may have toxicological significance) is likely to be caused by oduces, or contains a substance which produces severe lesions. Such damage may		
Rechargeable Battery -	Harmful: danger of serious damage to health by prolonged Serious damage (clear functional disturbance or morpholo repeated or prolonged exposure. As a rule the material probecome apparent following direct application in subchronic tests.	d exposure through inhalation, in contact with skin and if swallowed. gical change which may have toxicological significance) is likely to be caused by oduces, or contains a substance which produces severe lesions. Such damage may c (90 day) toxicity studies or following sub-acute (28 day) or chronic (two-year) toxicity		
Rechargeable Battery -	Harmful: danger of serious damage to health by prolonged Serious damage (clear functional disturbance or morpholo repeated or prolonged exposure. As a rule the material probecome apparent following direct application in subchronic tests. TOXICITY Not Available TOXICITY	d exposure through inhalation, in contact with skin and if swallowed. gical change which may have toxicological significance) is likely to be caused by oduces, or contains a substance which produces severe lesions. Such damage may c (90 day) toxicity studies or following sub-acute (28 day) or chronic (two-year) toxicity IRRITATION Not Available		
Rechargeable Battery -	Harmful: danger of serious damage to health by prolonged Serious damage (clear functional disturbance or morpholo repeated or prolonged exposure. As a rule the material probecome apparent following direct application in subchronic tests. TOXICITY Not Available TOXICITY dermal (rat) LD50: >2000 mg/kg ^[1]	d exposure through inhalation, in contact with skin and if swallowed. gical change which may have toxicological significance) is likely to be caused by oduces, or contains a substance which produces severe lesions. Such damage may c (90 day) toxicity studies or following sub-acute (28 day) or chronic (two-year) toxicity IRRITATION Not Available IRRITATION		
Rechargeable Battery - NL2140	Harmful: danger of serious damage to health by prolonged Serious damage (clear functional disturbance or morpholo repeated or prolonged exposure. As a rule the material probecome apparent following direct application in subchronic tests. TOXICITY Not Available TOXICITY	d exposure through inhalation, in contact with skin and if swallowed. gical change which may have toxicological significance) is likely to be caused by oduces, or contains a substance which produces severe lesions. Such damage may c (90 day) toxicity studies or following sub-acute (28 day) or chronic (two-year) toxicity IRRITATION Not Available IRRITATION		
Rechargeable Battery - NL2140	Harmful: danger of serious damage to health by prolonged Serious damage (clear functional disturbance or morpholo repeated or prolonged exposure. As a rule the material probecome apparent following direct application in subchronic tests. TOXICITY Not Available TOXICITY dermal (rat) LD50: >2000 mg/kg ^[1] Inhalation(Rat) LC50; 5.05 mg/l4h ^[1]	d exposure through inhalation, in contact with skin and if swallowed. gical change which may have toxicological significance) is likely to be caused by oduces, or contains a substance which produces severe lesions. Such damage may c (90 day) toxicity studies or following sub-acute (28 day) or chronic (two-year) toxicity IRRITATION Not Available IRRITATION		
Rechargeable Battery - NL2140	Harmful: danger of serious damage to health by prolonged Serious damage (clear functional disturbance or morpholo repeated or prolonged exposure. As a rule the material probecome apparent following direct application in subchronic tests. TOXICITY Not Available TOXICITY dermal (rat) LD50: >2000 mg/kg[1] Inhalation(Rat) LC50; 5.05 mg/l4h[1] Oral (Rat) LD50; >5000 mg/kg[1]	d exposure through inhalation, in contact with skin and if swallowed. gical change which may have toxicological significance) is likely to be caused by oduces, or contains a substance which produces severe lesions. Such damage may c (90 day) toxicity studies or following sub-acute (28 day) or chronic (two-year) toxicity IRRITATION Not Available IRRITATION Not Available IRRITATION		
Rechargeable Battery - NL2140 lithium cobaltate	Harmful: danger of serious damage to health by prolonged Serious damage (clear functional disturbance or morpholo repeated or prolonged exposure. As a rule the material probecome apparent following direct application in subchronic tests. TOXICITY Not Available TOXICITY dermal (rat) LD50: >2000 mg/kg ^[1] Inhalation(Rat) LC50; 5.05 mg/l4hl ^[1] Oral (Rat) LD50; >5000 mg/kg ^[1]	d exposure through inhalation, in contact with skin and if swallowed. gical change which may have toxicological significance) is likely to be caused by oduces, or contains a substance which produces severe lesions. Such damage may c (90 day) toxicity studies or following sub-acute (28 day) or chronic (two-year) toxicity IRRITATION Not Available IRRITATION Not Available		
Rechargeable Battery - NL2140 lithium cobaltate	Harmful: danger of serious damage to health by prolonged Serious damage (clear functional disturbance or morpholo repeated or prolonged exposure. As a rule the material probecome apparent following direct application in subchronic tests. TOXICITY Not Available TOXICITY dermal (rat) LD50: >2000 mg/kg ^[1] Inhalation(Rat) LC50; 5.05 mg/l4h ^[1] Oral (Rat) LD50: >5000 mg/kg ^[1] TOXICITY Inhalation(Rat) LC50; >2.3 mg/l4h ^[1]	d exposure through inhalation, in contact with skin and if swallowed. Ingical change which may have toxicological significance) is likely to be caused by oduces, or contains a substance which produces severe lesions. Such damage may be (90 day) toxicity studies or following sub-acute (28 day) or chronic (two-year) toxicity IRRITATION Not Available IRRITATION Not Available IRRITATION Eye: no adverse effect observed (not irritating)[1]		
Rechargeable Battery - NL2140 lithium cobaltate	Harmful: danger of serious damage to health by prolonged Serious damage (clear functional disturbance or morpholo repeated or prolonged exposure. As a rule the material probecome apparent following direct application in subchronic tests. TOXICITY Not Available TOXICITY dermal (rat) LD50: >2000 mg/kg ^[1] Inhalation(Rat) LC50; 5.05 mg/l4h ^[1] Oral (Rat) LD50; >5000 mg/kg ^[1] TOXICITY Inhalation(Rat) LC50; >2.3 mg/l4h ^[1] Oral (Rat) LD50; >2000 mg/kg ^[1]	d exposure through inhalation, in contact with skin and if swallowed. gical change which may have toxicological significance) is likely to be caused by oduces, or contains a substance which produces severe lesions. Such damage may of (90 day) toxicity studies or following sub-acute (28 day) or chronic (two-year) toxicity IRRITATION Not Available IRRITATION Not Available IRRITATION Eye: no adverse effect observed (not irritating) ^[1] Skin: no adverse effect observed (not irritating) ^[1]		
Rechargeable Battery - NL2140 lithium cobaltate aluminium	Harmful: danger of serious damage to health by prolonged Serious damage (clear functional disturbance or morpholo repeated or prolonged exposure. As a rule the material probecome apparent following direct application in subchronic tests. TOXICITY Not Available TOXICITY dermal (rat) LD50: >2000 mg/kg ^[1] Inhalation(Rat) LC50; 5.05 mg/l4hl ^[1] Oral (Rat) LD50; >5000 mg/kg ^[1] TOXICITY Inhalation(Rat) LC50; >2.3 mg/l4hl ^[1] Oral (Rat) LD50; >2000 mg/kg ^[1] TOXICITY Inhalation(Rat) LC50; >2000 mg/kg ^[1]	d exposure through inhalation, in contact with skin and if swallowed. gical change which may have toxicological significance) is likely to be caused by oduces, or contains a substance which produces severe lesions. Such damage may of (90 day) toxicity studies or following sub-acute (28 day) or chronic (two-year) toxicity IRRITATION Not Available IRRITATION Not Available IRRITATION Eye: no adverse effect observed (not irritating) ^[1] Skin: no adverse effect observed (not irritating) ^[1] IRRITATION IRRITATION		
Rechargeable Battery - NL2140 lithium cobaltate aluminium graphite	Harmful: danger of serious damage to health by prolonged Serious damage (clear functional disturbance or morpholo repeated or prolonged exposure. As a rule the material probecome apparent following direct application in subchronic tests. TOXICITY Not Available TOXICITY dermal (rat) LD50: >2000 mg/kg ^[1] Inhalation(Rat) LC50; 5.05 mg/l4h ^[1] Oral (Rat) LD50; >5000 mg/kg ^[1] TOXICITY Inhalation(Rat) LC50; >2.3 mg/l4h ^[1] Oral (Rat) LD50; >2000 mg/kg ^[1] TOXICITY Inhalation(Rat) LC50; >2000 mg/kg ^[1]	d exposure through inhalation, in contact with skin and if swallowed. gical change which may have toxicological significance) is likely to be caused by oduces, or contains a substance which produces severe lesions. Such damage may of (90 day) toxicity studies or following sub-acute (28 day) or chronic (two-year) toxicity IRRITATION Not Available IRRITATION Not Available IRRITATION Eye: no adverse effect observed (not irritating) ^[1] Skin: no adverse effect observed (not irritating) ^[1] IRRITATION IRRITATION		
Rechargeable Battery - NL2140 lithium cobaltate aluminium	Harmful: danger of serious damage to health by prolonged Serious damage (clear functional disturbance or morpholo repeated or prolonged exposure. As a rule the material probecome apparent following direct application in subchronic tests. TOXICITY Not Available TOXICITY dermal (rat) LD50: >2000 mg/kg ^[1] Inhalation(Rat) LC50; 5.05 mg/l4hl ^[1] Oral (Rat) LD50; >5000 mg/kg ^[1] TOXICITY Inhalation(Rat) LC50; >2.3 mg/l4hl ^[1] Oral (Rat) LD50; >2000 mg/kg ^[1] TOXICITY Inhalation(Rat) LC50; >2 mg/L4hl ^[1] Oral (Rat) LD50; >2000 mg/kg ^[1]	d exposure through inhalation, in contact with skin and if swallowed. Igical change which may have toxicological significance) is likely to be caused by oduces, or contains a substance which produces severe lesions. Such damage may be contained to produce of the contained of t		

The following information refers to contact allergens as a group and may not be specific to this product.

LITHIUM COBALTATE

Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. The significance of the contact allergen is not simply determined by its sensitisation potential: the distribution of the substance and the opportunities for contact with it are equally important. A weakly sensitising substance which is widely distributed can be a more important allergen than one with stronger sensitising potential with which few individuals come into contact. From a clinical point of view, substances are noteworthy if they produce an allergic test reaction in more than 1% of the persons tested. Allergic reactions which develop in the respiratory passages as bronchial asthma or rhinoconjunctivitis, are mostly the result of reactions of the allergen with specific antibodies of the IgE class and belong in their reaction rates to the manifestation of the immediate type. In addition to the allergen-specific potential for causing respiratory sensitisation, the amount of the allergen, the exposure period and the genetically determined disposition of the exposed person are likely to be decisive. Factors which increase the sensitivity of the mucosa may play a role in predisposing a person to allergy. They may be genetically determined or acquired, for example, during infections or exposure to irritant substances. Immunologically the low molecular weight substances become complete allergens in the organism either by binding to peptides or proteins (haptens) or after metabolism (prohaptens).

Particular attention is drawn to so-called atopic diathesis which is characterised by an increased susceptibility to allergic rhinitis, allergic bronchial asthma and atopic eczema (neurodermatitis) which is associated with increased IgE synthesis. Exogenous allergic alveolitis is induced essentially by allergen specific immune-complexes of the IgG type; cell-mediated reactions (T

lymphocytes) may be involved. Such allergy is of the delayed type with onset up to four hours following exposure.

Chemwatch: 5515-04 Page **7** of **10**

Issue Date: 01/12/2021 Version No: 2.1

High Performance Rechargeable Battery - NL2140

Print Date: 21/06/2022

Goitrogenic:.

Goitrogens are substances that suppress the function of the thyroid gland by interfering with iodine uptake, which can, as a result, cause an enlargement of the thyroid, i.e., a goitre

Goitrogens include:

- Vitexin, a flavanoid, which inhibits thyroid peroxidase thus contributing to goiter.
- Inns such as thiocyanate and perchlorate which decrease iodide uptake by competitive inhibition; as a consequence of reduced thyroxine and triiodothyronine secretion by the gland, at low doses, this causes an increased release of thyrotropin (by reduced negative feedback), which then stimulates the gland.
- Lithium which inhibits thyroid hormone release.
- Certain foods, such as soy and millet (containing vitexins) and vegetables in the genus Brassica (e.g. broccoli, brussels sprouts, cabbage, horseradish).
- Caffeine (in coffee, tea, cola, chocolate) which acts on thyroid function as a suppressant.

LITHIUM COBALTATE & ALUMINIUM & GRAPHITE & LITHIUM **FLUOROPHOSPHATE**

No significant acute toxicological data identified in literature search.

GRAPHITE & LITHIUM FLUOROPHOSPHATE

Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing, and the lack of minimal lymphocytic inflammation, without eosinophilia. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. On the other hand, industrial bronchitis is a disorder that occurs as a result of exposure due to high concentrations of irritating substance (often particles) and is completely reversible after exposure ceases. The disorder is characterized by difficulty breathing, cough and mucus production.

Acute Toxicity	~	Carcinogenicity	✓
Skin Irritation/Corrosion	✓	Reproductivity	×
Serious Eye Damage/Irritation	✓	STOT - Single Exposure	✓
Respiratory or Skin sensitisation	✓	STOT - Repeated Exposure	✓
Mutagenicity	×	Aspiration Hazard	×

Legend:

💢 – Data either not available or does not fill the criteria for classification

- Data available to make classification

SECTION 12 Ecological information

Toxicity

High Performance	Endpoint	Test Duration (hr)	Species	V	alue	Source
Rechargeable Battery - NL2140	Not Available	Not Available	Not Available		lot vailable	Not Availabl
	Endpoint	Test Duration (hr)	Species	\\	/alue	Sourc
	NOEC(ECx)	24h	Algae or other aquatic plants	C	0.025mg/l	2
lithium cobaltate	EC50	48h	Crustacea	5	5.89mg/l	2
	EC50	96h	Algae or other aquatic plants	2	23.8mg/l	2
	LC50	96h	Fish	1	I.512mg/l	2
	Endpoint	Test Duration (hr)	Species	Value		Source
	LC50	96h	Fish	0.078-0).108mg/l	2
	NOEC(ECx)	48h	Crustacea	>100mg	g/l	1
aluminium	EC50	72h	Algae or other aquatic plants 0.2mg/l			2
	EC50	48h	Crustacea 1.5mg/l			2
	EC50	96h	Algae or other aquatic plants	0.024m	ng/l	2
	Endpoint	Test Duration (hr)	Species	V	alue	Sour
	NOEC(ECx)	72h	Algae or other aquatic plants	>:	=100mg/l	2
graphite	EC50	72h	Algae or other aquatic plants	>	100mg/l	2
	EC50	48h	Crustacea	>	100mg/l	2
	LC50	96h	Fish	>	100mg/l	2
	Endpoint	Test Duration (hr)	Species		Value	Sour
	EC50	72h	Algae or other aquatic plants		62mg/l	2
list. i fl	NOEC(ECx)	528h	Fish		0.2mg/l	2
lithium fluorophosphate	EC50	48h	Crustacea		98mg/l	2
	EC50	96h	Algae or other aquatic plants		43mg/l	2
	LC50	96h	Fish		42mg/l	2

- Bioconcentration Data 8. Vendor Data

Chemwatch: 5515-04 Version No: 2.1

High Performance Rechargeable Battery - NL2140

Issue Date: 01/12/2021 Print Date: 21/06/2022

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient Persistence:	Water/Soil	Persistence: Air	
No Data avail	able for all ingredients	No Data available for all ingredients	

Bioaccumulative potential

Ingredient	Bioaccumulation
	No Data available for all ingredients

Mobility in soil

Ingredient	Mobility
	No Data available for all ingredients

SECTION 13 Disposal considerations

Waste treatment methods

Product / Packaging disposal

Pick up and transfer to properly labeled containers.

- ▶ Recycle wherever possible or consult manufacturer for recycling options.
- Consult State Land Waste Management Authority for disposal.
- Bury residue in an authorised landfill.
- ▶ Recycle containers if possible, or dispose of in an authorised landfill.

SECTION 14 Transport information

Labels Required



Marine Pollutant	NO
HAZCHEM	2Y

Land transport (ADG)

UN number	3480		
UN proper shipping name	LITHIUM ION BATTERIES (including lithium ion polymer batteries)		
Transport hazard class(es)	Class 9 Subrisk Not Applicable		
Packing group	Not Applicable		
Environmental hazard	Not Applicable		
Special precautions for user	Special provisions 188 230 310 348 376 377 384 387 390 Limited quantity 0		

Air transport (ICAO-IATA / DGR)

UN number	3480			
UN proper shipping name	Lithium ion batteries (including lithium ion polymer batteries)			
Transport hazard class(es)	ICAO/IATA Class ICAO / IATA Subrisk ERG Code	9 Not Applicable 12FZ		
Packing group	Not Applicable			
Environmental hazard	Not Applicable			
Special precautions for user		Qty / Pack Packing Instructions	A88 A99 A154 A164 A183 A201 A206 A213 A331 A334 A802 See 965 See 965 Forbidden Forbidden Forbidden	

Version No: 2.1 High Performance Rechargeable Battery - NL2140 Issue Date: 01/12/2021 Print Date: 21/06/2022

Sea transport (IMDG-Code / GGVSee)

<u> </u>				
UN number	3480			
UN proper shipping name	LITHIUM ION BATTE	LITHIUM ION BATTERIES (including lithium ion polymer batteries)		
Transport hazard class(es)	IMDG Class 9 IMDG Subrisk Not Applicable			
Packing group	Not Applicable			
Environmental hazard	Not Applicable			
Special precautions for user	EMS Number Special provisions Limited Quantities			

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
lithium cobaltate	Not Available
aluminium	Not Available
graphite	Not Available
lithium fluorophosphate	Not Available

Transport in bulk in accordance with the ICG Code

Product name	Ship Type
lithium cobaltate	Not Available
aluminium	Not Available
graphite	Not Available
lithium fluorophosphate	Not Available

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

lithium cobaltate is	found on the	following re	egulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals Australian Inventory of Industrial Chemicals (AIIC) Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 2B: Possibly carcinogenic to humans

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

aluminium is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals Australian Inventory of Industrial Chemicals (AIIC)

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

graphite is found on the following regulatory lists

Australian Inventory of Industrial Chemicals (AIIC)

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

lithium fluorophosphate is found on the following regulatory lists

Australian Inventory of Industrial Chemicals (AIIC)

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

National Inventory Status

National inventory Status	
National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	Yes
Canada - DSL	No (lithium fluorophosphate)
Canada - NDSL	No (lithium cobaltate; aluminium; graphite)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	No (aluminium; graphite; lithium fluorophosphate)
Korea - KECI	Yes
New Zealand - NZIoC	No (lithium fluorophosphate)
Philippines - PICCS	No (lithium cobaltate)
USA - TSCA	Yes
Taiwan - TCSI	Yes

Chemwatch: 5515-04 Page 10 of 10 Issue Date: 01/12/2021 Version No: 2.1 Print Date: 21/06/2022

High Performance Rechargeable Battery - NL2140

National Inventory	Status
Mexico - INSQ	No (lithium cobaltate; lithium fluorophosphate)
Vietnam - NCI	No (lithium cobaltate)
Russia - FBEPH	No (lithium cobaltate; lithium fluorophosphate)
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

SECTION 16 Other information

Revision Date	01/12/2021
Initial Date	01/12/2021

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC-TWA: Permissible Concentration-Time Weighted Average

PC-STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit。

IDLH: Immediately Dangerous to Life or Health Concentrations

ES: Exposure Standard OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level

LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value

LOD: Limit Of Detection

OTV: Odour Threshold Value

BCF: BioConcentration Factors

BEI: Biological Exposure Index AIIC: Australian Inventory of Industrial Chemicals

DSL: Domestic Substances List

NDSL: Non-Domestic Substances List

IECSC: Inventory of Existing Chemical Substance in China

EINECS: European INventory of Existing Commercial chemical Substances

ELINCS: European List of Notified Chemical Substances

NLP: No-Longer Polymers

ENCS: Existing and New Chemical Substances Inventory

KECI: Korea Existing Chemicals Inventory NZIoC: New Zealand Inventory of Chemicals

PICCS: Philippine Inventory of Chemicals and Chemical Substances

TSCA: Toxic Substances Control Act TCSI: Taiwan Chemical Substance Inventory

INSQ: Inventario Nacional de Sustancias Químicas

NCI: National Chemical Inventory

FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.